æ

GSI Job No. 2111034 A8-WM KSA 82a-1212 ID No. 00313546 WATER WELL RECORD Form WWC-5 1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number Sedgwick SW ½ SW ½ 28 27 1 County: R Distance and direction from nearest town or city street address of well if located within city? 1002 E. Lincoln Tom Mai 2 WATER WELL OWNER: 803 5<sup>th</sup> Street RR#, St. Address, Box # Board of Agriculture, Division of Water Resources Orange City, IA 51041 City, State, ZIP Code Application Number: 3 LOCATE WELL'S LOCATON WITH DEPTH OF COMPLETED WELL 23 ft. ELEVATION: 1293.27 TOC AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1 Depth(s) Groundwater Encountered 1 16.4 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 16.32 ft. below land surface measured on mo/day/yr 3-17-03 Ν Pump test data: Well water was ft. after hours pumping gpm NF Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 8.5 in. to 23 ft. and in. to ft. Bore Hole Diameter 8.5 in. to 23 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply
1 Domestic 3 Feed lot 6 Oil field water supply
9 Dewatering 12 Other (Specify below) 皇 Bore Hole Diameter 8.5 in. to W 7 Lawn and garden (domestic) 10 Monitoring well 2 Imigation 4 Industrial Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Flush 4 ABS 7 Fiberglass 12.5 ft., Dia in. to ft., Dia in. to in., weight 0.703 lbs./ft. Wall thickness or gauge No. Sch. 40 Blank casing diameter 2 in. to Casing height above land surface Flush in., weight TYPE OF SCREEN OR PERFORATION MATERIAL: 5 Fiberglass 8 RMP (SR) 11 Other (specify)
6 Concrete tile 9 ABS 12 None used (open hole)
8 Saw cut 11 Non 1 Steel 3 Stainless steel 4 Galvanized steel SCREEN OR PERFORATION OPENINGS ARE: 11 None (open hole) 3 Mill slot 6 Wire wrapped 1 Continuous slot 9 Drilled holes 10 Other (specify) 2 Louvered shutter 4 Key punched 7 Torch cut SCREEN-PERFORATED INTERVALS: 12.5 ft. to 22.5 ft. From ft. to ft. 
 From
 ft. to
 ft. From
 ft. to
 ft.

 From
 10
 ft. to
 23
 ft. From
 ft. to
 ft.
 GRAVEL PACK INTERVALS: 3 Bentonite 4 Other Concrete 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout Grout Intervals From 0 ft. to 1 ft. From 1 ft. to 10 ft. From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 15 Oil well/ Gas well 7 Pit privy 11 Fuel storage 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 13 Insecticide storage 9 Feedyard Direction from well? How many feet? FROM TO CODE LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 0.5 Concrete 0.5 Fat Clay, black 5 23 Sand, brown 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr)

3-11-03

and this record is true to the best of my knowledge and belief Kansas 531 This Water Well Record was completed on (molegay/yr) Water Well Contractor's License No.

under the business name of

Geotechnical Services, Inc.

by (signature)

INSTRUCTIONS:. Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W

Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.