WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick SWNE 32 27 т s 1E 1/4 R E/W Distance and direction from nearest town or city street address of well if located within city? 1626 S. Water Wichita, Kansas BETHANY UNITED METHODIST CHURCH WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 1626 S. Water CITY, STATE: Wichita, Kansas ZIP CODE: Application Number: 4 DEPTH OF COMPLETED WELL: 40 LOCATE WELL'S LOCATION **ELEVATION:** WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft ft. WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 5/5/03 ΝŁ Pump test data: Well water was ft. after gpm Est. Yield: apm Well water was ft. after hours of pumping @ gpm ≌ 12 to 40 Bore Hole Diameter and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering SW SF-5. Public water supply 7. Lawn and garden only 1. Domestic 3. Feedlot 12. Other (Specify below) 2. Irrigation 8. Air conditioning 10. Monitoring well 4. Industrial 6. Oil field water supply ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO submitted Was Water Well Disinfected? (YES) 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Clued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile 5 Blank casing diameter 25 in. to ft.. Dia. in. to Dia ft. in. 12 Casing height above land surface: in., Weight: 2.35 Wall thickness or gauge No. lbs. / ft. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 1. Steel 3. Stainless Steel 5. Fiberglass 9 ARS 11. Other (specify) 2 Brass 8. RMP (SR) 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 8. Saw cut 4. Key punched 10. Other (specify) SCREEN - PERFORATION INTERVAL 25 40 ft. From to ft., From to ft. From ft. to ft., From to ft. **GRAVEL PACK INTERVALS:** 24 to 40 From ft., From ft. From ft. to ft.. From ft ft **GROUT MATERIALS:** 6 Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: ft. From ft.. to ft., From ft. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 15. Oil well/Gas well 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit Direction from well? East How many feet? 20 From LITHOLOGIC LOG Τo LITHOLOGIC LOG From Τo 0 3 topsoil 3 10 clay 10 20 medium fine sand 20 38 medium sand 38 40 shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or under my jurisdiction and was completed on (mo/day/year) 5-5-2003 and this record is true to the best of my knowledge and belief. 236 Kansas Water Well Contractor's License No. This water well record was completed on (mo/day/year) 5-7-2003

under the business name of Harp Well & Pump Service Inc. by (signature) Jodd S. Harp