	WATE	R WELL	RECO	RD F	orm	ww	/C-5 K	(SA 82a-1	212		
1 LOCATION OF WATER WELL:	FRACTION					SECT	ION NUMBE	R TOWNSHIP NUMBER		RANGE NUMBER	
Sedgwick	SW	1/4 SI		NW	1/4	L	8	Т	27 S	R	1E E/W
Distance and direction from nearest town or city			ted within c	ity?							
	Vichita, I	Cansas									
— <u>1</u>	A, Betty olling Hil	lle Ct							Board of A	griculture, Division	of Water Resource
	on, Kans					715	CODE: 6	67114	Application N	umber:	
	EPTH OF		WELL:	2	6	ft.	OODL.	ELEVATION	 		
WITH AN "X" IN SECTION BOX:	th of ground					ft.			ft.		ft.
	LL'S STATI			17	FT F		W LAND S	URFACE MEA	SURED ON mo	n/dav/vr: 6	5/17/03
NWNE		Pump tes		Well wa				ft. after		irs of pumping (
	Est. Yield:	•	pm	Well wa				ft. after		irs of pumping (-
w X Bo	re Hole Dia	-	•	in.		to	ft	t. and	in.	te	o ft.
-	LL WATER	W E OSE	ED AS:						9. Dewate	ring 11.	Injection well
	Domestic	3. Feedl						and garden o			r (Specify belov
	Irrigation	4. Indus		Oil field w				nditioning	10. Monito	ri ng we ii s, wh <u>at</u> mo/day/	vr was sample
	as a chemical mitted	/bactenologic	ai sample s	submitted to t	Departm	ent?	YE \$ Was '	NO No Water Well Dis		YES	NO
TYPE OF CASING USED:	- 141	-1-1-1	-	Cib a sala a a		9 Ot	her (Specif	v below) C	ASING JOINTS	Glued	Threaded
1. Steel 3. RPM (SR	5. Wr	ought Iron	7.	Fiberglass		U. U.	nor (opcom	, 50.0,		Welded	Clamped
2. PVC 4. ABS	6. Asl	bestos-Cem	ent 8.	Concrete t	ile						
Blank casing diameter 1 1/4	ic t	0	ft.,	Dia.		in.	to	ft.,	Dia.	in. to	ft.
Casing height characters	6	in.,	٧	Veight:		lb	s. / ft.	Wall	thickness or ga	uge No.	
TYPE OF SCREEN OR PERFORATION	MATERIAL	.:								NI/A	
1. Steel 3. Stainless Steel	5. Fiber	glass	7. F	PVC		9. A	BS		Other (specify)		
2. Brass 4. Galvanized	6. Conc	rete Tile	8. F	RMP (SR)		10. A	sbestos-Ce	ement 12.	None used (ope	en hole)	
SCREEN OR PERFORATION OPENING	S ARE:										
1. Continuous slot 3. Mill slo	ot	5. Gauze	d wrappe	ed		7. Toi	rch cut	9. D	rilled holes	11. Non	e (open hole)
2. Louvered shutter 4. Key pu	inched	6. Wire v	vrapped			8. Sa v	w cut	10 . O	ther (specify)	N/A	
SCREEN - PERFORATION INTERVAL	From		ft.	to)		ft.,	From	ft.	to	ft.
	From		ft.	to)		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From		ft.	to)		ft.,	From	ft.	to	ft.
	From		ft.	to	,		ft.,	From	ft.	to	ft.
G GROUT MATERIALS: 1 Neat of										ntonite hole	
<u> </u>		. -	Cement C				. Bentonite	_			. 26
Grout Intervals: From $oldsymbol{0}$ What is the nearest source of possible co			rt.,	From		ft.	to	ft.,	From		
1. Septic tank 4. Lateral		7. Pit p	rivy	•	10. Liv e	estoci	k pens	13. Inse	cticide storage		ell/Gas well
2. Sewer lines 5. Cess P	ool	8. Sew	age lago	on	11. Fue	el stor	rage	14. Aba	ndon water we	II 16. Othe	r (specify below
3. Watertight sewer line 6. Seepag	je pit	9. Feed	i yard		12. Fer	tilizer	storage				
Direction from well? West								How	many feet? 8		
From To 1	ITHOLOGIC LOG				From To			ļ		OGIC LOG	j
				-			.5	cement gr			
	 				+	5	26	bentonite	note plug		
					 						
	,				_			<u> </u>			
					 			<u> </u>			
					+			 	 		
					\vdash						
					 			ļ			
					<u> </u>		<u> </u>	.L			
Contractor's or Landowner's Certific	ation: This	water well w	vas 1. c	onstructed	d 2	rec	constructe	od or 3.C	plugged	under my juri	sdiction and

was completed on (mo/day/year) 6-17-2003 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6-20-2003

under the business name of Harp Well & Pump Service Inc. by (signature) 50 d d 5. Harp