		CORD Form WWC-				
LOCATION OF WATER WELL:			Section Number	Township Number	Range Number	
ounty: Sedgwick	SW ½ NW	1/4 SW 1/4	33	т 27 s	R 01 (E)N	
stance and direction from neares 2160 S. Broadway	t town or city street address of wel	I if located within city	,			
WATER WELL OWNER:	John Ve				· · · · · · · · · · · · · · · · · · ·	
•		2160 S. Broadway		December 1 to 1 t		
R#, St. Address, Box # :	•	•		Board of Agriculture, Division of Water Resources		
y, State, ZIP Code :	e, ZIP Code : Wichita, KS 67211		Application Number:			
LOCATE WELL'S LOCATON W AN "X" IN SECTION BOX:	ITH 4 DEPTH OF COMPLETE) \/E1 1	20 # ELEV	ATION:		
	DEPTH OF COMPLETED		II. ELEV	ATION.		
N	Depth(s) Groundwater Encou					
	WELL'S STATIC WATER LE	VEL	ft. below land su	urface measured on mo/day/	yr	
NW NE	Pump test data:	Well water was	ft.	after hours p	umping gpm	
1	Est. Yield gpm:	Well water was	ft.	after hours p	umping gpm	
w	E Bore Hole Diameter 12.	5 in. to	20	ft. and in	. to ft.	
	Est. Yield gpm: E Bore Hole Diameter 12.5 WELL WATER TO BE USED	AS: 5 Public water	supply	8 Air conditioning 1	Injection well	
X SW SE	1 Domestic 3 Feed in	ot 6 Oli field wat	er suppiy	9 Dewatering (12	Other (Specify below)	
3K	2 Irrigation 4 Industr	rial 7 Lawn and g	arden (domestic)	10 Monitoring well	SVE	
	Was a chemical/bacteriologic					
S	submitted	·		er Well Disinfected? Yes		
TYPE OF BLANK CASING USE		ht Iron 8 Cor		CASING JOINTS: Glued		
1 Steel 3 RM	Ţ.					
		tos-Cement 9 Oth	er (specify below			
(2 PVC) 4 AE	S 7 Fibergl	ass		Threa	ded Flush	
nk casing diameter 4	in. to 10 ft., Dia	a i	n. to	ft., Dia	in. to ft.	
sing height above land surface	Flush in., weight	2	lbs./ft. V	ft., Dia Vall thickness or gauge No. 10 Asbestos-ceme	Sch 40	
PE OF SCREEN OR PERFORA	FION MATERIAL:		Z PVC)	10 Asbestos-ceme	nt _	
	ainless steel 5 Fibergl	ass	RMP (SR)	11 Other (specify)	; 	
2 Brass 4 Ga	Ivanized steel 6 Concre	ete tile 5 Gauzed wrappe	ABS	12 None used (ope	n hole)	
REEN OR PERFORATION OPE	NINGS ARE:			8 Saw cut	11 None (open hole)	
1 Continuous slot	3 Mill slot	6 Wire wrapped		9 Drilled holes		
2 Louvered shutter	4 Key punched	7 Torch cut		10 Other (specify)		
REEN-PERFORATED INTERVA	LS: From 10	ft. to 20	ft. Fn	om ft. to)ft.	
	From	ft. to	ft. Fr	om ft. to	ft.	
GRAVEL PACK INTERVAL	S: From 8 f	ft. to 20	ft. Fr	omft. to		
	From	ft. to	ft. Fr	om ft. to	ft.	
GROUT MATERIAL: 1 No	eat cement 2 Cement gro	ut 3 B	entonite 4	Other Concrete	•	
out intervals From 0	ft. to 0.5 ft. From	0.5 fi	to 8	ft From	ft. to ft.	
at is the nearest source of possil	ale contamination:		10 Livesto		ndoned water well	
Septic tank	4 Lateral lines 7	7 Dit noise			vell/ Gas well	
2 Sewer lines	5 Cess pool 8	· •		er storage 16 Oth		
3 Watertight sewer lines				· · ·	er (specify below)	
•	6 Seepage pit 9	Feedyard		cide storage		
ection from well? ROM TO CODE	LITUOLOGIC LOC	FDOA	How many fe		TERVALO	
	LITHOLOGIC LOG	FROM	1 TO	PLUGGING IN	IERVALS	
	Silty Clay, brown	grained	 			
	Sand, well sorted, med.	yraineu	 			
	Silty Clay Sand, well sorted					
	Sand, well sorted Sand, fine to med. grain	od				
					<u>.</u>	
	Sand, med. to coarse graps of the property sorted.	anieu,				
10 20	Journy Surfed.					
			-			
	195.1					
			+	- · · · · · · · · · · · · · · · · · · ·		
				· · · · · · · · · · · · · · · · · · ·		
CONTRACTOR'S OR LANDOW!	NER'S CERTIFICATION: This wat	ter well was(1) const	icted 12\ record	tructed or (3) physical under	my jurisdiction and was	
				/:	11	
npleted on (mo/day/yr)				e to the best of my knowledg		
ter Well Contractor's License No.	531			ord was completed on (mo/d		
er the business name of	Geotechnical Services	s, Inc. by (signature) /	(like IT	· Ilm	
INSTRUCTIONS:. Please fill in bi	anks and circle the correct answers. S	Send three copies to Ka	nsas Department	of Health and Environment, Bur	eau of Water, 1000 S W	
Jackson St., Ste. 420, Topeka, Ka	nsas 66612-1367. Telephone: 913-2	296-5545. Send one to	WATER WELL OV	VNER and retain one for your re	ecords.	