

1 LOCATION OF WATER WELL: Fraction SE 1/4 NE 1/4 SE 1/4 Section Number 32 Township Number 27 S Range Number 1 E

County: Sedgwick Distance and direction from nearest town or city street address of well if located within city? 2153 Market in City Right of Way along Linkard Wichita, KS

2 WATER WELL OWNER: City of Wichita MW-20B Board of Agriculture, Division of Water Resources Application Number: -

RR#, St. Address, Box #: 485 N. Main City, State, ZIP Code: Wichita, KS 67202

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 3x3 grid with 'X' in the SE section]

4 DEPTH OF COMPLETED WELL: 36.18 ft. ELEVATION: 19 ft. 2. 19 ft. 3. 19 ft.

Depth(s) Groundwater Encountered 19.71 ft. below land surface measured on mo/day/yr 4/10/03

WELL'S STATIC WATER LEVEL 19.71 ft. below land surface measured on mo/day/yr 4/10/03

Pump test data: Well water was - ft. after - hours pumping - gpm

Est. Yield - gpm Well water was - ft. after - hours pumping - gpm

Bore Hole Diameter 3.5 in. to 3.5 ft., and - in. to - ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

Blank casing diameter 1 in. to 31 ft., Dia 7 Fiberglass Threaded X

Casing height above land surface - in., weight - lbs./ft. Wall thickness or gauge No. SCH 40

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 31 ft. to 36 ft., From - ft. to - ft.

GRAVEL PACK INTERVALS: From 28 ft. to 36 ft., From - ft. to - ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 2 ft. to 28 ft., From - ft. to - ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? East How many feet? ~500

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 4 Silty clay

4 6 Silty clay

6 8 Sand, fine

8 10 Silty clay

10 14.5 Sand, fine, poorly sorted

14.5 20 Sand, fine to med, poorly sorted

20 24 Sand, coarse w/ gravel, well sorted

24 36 Sand, coarse, well sorted

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/12/03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 710 This Water Well Record was completed on (mo/day/yr) 4/10/03 under the business name of Below Ground Surface, Inc. by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.