

1 LOCATION OF WATER WELL: County: Sedgewick Fraction SE 1/4 SE 1/4 SE 1/4 Section Number 32 Township Number T 27 S Range Number R 1 E/W

Distance and direction from nearest town or city street address of well if located within city? 2336 Market St in city Right-of-Way Wichita, KS

2 WATER WELL OWNER: City of Wichita RR#, St. Address, Box #: 465 N. Main City, State, ZIP Code: Wichita, KS 67202 Board of Agriculture, Division of Water Resources Application Number: MW-34

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the SE corner]

4 DEPTH OF COMPLETED WELL: 26 ft. ELEVATION: 18' ft. WELL'S STATIC WATER LEVEL: 18' ft. below land surface measured on mo/day/yr

Pump test data: Well water was 18' ft. after 18' hours pumping 18' gpm Est. Yield 18' gpm: Well water was 18' ft. after 18' hours pumping 18' gpm Bore Hole Diameter: 3.5 in. to 26 in. and 26 in. to 26 in.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded X

Blank casing diameter: 1 in. to 16 in. Dia. 16 in. to 16 in. Dia. 16 in. to 16 in. Dia. Casing height above land surface: 16 in. weight 16 lbs./ft. Wall thickness or gauge No. SCH 40

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 16 ft. to 26 ft. From 16 ft. to 26 ft. From 16 ft. to 26 ft. GRAVEL PACK INTERVALS: From 14 ft. to 26 ft. From 14 ft. to 26 ft. From 14 ft. to 26 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 2 ft. to 12 ft. From 2 ft. to 12 ft. From 2 ft. to 12 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? South Northeast How many feet? 1200

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 16 unknown 0 16

16 18 Sand, coarse grained w/ small gravel 16 18

18 20 Sand, med. grained 18 20

20 26 Sand, coarse grained w/ gravel well graded 20 26

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/29/03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 710 This Water Well Record was completed on (mo/day/yr) 8/22/03 under the business name of Below Ground Surface, Inc. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.