	WATER WELL RECOR	RD Form WWC-5	KSA 82a-1212	
1 LOCATION OF WATER WELL:	FRACTION	SECTION N	UMBER TOWNSHIP NUMBER	RANGE NUMBER
Sedgwick	NW 1/4 NW 1/4	NW 1/4 6	т 27 s	R 1E E/W
Distance and direction from nearest	town or city street address of well if located within city	?		
1929 W. 29th N.	Wichita, Kansas			
2 WATER WELL OWNER:	BURKHOLDER, Ron	-		
RR#,ST. ADDRESS,BOX #:	1929 W. 29th N.		Board of Agr	iculture, Division of Water Resource
CITY, STATE:	Wichita, Kansas	ZIP COL	DE: Application Nur	nber:
3 LOCATE WELL'S LOCATION	4 DEPTH OF COMPLETED WELL:	40 ft.	ELEVATION:	
WITH AN "X" IN SECTION BO	x: 💾	ft.	ft,	ft.
N N	Depth of groundwater Encountered:			40.00.00
	WELL'S STATIC WATER LEVEL		ND SURFACE MEASURED ON mo/o	,,
NW NE	Pump test data:	Well water was		s of pumping @ gpm
w Wile	Est. Yield: gpm	Well water was		s of pumping @ gpm
	E Bore Hole Diameter 12 in.	to 40	ft. and in.	to ft.
SW - SE	WELL WATER TO BE USED AS:	ublic water supply 7.L	9. Dewateri	•
I SW SE	1 1			12. Other (Specify below)
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/hacterological sample submitted to Department? VES NO ; If yes, what mo/day/yr was sample				
S	Was a chemical/bacteriological sample sub submitted		ES NO ; If yes, yes, was Water Well Disinfected?	YES NO
5 TYPE OF CASING USE				
[*]	5. Wrought Iron 7. Fi	iberglass 9. Other (S	pecify below) CASING JOINTS:	Glued Threaded
	• •	oncrete tile SDR-26		Welded Clamped
	. ADS	Die in 4	o ft., Dia.	in to #
Blank casing diameter		Dia. in. to	o ft., Dia.	in. to ft.
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214				
TYPE OF SCREEN OR PERF		_		
Steel 3. Stainles	ss Steel 5. Fiberglass 7. PV	9. ABS	11. Other (specify)	
2 Brass 4 Galvan	ized 6. Concrete Tile 8. RN	MP (SR) 10. Asbesto	s-Cement 12. None used (open	hole)
SCREEN OR PERFORATION	OPENINGS ARE:			
1. Continuous slot	3. Mill slot 5. Gauzed wrapped	7. Torch cu	t 9. Drilled holes	11. None (open hole)
2. Louvered shutter			40 Other (consist)	
2. Louvered Snutter	4. Key punched 6. Wire wrapped	8. Saw cut) 10. Other (specify)	
SCREEN - PERFORATION IN	TERVAL From 30 ft.	to 40 ft.,	From ft.	to ft.
	From ft.	to ft.,	From ft.	to ft.
GRAVEL PACK INTE	RVALS: From 24 ft.	to 40 ft	From ft.	to ft.
	From ft.	to ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug				
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.				
What is the nearest source of p	7 Dit makes	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
1. Septic tank	4. Lateral lines	_		16. Other (specify below)
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)				
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage				
Direction from well? So	uth		How many feet? 10	
From To	LITHOLOGIC LOG	From T	o LITHOLO	OGIC LOG
0 3 topsoi	l			
3 10 clay				
10 15 sandy	clay			
15 40 mediu	m sand			
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and				
was completed on (mo/day/year) 10/22/2003 and this record is true to the best of my knowledge and belief.				
	. ,		,	4/2003
under the business name of Harp Well & Pump Service Inc. by (signature) Jo dd S. Harp				
•				