		WATER WELL RECORD	Form WWC-5	KSA 82a			
1 LOCATION OF WA				Number	Township Numb	ı	Range Number
County: Seacu		E 1/4 SE 1/4 NU street address of well if locate		<u> </u>	T 27	s	R / (5/W
		, Wilhita Ks					
	VNER: LBJ Paut						
2 WATER WELL OV	vneh: LD3 FUX vx # : 605 Wlst	i kr ship			Decad of Assis	da Dist	
					•	•	sion of Water Resources
City, State, ZIP Code	K.C. Mo.	67112	151		Application Nu		
AN "X" IN SECTIO	N BOX:	H OF COMPLETED WELL	<i>[</i>]	t. ELEVA	TION:		
_	N Depth(s)	Groundwater Encountered	10	ft. 2	<u>2</u>	ft. 3	715782ft.
Ĭ	WELL'S	STATIC WATER LEVEL					
NW	NE	Pump test data: Well wat					
	Est. Yiek	J gom; Well wat	er was	ft. a	fter ho	ours pumpi	ng gpm
* w		e Diameter	-				
¥ W !	WELL W	ATER TO BE USED AS:	5 Public water so		8 Air conditioning		ction well
Ī	1 De	omestic 3 Feedlot					er (Specify below)
1 1		igation 4 Industrial			Monitoring well		
ļ <u> </u>	l Was a ch	nemical/bacteriological sample	submitted to Depa	rtment? Ye	esNo 🔏	; If yes, mo	/day/yr sample was sub-
	s mitted		<u>-</u>	Wa	ter Well Disinfected?	Yes	No)
5 TYPE OF BLANK	CASING USED:	5 Wrought iron	8 Concrete			Glued	Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (sp	ecify below	v)	Welded .	
2 PVC	A ABS	7 Fiberglass		<i>.</i>		Threaded	1. 🖍
•	0.3.15 in. to	1 7 1			ft., Dia	_	'-1 1/ 1
Casing height above I	and surface.F.U.	.அ£.∢in., weight	<u></u>	lbs./	ft. Wall thickness or ga	auge No. 之	190 m
TYPE OF SCREEN C	R PERFORATION MATER	IIAL:	7 PVC		10 Asbesto	s-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (s	specify)	
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS		12 None us	sed (open	hole)
SCREEN OR PERFO	RATION OPENINGS ARE:	5 Gauz	zed wrapped		8 Saw cut	11	None (open hole)
1 Continuous sl	ot 3 Mill slot	6 Wire	wrapped		9 Drilled holes		
2 Louvered shut	tter 4 Key punche	ed 7 Torci	h_cut		10 Other (specify)		
SCREEN-PERFORAT	ED INTERVALS: From	/5 ft. to .	5	ft., From	m	ft. to	
	From	<u> ft</u> . to .		ft., From	m	. , ft. to	
GRAVEL PA	ACK INTERVALS: From	15! ft. to .	4.!	ft., Froi	m	ft. to	
	From	ft. to		ft., From		ft. to	ft.
6 GROUT MATERIA	L: 1 Neat cement	2 Cement groutft., From ation:	3 Bentonite	, 4	Other CEMENT.		
Grout Intervals: Fro	m4. 5. to .6	ران ft., From		D	ft., From		ft. to
What is the nearest s	ource of possible contamin	ation:	(4)	10 Lives	tock pens	14 Aban	doned water well
1 Septic tank	4 Lateral lines	7 Pit privy	•	11) Fuel:	storage Founer	15 Oil w	ell/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lag	goon	12 Fertili	zer storage	16 Othe	r (specify below)
3 Watertight sev	wer lines 6 Seepage pit	9 Feedyard		13 Insec	ticide storage		
	Douthwest	•			ny feet? (a)		
FROM TO	LITHO	LOGIC LOG	FROM	то	PLUG	GING INTE	RVALS
0 1.0	Broclaveus	al wiroots ma	WD				
10 4.0	1+Binclany	I caliene, Hois	5				
4.0 11.0	14. PaleBin	Law wirdlich) ,				
	& Olles Moo	n Caustrinal	u				
11.0 14.0	1 A . T - 71	ottled clay with	3 T				
	ant of sand	7					
14.0 15.0	yellow Bin	Made tight.	no ala				
1,0 1510	guesto.	criace) Sicop					
 							
 				<u>_</u>			
		TIFICATION: This water well v		_			
completed on (mo/day							edge and belief. Kansas
Water Well Contracto	r's License No	This Water \	Well Record was c	ompleted	on (mo/day/yr) <i>!.O./. l</i>	7/03	
under the business na	ame of Benul	W		by (signa	ture) (AMOS)	COLR	
		E PRESS FIRMLY and PRINT clearly. Pnsas 66620-0001. Telephone: 913-296-					es to Kansas Department
OF FREEITH AND ENVIRONS	non, purcau or maior, ropera, na	000c0-0001, Telephone, 313-230-	SO TO. SOLID ONE TO YVA	**LLL U	una retam one loi you		