		ER WELL RECOF	RD Form W		SA 82a-1						
LOCATION OF WATER WELL:	Fraction			Section N			ship Nu	mber	Range Number		
ounty: Sedgwick		NE ½			5	T	27	<u>.</u> S	R	01	E
istance and direction from nearest to South side of Murdoc			ocated within	city?							
WATER WELL OWNER:		ific Railroad				 					
R#, St. Address, Box # :		e Street, Ro				Board (of Agricu	ılture, Divi	sion of W	Jater Res	
ity, State, ZIP Code :	Omaha NE						tion Nur		31011 01 1	valor res	ouices
LOCATE WELL'S LOCATON WITH				20.0							
'_AN "X" IN SECTION BOX:	DED IN OF	COMPLETED W	ELL	30.6 f	t. ELEV	ATION:					
	Depth(s) Ground	dwater Encounte	red 1		^{ft.}	. 2		ft.	3		ft.
`		WATER LEVEL									
NW NE		p test data: We			¹¹	t, after		. hours p	umping		gpm
W E		gpm; We eter 8.5		32.5	π	t. after t. after ft. and		_ nours p	umping		gpm
	Bore Hole Diam WELL WATER 1 1 Domestic	TO BE USED AS	in. io 3: 5 Public v	water supply		8 Airc	onditioni	ina 11	. to I Iniectic	n well	п.
SE	1 Domesti	c 3 Feed lot	6 Oil field	l water suppl	y	9 Dew	atering	12	Other (Specify b	elow)
,	2 Irrigation	4 Industrial	7 Lawn a	nd garden (d	lomestic) 10 Mo	nitoring	well			
S	Was a chemical	/bacteriological s	ample submit	ted to Depar	tment?	Yes	No X	if yes,	mo/day/	yr sample	was
	submitted					er Well Dis					
TYPE OF BLANK CASING USED:		5 Wrought In	ron 8	Concrete tile	е	CASIN	G JOINT	ΓS: Glued	1	Clamped	1
1 Steel 3 RMP	(SR)	6 Asbestos-	Cement 9	Other (spec	ify belov	v)		Welde			
2 PVC 4 ABS		7 Fiberglass						Threa	ded	Flush	1
lank casing diameter 2	in. to 25.	3 ft., Dia		in. to		ft., Dia	· -		in. to		ft.
ank casing diameter 2 asing height above land surface F	lushmount	in., weight	0.70	3	lbs./ft.	Wall thickn	ess or g	auge No.		Sch. 40	j
PE OF SCREEN OR PERFORATIO	N MATERIAL:			7 PVC		10) Asbes	tos-ceme	nt		
1 Steel 3 Stainle	ess steel	5 Fiberglass		8 RMP		11	Other	(specify)			
	nized steel	6 Concrete t	ile	9 ABS		12	None	used (ope	n hole)		
CREEN OR PERFORATION OPENIN			Gauzed wra			8 Saw c			11 None	e (open h	ole)
	Mill slot		Wire wrapp			9 Drilled	-				ĺ
	Key punched		Torch cut			10 Other	(specify	/)			
CREEN-PERFORATED INTERVALS:	From	25.3 ft. to			π, FI #						
GRAVEL PACK INTERVALS:	From	ft. to 23 ft. to		32.5	'\ [] A []	rom		ft. to			
OTAVEET NOR INTERVALS.	From	ft. to						ft. to			'l. ft.
GROUT MATERIAL: 1 Neat of	rement 2	Coment grout	7	Pontonito	1	4 Other		11. 10			11.
rout Intervals From 1	4 23	4 Com		Deritorine		- Culei					
hat is the nearest source of possible		II. From	·			π. F ock pens		14 Aba			
1 Septic tank	4 Lateral lines	7 P	it privy		Fuel st	•			vell/ Gas		
2 Sewer lines	5 Cess pool		Sewage lagoo			er storage				y below)	
3 Watertight sewer lines	6 Seepage pit		eedyard		Insecti	cide storaç	je		, , , , , , , , , , , , , , , , , , ,	,,	
irection from well?					v many f	eet?					
FROM TO CODE Cla	LITHOL ay & Silt	OGIC LOG	F	ROM 1	го		PLUC	GING IN	TERVAL	<u>s</u>	
11 32 Sa											
	p of Shale								· · · · · ·		
						 					
					-						
CONTRACTOR'S OR LANDOWNER	D'S CEDTICICATI	ON: This water	wall was 71\c	onetructor /	(2) mag-	netruoted a	r /3) ali	and und-	e mu iusia	diation an	dues
J	3 CERTIFICATI 11-1							-		,	- 1
ompleted on (mo/day/yr)	1-14	4- 03 531		and this reco							
/ater Well Contractor's License No.	Geotechnica			This Water \		rowas co	ompleted	on (mo/d	ay/yr)		-03
nder the business name of INSTRUCTIONS:. Please fill in blank				by (signature		of Health ar	nd Environ	pment Ru	ear of W	ater 1000	Sw.
Jackson St., Ste. 420, Topeka, Kansa										ater, 1000 i	- **