	WATER	WELL RECORD	Form WV	NC-5 k	(SA 82a-1212		
1 LOCATION OF WATE	R WELL: FRACTION		SEC	TION NUMBE	R TOWNSHIP NUMBE	R RANGE	NUMBER
Sedgwick			W 1/4	7	T 27 S	R 1	IE E/W
	m nearest town or city street address of						
	f 13th and Clarence and		and Minisa		Wichita, Kansas		
2 WATER WELL	, -	TY OF			Boar	d of Agriculture, Division o	f Water Resource
RR#,ST. ADDRESS					Doard	of Agriculture, Division o	Trace Resource
CITY,	STATE: Wichita, Kansa	as		IP CODE:	Applicat	ion Number:	
3 LOCATE WELL'S LOW	DEPTH OF CO	OMPLETED WELL:	40 ft.		ELEVATION:		
WITH AN A IN SE		vater Encountered:	ft	t.	ft.		ft.
	WELL'S STATIC	WATER LEVEL 12	FT. BELC	OW LAND S	URFACE MEASURED ON	N mo/day/yr: 1/3	14/04
	NE	Pump test data: We	II water was		ft. after	hours of pumping @	gpm
1 1 1	Est. Yield:	gpm We	ell water was		ft. after	hours of pumping @	gpm
w Mile	Bore Hole Diam	neter 12 in.	to 4	40 f	and	in. to	ft.
-	,	O BE USED AS:			9. De	watering 11. In	jection well
sw	1. Domestic	3. Feedlot 5. Publi	ic water supply	7. Lawn	and garden only		Specify below
	2. Irrigation	4. Industrial 6. Oil fi	•••	y 8. Airco		nitoring well	
S	Was a chemical/t submitted	pacteriological sample submitte	ed to Department?	YES	NO ; 1 Water Well Disinfected?	f yes, what mo/day/yr	NO
5 TYPE OF CAS						\rightarrow	
5 TYPE OF CAS	3. RPM (SR) 5. Wro	ught Iron 7. Fiber	glass 9. C	ther (Specif	y below) CASING JOI		Threaded
2. PVC	• •	estos-Cement 8. Conci	rete tile SD	R-26		Welded	Clamped
Blank casing diamet		20 ft., Dia	ı. in.	to	ft., Dia.	in. to	ft.
ľ	24						
Casing height above		., Weight	: 5.52	lbs. / ft.	Wall thickness of	or gauge No33	32
•	OR PERFORATION MATERIAL:	lass 7. PVC		NDC	11. Other (spec	~ifu)	
	B. Stainless Steel 5. Fiberg			ABS	• •		
2. Brass	4. Galvanized 6. Concre	ete Tile 8. RMP (SR) 10. A	\sbestos-Ce	ment 12. None used	(open noie)	
SCREEN OR PERFO	DRATION OPENINGS ARE:						
1. Continuous slo	t 3. Mill slot	5. Gauzed wrapped	7. T c	orch cut	9. Drilled holes	11. None	(open hole)
2. Louvered shutte	er 4. Key punched	6. Wire wrapped	8. Sa	w cut	10. Other (speci	ify)	
SCREEN - PERFORA	ATION INTERVAL From	20 ft.	to 40	ft.,	From #	40	ft.
00.122.1	From	ft.	to		_		
ODAVE DA		20 ft.		ft.,	From ft.		ft.
GRAVEL PA	CK INTERVALS: From	20 II.	to 40	ft.,	From ft.	to	ft.
	From	ft.	to	ft.,	From ft.	to	ft.
6 GROUT MATER	IALS: 1. Neat cement	2. Cement Grout		3. Bentonite	Other	bentonite hole p	lug
Grout intervals:	From 4 ft.	to 24 ft., Fr	om ft.	to	ft., From	ft. t	to ft.
What is the nearest s	ource of possible contamination:	7 Dit melan	10 Livestor	rk none	12 Innocialdo eta	rage 15. Oil well	l/Gae wall
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens					13. Insecticide sto	46 Other (
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (spec							
3. Watertight sew	er line 6. Seepage pit	9. Feed yard	12. Fertilize	r storage		None A	Apparent
Direction from well?					How many feet?		
From To	LITHOLO	GIC LOG	From	To	LITH	IOLOGIC LOG	
0 3	topsoil						
3 5	clay			-			
5 40	medium sand			+			
h							
				+			
				1			
						·	
						· · · · · ·	
			L	<u> </u>			
7 Contractor's or	Landowner's Certification: This w	ater well was 1. constru	ucted 2. re	constructe	d or 3. plugged	under my jurisd	iction and
was completed on	4 4 4 4 4 4			e best of my	knowledge and belief.		
i i	` ,, ,			-	-	1/16/2004	
	l Contractor's License No.		lei weil record wa	as complete	d on (mo/day/year)	1/10/2004	
						O 11	
under the business	name of Harp Well & Pu	mp Service Inc.	by (s	ignature)		S. Harp	