	WATER WEI	LL RECORD	Form V	VWC-5	KSA 82a-	1212				
1 LOCATION OF WATER WELL:	FRACTION			SECTION NUMBER				RANGE NUMBER		
Sedgwick		NW 1/4 SV	W 1/4	6	T	27 S	R	1E	E/W	
Distance and direction from nearest town or c 2625 Manhattan	ity street address of well if l Wichita, K	•								
	OCKWELL, Wil									
RR#,ST. ADDRESS,BOX #: 2625 Manhattan Board of Agriculture, Division of Wa								n of Wat	ler Resource	
CITY, STATE: Wi	chita, Kansas			ZIP CODE:		Application No	umber:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF DIMENSE	WELL:	25	ft.	ELEVATIO	N:				
	Depth of groundwater En	ncountered:		ft.		ft.			ft.	
	WELL'S STATIC WATE	R LEVEL 14	FT. BE	LOW LAND S	SURFACE ME	ASURED ON mo	o/day/yr: 1	2/17/	03	
NWNE			water was		ft. after		irs of pumping (_	gpn	
w W	Est. Yield: Bore Hole Diameter	01	water was		ft. after		irs of pumping	_	gpm	
	wn s	in. USED AS:	to	1	ft. and	in.	4.4	0 Injecti	ft. ion well	
swse			water supp	ly 7. Lawn	and garden o	9. Dewate	9	•	cify below	
	_		d water sup		onditioning	10. Monitor	ring well			
s	Was a chemical/bacteriolo submitted	ogical sample submitted	to Departmen		Water Well Di	,	yes (YES)	/yr was	•	
5 TYPE OF CASING USED:						CASING JOINTS:			hreaded	
1. Steel 3. RPM (,	•	ass 9.	Other (Speci	ry below) C	ASING JUINTS:	Welded		Clamped	
2. PVC 4. ABS	6. Asbestos-Co	ement 8. Concret	te tile				.,		, and the contract of the cont	
Blank casing diameter 1 1/4		ft., Dia.	in.	to	ft.,	Dia.	in. to		ft.	
Casing height above land surface:	60 _{in.,}	Weight:		lbs. / ft.	Wa	I thickness or ga	uge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) N/A										
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) IN/A 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)										
SCREEN OR PERFORATION OPENII		G (G.	., 10	. 13003103-00		Tronjo adod (oper	· · · · · · · · · · · · · · · · · · ·			
1. Continuous slot 3. Mill:		ızed wrapped	7.	Torch cut	. 9. 0	rilled holes	11. N on	e (one	en hole)	
2. Louvered shutter 4. Key		e wrapped		Saw cut		other (specify)		· (op ·	,	
SCREEN - PERFORATION INTERVAL	•						4/21			
GOREEN - PERFORATION INTERVAL	- From From	ft. ft.	to	ft.,	From	ft,	to		ft.	
GRAVEL PACK INTERVALS:	From	ft.	to to	ft.,	From	ft.	to		ft.	
STATE THE REPORT OF THE PARTY AND A STATE OF T	From	ft.	to	ft.,	From	ft.	to		ft.	
6 GROUT MATERIALS: 1. Nea				ft.,	From	ft. Other hen	to		ft.	
Grout Intervals: From	t cement ;	 Cement Grout ft., Fron 	n	3. Bentonit oft. to			tonite hole 2 ft.	prug to 25	-	
What is the nearest source of possible of					ft.,				•	
N = Service Lauring				10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well						
2. 50.751 11103				1. Fuel storage 14. Abandon water well 16. Other (specify below)						
3. Watertight sewer line 6. Seepage pit 9. Feed yard 1 Direction from well?			12. Fertili:	2. Fertilizer storage None Apparent						
From To	LITHOLOGIC L	OG	From	1 To	How	many feet?	OGIC LOG			
		.00	0	2	surface cl	ay and silt	JGIC LOG			
			2	25	bentonite					
		·								
					 	- 10				
							· · · · · · · · · · · · · · · · · · ·			
										
	·									
	****		+							
				 	 _					
					<u> </u>					
	22.0			+						
7 Contractor's or Landowner's Certif	lication: This water well	was 1 construct	ted 2	reconstructe	d or 3, C	plugged	under my juris	diction	and	
was completed on (mo/day/year)	12/17/2003				knowledge an		onder my juris	diction	anu	
					•		0/2002			
Kansas Water Well Contractor's Licer					d on (mo/day/y	,	9/2003			
under the business name of Harp	Well & Pump Se	ervice Inc.	by (signature)		7119	11			