1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
ounty: SEDGWICK	SE ¼ NE ¼ NE	,	т 27 s	R 1 E
stance and direction from nearest tow	wn or city street address of well if located wit	thin city?		
1759 S. HILLSIDE, WIC	TOWN & COUNTRY			
WATER WELL OWNER:	PO BOX 17087	•	Daniel of Assistantiana Di	visian of Motor Donovison
R#, St. Address, Box # :	WICHITA, KS 67217		•	vision of Water Resources
City, State, ZIP Code LOCATE WELL'S LOCATON WITH			Application Number:	
AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL	27 ft. ELEV	ATION:	
N	Depth(s) Groundwater Encountered 1			
<u> </u>	WELL'S STATIC WATER LEVEL	ft. below land sr	urface measured on mo/day	//yr
NWNE X	Pump test data: Well water w	vas ft	. after hours	pumpinggpm
	Est. Yield gpm: Well water w	vas ft	. after hours	pumpinggpm
W E	Bore Hole Diameter 8.5 in. to WELL WATER TO BE USED AS: 5 Pub 1 Domestic 3 Feed lot 6 Oil (30	ft. and i	in. to ft.
Su SE	1 Domestic 3 Feed lot 6 Oil:	alic water supply field water supply	8 Air conditioning 9 Dewatering	11 Injection well 12 Other (Specify below)
SW SE	2 Irrigation 4 Industrial 7 Law			, 2 Guidi (Gpoon) Bolon)
/				
S	Was a chemical/bacteriological sample sub			V
TYPE OF BLANK CASING USED:	submitted 5 Wrought Iron		er Well Disinfected? Yes CASING JOINTS: Glue	
1 Steel 3 RMP (•	9 Other (specify below		
	•	5 Other (specify below	·	
2 PVC 4 ABS	7 Fiberglass			eaded FLUSH
lank casing diameter 2	in. to 5.5 ft., Dia	in. to	ft., Dia	in. to ft.
	in., weight	lbs./ft.	Wall thickness or gauge No	5ch40
YPE OF SCREEN OR PERFORATION			10 Asbestos-ceme	
1 Steel 3 Stainle	•	8 RMP (SR) 9 ABS	11 Other (specify)	
2 Brass 4 Galvan CREEN OR PERFORATION OPENING	nized steel 6 Concrete tile IGS ARE: 5 Gauzed	9 ABS	12 None used (op 8 Saw cut	•
	Mill slot 6 Wire wra		9 Drilled holes	The trong (open nois)
	Key punched 7 Torch cu	• •	10 Other (specify)	
CREEN-PERFORATED INTERVALS:	4=	27 ft. Fr	rom ft.	to ft.
	From ft. to	ft. Fı	rom ft.	to ft.
GRAVEL PACK INTERVALS:	From 15 ft. to	27 ft. Fi	rom ft.	to ft.
	From ft. to		rom ft.	
GROUT MATERIAL: 1 Neat c	cement 2 Cement grout	3 Bentonite	4 Other	
rout Intervals From 0.5	ft. to 15 ft. From	ft. to	ft. From	ft. to ft.
hat is the nearest source of possible c		10 Livesto		andoned water well
1 Septic tank	4 Lateral lines 7 Pit privy	11 Fuel st	torage 15 Oil	l well/ Gas well
2 Sewer lines	5 Cess pool 8 Sewage la	goon 12 Fertiliz	er storage 16 Ot	her (specify below)
3 Watertight sewer lines	6 Seepage pit 9 Feedyard		cide storage	
rection from well? FROM TO CODE	LITUOLOGICLOG	How many f		NTEDVALO
	LITHOLOGIC LOG T CLAY, silty	FROM TO	PLUGGING II	NIERVALS
	ND, poorly graded,			
	reasing grain size with			
inc	rease in depth			
inc	rouse in depuir			
inc	nouse in depth			
inc	nouse in depth			
inc	Todo in depui			
inc	Todo in depart			
inc				
inc				
inc	- Cade III deptil			
5.5 30 inc inc				
5.5 30 inc inc	R'S CERTIFICATION: This water well was			
5.5 30 inc inc inc inc	R'S CERTIFICATION: This water well was (and this record is tru	to the best of my knowled	ige and belief. Kansas
CONTRACTOR'S OR LANDOWNER ompleted on (mo/day/yr) //dater Well Contractor's License No.	R'S CERTIFICATION: This water well was	and this record is tru This Water Well Rec		ige and belief. Kansas