

NMW 51D

WATER WELL RECORD Form WWC-5 KSA 82a-1212

LOCATION OF WATER WELL:

County Sedgwick

Distance and direction from nearest town or city street address of well if located within city?

8' W. of Ohio, and 167' S. of Murdock St.

Fraction

1/4 SW 1/4 SE 1/4

Section Number

116

Township Number

T 27

Range Number

R 1

EW

WATER WELL OWNER:

R# St. Address, Box #

City, State, ZIP Code

City of Wichita, Wichita, KS.

Board of Agriculture, Division of Water Resources

Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N

W

SW

SE

S

E

X

DEPTH OF COMPLETED WELL

28.0

ft.

ELEVATION:

ft.

Depth(s) Groundwater Encountered

1

ft.

2

ft.

3

ft.

WELL'S STATIC WATER LEVEL

14.0

ft. below land surface measured on mo/day/yr

Pump test data:

Well water was

ft. after

hours pumping

gpm

Est. Yield

N/A

gpm:

Well water was

ft. after

hours pumping

gpm

Bore Hole Diameter

in. to

ft., and

in. to

ft.

WELL WATER TO BE USED AS:

5 Public water supply

8 Air conditioning

11 Injection well

1 Domestic

3 Feedlot

6 Oil field water supply

9 Dewatering

12 Other (Specify below)

2 Irrigation

4 Industrial

7 Lawn and garden only

10 Monitoring well

Was a chemical/bacteriological sample submitted to Department?

Yes

No

X

If yes, mo/day/yr sample was submitted

Water Well Disinfected?

Yes

No

X

TYPE OF BLANK CASING USED:

1 Steel

3 RMP (SR)

2 PVC

4 ABS

5 Wrought iron

6 Asbestos-Cement

7 Fiberglass

8 Concrete tile

9 Other (specify below)

CASING JOINTS:

Glued

Clamped

Welded

Threaded

X

Blank casing diameter

1

in. to

23.0

ft., Dia

in. to

ft., Dia

in. to

ft.

Casing height above land surface

1.5

ft., weight

lbs./ft. Wall thickness or gauge No.

SCH 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless steel

5 Fiberglass

8 RMP (SR)

10 Asbestos-cement

2 Brass

4 Galvanized steel

6 Concrete tile

9 ABS

11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

SCREEN-PERFORATED INTERVALS:

From

23.0

ft. to

28.0

ft., From

ft. to

ft.

GRAVEL PACK INTERVALS:

From

21.0

ft. to

23.0

ft., From

ft. to

ft.

GRROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout intervals:

From

1

ft. to

2

ft., From

ft. to

ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Location from well?

How many feet?

FROM

TO

LITHOLOGIC LOG

FROM

TO

PLUGGING INTERVALS

0

1'

Topsoil

1

10'

silt & clay

10

28'

sand w/ silt stringers

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:

This water well was

1

constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)

2/17/04

and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No.

604

This Water Well Record was completed on (mo/day/yr)

3/5/04

Under the business name of

Environmental Priority Service, Inc

by (signature)

Todd B. M...

INSTRUCTIONS:

Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send 1/3 three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.