. WATER WELL RECORD F	orm WWC-5 KSA 82a-1212
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER
Sedgwick NE 1/4 SE 1/4 NE	1/4 34 T 27 S R 1E E/W
Distance and direction from nearest town or city street address of well if located within city?	
1842 S. Chautauqua Wichita, Kansas 2 WATER WELL OWNER: YOUNT, Leneda	
2 WATER WELL OWNER: YOUNT, Leneda RR#,ST. ADDRESS,BOX #: 1842 S. Chautauqua	Board of Agriculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE: Application Number:
3 LOCATE WELL'S LOCATION 4 DEPTH OF CALCADOWELL: 2	
WITH AN "X" IN SECTION BOX:	ft. ft. ft.
N Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 13	FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 7/14/04
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
Est. Yield: gpm Well wa	to ft. and in. to ft.
₩ELL WATER ₩ SUSED AS:	9 Dewatering 11. Injection well
1. Domestic 3. Feedlot 5. Public wa	er supply 12. Other (Specify below)
2. Irrigation 4. Industrial 6. Oil field w	ter supply 8. Air conditioning 10. Monitoring well
S Was a chemical/bacteriological sample submitted to I submitted	epartment? YES NO ; If yes, what mo/day/yr was sample Was Water Well Disinfected? YES NO
TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass	Other (Specify below) CASING JOINTS: Glued Threaded Welded Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete to	
Blank casing diameter 6 in. to ft., Dla.	in. to ft., Dia. in. to ft.
Casing height carries 72 in., Weight:	lbs. / ft. Wall thickness or gauge No.
TYPE OF SCREEN OR PERFORATION MATERIAL:	iso. 7 ti.
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS 11. Other (specify) N/A
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Cement 12. None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut 9. Drilled holes 11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut 10. Other (specify) N/A
SCREEN - PERFORATION INTERVAL From ft. to	ft., From ft. to ft.
From ft. to	ft., From ft. to ft.
GRAVEL PACK INTERVALS: From ft. to	ft., From ft. to ft.
From ft. to	ft., From ft. to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite Other bentonite hole plug
Grout Intervals: From 6 ft. to 9 ft., From	ft. to ft., From ft. to ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy). Livestock pens 13. Insecticide storage 15. Oil well/Gas well
	I. Fuel storage 14. Abandon water well 16. Other (specify below)
2. Sewer lines 0. dess root	2. Fertilizer storage None Apparent
3. Watertight sewer line 6. Seepage pit 9. Feed yard Direction from well?	How many feet?
From To LITHOLOGIC LOG	From To LITHOLOGIC LOG
	0 6 tornado shelter-concrete pit
	6 9 cement grout
	9 15 bentonite hole plug
	15 28 chlorinated sand & gravel
, .	
7 Contractor's or Landowner's Certification: This water well was 1. constructed	2. reconstructed or 3. plugged under my jurisdiction and
was completed on (mo/day/year) 7/14/2004 and this record is true to the best of my knowledge and belief.	
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/16/2004	
under the business name of Harp Well & Pump Service Inc.	by (signature) $\int_{0}^{\infty} dd \mathcal{S}_{r} \mathcal{A}_{rp}$