. WATER WELL RECORD F	orm WWC-5 KSA 82a-1212
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER
Sedgwick SW 1/4 SE 1/4 SE	1/4 7 T 27 S R 1E E/W
Distance and direction from nearest town or city street address of well if located within city?	
Intersection of 13th N. and McLean (SW corner)	
2 WATER WELL OWNER: WICHITA, CITY OF	Board of Agriculture, Division of Water Resource
RR#,ST. ADDRESS,BOX #: 455 N. Main	
CITY, STATE: Wichita, Kansas	ZIP CODE: Application Number:
UCCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF LINES COLD WELL:	ft. ELEVATION:
Depth of groundwater Encountered:	ft. ft.
WELL'S STATIC WATER LEVEL 15	FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 7/14/04
Pump test data: Well wat	r was ft. after hours of pumping @ gpm
Est. Yield: gpm Well wat Bore Hole Diameter in.	r was ft. after hours of pumping @ gpm
	to ft. and in. to ft.
WELL WATER WAS USED AS:	9. Dewatering 11. Injection well 9. Dewatering 12. Other (Specify below)
	12. Other (Specify below)
2, Irrigation 4, Industrial 6. Oil field w	16 was what made and a supply
S Was a chemical/bacteriological sample submitted to D submitted	was Water Well Disinfected? YES NO
5 TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass	9. Other (Specify below) CASING JOINTS: Glued Threaded
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass	Welded Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete til	
Blank casing diameter 8 in. to ft., Dla.	in. to ft., Dia. in. to ft.
Casing heigh ation land surface: 36 in., Weight:	lbs. / ft. Wall thickness or gauge No. #
TYPE OF SCREEN OR PERFORATION MATERIAL:	No. / III
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS 11. Other (specify) N/A
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Cement 12. None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut 9. Drilled holes 11. None (open hole)
· · · · · · · · · · · · · · · · · · ·	
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut 10. Other (specify) N/A
SCREEN - PERFORATION INTERVAL From ft. to	ft., From ft. to ft.
From ft. to	ft., From ft. to ft.
GRAVEL PACK INTERVALS: From ft. to	ft., From ft. * to ft.
From ft. to	ft., From ft. to ft.
1. Neat cement 2. Sement Glock	5. Bentonie Dentonie Prag
Grout Intervals: From ft. to ft., From What is the nearest source of possible contamination:	ft. to ft., From 3 ft. to 24 ft.
1. Septic tank 4. Lateral lines 7. Pit privy 1	. Livestock pens 13. Insecticide storage 15. Oil well/Gas well
1	14. Abandon water well 16. Other (specify below)
0.5-4	2. Fertilizer storage None Apparent
3. Watertight sewer line 6. Seepage pit 9. Feed yard Direction from well?	How many feet?
From To LITHOLOGIC LOG	From To LITHOLOGIC LOG
Trom To Entrocesio Edd	0 3 surface clay and silt
	3 24 bentonite hole plug
	24 40 chlorinated sand & gravel
7 Contractor's or Landowner's Certification: This water well was 1, constructed	2. reconstructed or 3. plugged under my jurisdiction and
was completed on (mo/day/year) 7/14/2004 and this record is true to the best of my knowledge and belief.	
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/16/2004	
under the business name of Harp Well & Pump Service Inc. by (signature) $\int_0^\infty dd \mathcal{S}$. \mathcal{A}_{rp}	