WATER WELL RECORD F	orm WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER		RANGE NUMBER
Sedgwick NE 1/4 SE 1/4 SW Distance and direction from nearest town or city street address of well if located within city?	1/4 12	T 27 S	R 1E E/W
5319 E. Crestview Wichita, Kansas			
2 WATER WELL OWNER: VEATCH, Andy			
RR#,ST. ADDRESS,BOX #: 5319 E. Crestview		Board of Agr	iculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Nur	mber:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 11	.7 ft.	ELEVATION:	
N Depth of groundwater Encountered:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL 21	FT. BELOW LAND SU	RFACE MEASURED ON mo/	day/yr: 7/21/04
Pump test data: Well wa			s of pumping @ gpm
Est. Yield: gpm Well wa	ter was to 117 ft.	ft. after hour and in.	s of pumping @ gpm to ft.
WELL WATER TO BE USED AS:	to 117 it.	9. Dewater	44 (-14)
	ter supply 7. Lawn a	nd garden only	12. Other (Specify below)
	rater supply 8. Air con	. 16	ng well what mo/day/yr was sample
S Was a chemical/bacteriological sample submitted to submitted		Vater Well Disinfected?	YES NO
5 TYPE OF CASING USED: 5 Wrought Iron 7 Fiberglass	9. Other (Specify		Glued Threaded
1. Steel 3. RPM (SR)	SDD 26	,	Welded Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete to	ile SDR-20		
Blank casing diameter 5 in. to 32 ft., Dia.	in. to	ft., Dia.	in. to ft.
Casing height above land surface: 12 in., Weight:	2.35 lbs. / ft.	Wall thickness or gau	ge No214
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)			
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Cer		hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 32 ft. to	117 ft.,	From ft.	to ft.
From ft. to	,	From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft. to	,	From ft.	to ft.
From ft. to	,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite		tonite hole plug
Grout Intervals: From 4 ft. to 24 ft., From	ft, to	ft., From	ft. to ft.
What is the nearest source of possible contamination:	10. Livestock pens		15. Oil well/Gas well
1. Septic tank 4. Lateral lines 5. Lateral lines 5. Lateral lines 5. Lateral lines 6. Later			
2. Sewer lines 5. Cess Pool 5. Servings agoon 14. Abandon water went			
3. Watertight sewer line 6. Seepage pit 9. Feed yard Direction from well? South	12. Tertinzer storage	How many feet? 100)
From To LITHOLOGIC LOG	From To		OGIC LOG
0 4 topsoil			
4 12 clay			
12 21 sand 21 25 clay	 		
25 117 shale			
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and			
was completed on (mo/day/year) 7/21/2004 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/23/2004			
under the business name of Harp Well & Pump Service Inc. by (signature)			