

1 LOCATION OF WATER WELL: County: <u>Sedgewick</u> Fraction: <u>NW 1/4 NW 1/4 SW 1/4</u> Section Number: <u>20</u> Township Number: <u>T 27 S</u> Range Number: <u>R 1 E</u>
--

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: <u>Ludeman Insulation + supply</u> RR#, St. Address, Box #: <u>203 N Handley</u> City, State, ZIP Code: <u>Wichita, KS 67201</u>	<u>MWLP</u> Board of Agriculture, Division of Water Resources Application Number:
--	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>23</u> ft. ELEVATION: ft.
--	---

1 Mile

W

N

E

S

Depth(s) Groundwater Encountered: 1 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL: 16.44 ft. below land surface measured on mo/day/yr ft.

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter. in. to ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes. No. ; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued. Clamped.
------------------------------	----------------	-----------------	--

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded

2 PVC 4 ABS 7 Fiberglass Threaded.

Blank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface. 0 in., weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
7 Torch cut 10 Other (specify) ft.

SCREEN-PERFORATED INTERVALS: From 13 ft. to 23 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 11.5 ft. to 24 ft., From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other: <u>Cement 0-2'</u>
-------------------	---------------	----------------	-------------	-----------------------------

Grout Intervals: From 2 ft. to 11.5 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage (former) 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Asphalt			
4	6	Silt w/ fine sand, light brown, moist			
9	11	Sand w/ silt stringers, light brown, moist			
14	16	Sand, fine to medium, moist			
	24	Wet, coarse sand, petroleum odor			

Flushmount Waiver by D Taylor

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/21/04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 602 This Water Well Record was completed on (mo/day/yr) 6/30/04 under the business name of Hydrologic, Inc. by (signature) D. Delaney
