	WATER WELL F	RECORD F	orm WV	VC-5 k	(SA 82a-12	12		
1 LOCATION OF WATER WELL:	FRACTION NW SV	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	1			P NUMBER		E NUMBER
Sedgwick	SHE 1/4 SHW	1/4 🖏	1/4	35	T 2	7 S	R	1E E/W
Distance and direction from nearest town or a	•	d within city?						
3318 Bellaire 2 WATER WELL OWNER: MO	Wichita, Kansas C CAMMON, Lois							
	18 Bellaire					Board of Agri	iculture, Division	of Water Reso
	ichita, Kansas		Z	P CODE:		Application Nun	nber:	
3 LOCATE WELL'S LOCATION	4 DEPTH OF Plugged	WELL: 2	2 ft.		ELEVATION:			
WITH AN "X" IN SECTION BOX:	Depth of groundwater Encour		ft.			ft.		ft.
	WELL'S STATIC WATER LE	VEL 12	FT. BELC	W LAND S	URFACE MEAS	URED ON mo/c	lay/yr: 8	/27/04
NWNE	Pump test of	data: Well wat	ter was		ft. after	hours	of pumping @	0
	Est. Yield: gpn				ft. after	hours	s of pumping @	
	Bore Hole Diameter	in.	to	ft	. and	in.	to	
	WELL WATER WORD USED 1. Domestic 3. Feedlot		ter supply	Z. Lawn	and garden on	9. Dewateri		njection wel (Specify be
		ial 6. Oil field w				10. Monitorin		(Shecus pe
s l	Was a chemical/bacteriological			YES	NO		what mo/day/y	
	submitted	· · · · · · · · · · · · · · · · · · ·		Was	Water Well Disin		YES	NO
5 TYPE OF CASING USED: 1. Steel 3. RPM	(SR) 5. Wrought Iron	7. Fiberglass	9. O	ther (Specify	y below) CAS	SING JOINTS:	Glued	Threade
2. PVC 4. ABS	6. Asbestos-Cemen	nt 8. Concrete ti	le				Welded	Clampe
Blank casing diameter 1 1/4	in. to t	ft., Dia.	in.	to	ft.,	Dia.	in. to	ft.
below basement fl Casing height above lead surface:	60 in.,	Weight:	R	bs. / ft.	Wall th	ickness or gaug	ae No. 🖕	
TYPE OF SCREEN OR PERFORATI		.						
1. Steel 3. Stainless Steel	5. Fiberglass	7. PVC	9. A	BS	11. Ol	ther (specify)	√/A	
2. Brass 4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. A	sbestos-Ce	ment 12. No	one used (open	hole)	
SCREEN OR PERFORATION OPEN	INGS ARE:							
1. Continuous slot 3. Mill	slot 5. Gauzed	wrapped	7. To	rch cut	9. Dril	led holes	11. None	e (open hole
2. Louvered shutter 4. Key	/ punched 6. Wire wra	apped	8. Sa	w cut	10. Oth	er (specify) N_{ℓ}	/A	
SCREEN - PERFORATION INTERVA	L From	ft. to		ft.,	From	ft.	to	ft
	From	ft. to		ft.,	From	ft.	to	f
GRAVEL PACK INTERVALS	: From	ft. to	i i	ft.,	From	ft. 🔳	to	fl
	From	ft. to	1	ft.,	From	ft.	to	fi
GROUT MATERIALS: 1, Ne	at cement 2. Ce	ement Grout		3. Bentonite	}	Other bent	onite hole	plug
Grout Intervals: From	0 ft. to 1	ft., From	ft.	to	ft.,	From 1	ft.	to 22
What is the nearest source of possible	7 54	<i>w</i> 1	0. Livestoc	k pens	13 Insect	icide storage	15 Oil we	ll/Gas well
• • • •			1. Fuel sto			lon water well		(specify bel
	page pit 9. Feed y	•	2. Fertilize	-		ion water wen		
3. Watertight sewer line 6. See Direction from well? North	page pit s. i eeu y		Z. I GIUNZE	storage	How m	any feet? 10		
From To	LITHOLOGIC LOG	}	From	То	[GIC LOG	
		····	0	1	cement grou			
			1	22	bentonite h	ole plug		
	· · · · · · · · · · · · · · · · · · ·			 				• • • • • •
				· · · · · · · · · · · · · · · · · · ·				
;	· · · · · · · · · · · · · · · · · · ·			ļ		<u> </u>	CENC	<u>-</u>
				 				12 r
	<u> </u>			<u> </u>		SEP	2 4 200	14
				ł				
						Bunan	じてアシング	NTER
		· · · ·	ļ	 				
<u>_</u>			I	L	L			
Contractor's or Landowner's Cer		1. constructed	2. re	constructe	d or 3. 🤇	plugged	under my juris	diction and
was completed on (mo/day/year)	8/27/2004	and this record	is true to the	best of my	knowledge and	belief.		
Kansas Water Well Contractor's Lic	ense No. 236	This water we	ell record wa	s completed	d on (mo/day/yea	ar) 8/30	/2004	
under the business name of Har	p Well & Pump Servi	ice Inc.	by (si	gnature)	ר	dd S.	11 .	
under the business name of Har	p wen & rump servi	ice mc.	by (0.	gnataro	-),	ndd S.	Ann	