WATER WELL RECORD F	orm WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION NW SW NW SW	SECTION NUMBER	TOWNSHIP NUMBER	RANGE NUMBER
Sedgwick 8 1/4 8 1/4 8 1/4 8 1/4	1/4 35	T 27 S	R 1E E/W
Distance and direction from nearest town or city street address of well if located within city?			
3318 Bellaire Wichita, Kansas			
2 WATER WELL OWNER: MC CAMMON, Lois		D	significate Division of Mater Resource
RR#,ST. ADDRESS,BOX #: 3318 Bellaire		Board of Ag	riculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Nu	mber:
3 LOCATE WELL'S LOCATION 4 DEPTH OF CHARGES WELL: 2.	3 ft.	ELEVATION:	
WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL 12	FT. BELOW LAND SU	JRFACE MEASURED ON mo/	/day/yr: 8/27/04
Pump test data: Well wa	er was	ft. after hour	s of pumping @ gpm
	ter was	ft. after hour	s of pumping @ gpm
Est. Yield: gpm Well wa	to ft.	and in.	to ft.
₩ELL WATER to SUSED AS:		9. Dewater	ina 11. Injection well
1. Domestic 3. Feedlot 5. Public wa	ter supply (Lawn a	and garden only	12. Other (Specify below)
2. Irrigation 4. Industrial 6. Oil field w	ater supply 8. Air cor		•
S Was a chemical/bacteriological sample submitted to I			what mo/day/yr was sample YES NO
submitted	vvas v	Vater Well Disinfected?	
TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass	Other (Specify	below) CASING JOINTS:	Glued Threaded
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete ti	le		Welded Clamped
Blank casing diameter 1 1/4 in to ft., Dia.	in. to	ft., Dia.	in, to ft.
below basement Cloor		•	
Casing height above the strate. 60 in., Weight: TYPE OF SCREEN OR PERFORATION MATERIAL:	lbs. / ft.	Wall thickness or gau	ige No. ←
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	11. Other (specify)	N/A
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Cer		
,	10. Assestos-Cel	nent 12. Hone asca (open	i riole)
SCREEN OR PERFORATION OPENINGS ARE:		0. 8.40. 4.1. 4.	44 Nove Constitution
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify) N	I/A
SCREEN - PERFORATION INTERVAL From ft. to	ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS: From ft. to		From ft.	
	10.1	-	to ft.
From ft. to	ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite		tonite hole plug
Grout Intervals: From 0 ft. to 1 ft., From What is the nearest source of possible contamination:	ft. to	ft., From $oldsymbol{1}$	l ft. to 23 ft
1. Septic tank 4. Lateral lines 7. Pit privy	0. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
1 ·	1. Fuel storage	14. Abandon water well	16. Other (specify below)
	2. Fertilizer storage		
3. Watertight sewer line 6. Seepage pit 9. Feed yard 1 Direction from well? North		How many feet? 10	
From To LITHOLOGIC LOG	From To		OGIC LOG
		cement grout	30.0200
		bentonite hole plug	* * ' . '
		\	
			······································
			EP 2 4 2004
		EUR	INU CHANAIA
		······································	
	L		
Contractor's or Landowner's Certification: This water well was 1. constructed	2. reconstructed	or 3. plugged	under my jurisdiction and
was completed on (mo/day/year) 8/27/2004 and this record is true to the best of my knowledge and belief.			
, , , , , , , , , , , , , , , , , , , ,			
under the business name of Harp Well & Pump Service Inc. by (signature) Jo d d S. Harp			