WATER WELL RECORD	Form WV	/C-5 K	SA 82a-1212		
1 LOCATION OF WATER WELL: FRACTION NE 1/4 SW 1/4 NE	1	ION NUMBER	1	RANGE NUMBER R 1E E/W	
Sedgwick NE 1/4 SW 1/4 NE Distance and direction from nearest town or city street address of well if located within city?	2 1/4	21	T 27 S	R IE E/W	
256 Ohio Wichita, Kansas					
2 WATER WELL OWNER: ST ANTHONY'S CHURCH			Board of A	griculture, Division of Water Resource	
RR#,ST. ADDRESS,BOX #: 256 Ohio		6'			
CITY, STATE: Wichita, Kansas	24 ft.	P CODE: 6	Application N	lumber:	
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	27 11.			ft.	
Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 12	FT BELO		n ent floor ft. Irrade measured on mi	10/10/01	
	vater was			urs of pumping @ gpm	
1 1 X 1 X 1 1 =	water was		ft. after hou	urs of pumping @ gpm	
Est. Yield: gpm Well	to	ft.		to ft.	
4	water supply	7. Lawn a	9. Dewate	ering 11. Injection well 12. Other (Specify below)	
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well					
S Was a chemical/bacteriological sample submitted submitted	to Department?	YES	NO ; If yes	s, what mo/day/yr was sample YES NO	
TYPE OF CASING USED:	0.0				
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fibergla	ss 9. O	ther (Specify	below) CASING JOINTS	Welded Clamped	
2. PVC 4. ABS 6. Asbestos-Cement 8. Concret	e tile				
Blank casing diameter 8 in. to ft., Dia. Casing height above land surface: in., Weight:	in.	to	ft., Dia.	in. to ft.	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) N/A					
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. To	rch cut	9. Drilled holes	11. None (open hole)	
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Sa	w cut	10. Other (specify)	N/A	
SCREEN - PERFORATION INTERVAL From ft.	to	ft.,	From ft.	to ft.	
From ft.	to	ft.,	From ft.	to ft.	
GRAVEL PACK INTERVALS: From ft.	to	ft.,	From ft.	to ft.	
From ft.	to	ft.,	From ft.	to ft.	
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3	B. Bentonite	Other be	ntonite hole plug	
Grout Intervals: From 0 ft. to .5 ft., From ft. to ft., From .5 ft. to 24 ft. What is the nearest source of possible contamination:					
1. Septic tank 4. Lateral lines 7. Pit privy	10. Livestoc	k pens	13. Insecticide storage	15. Oil well/Gas well	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)					
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage					
Direction from well? West From To LITHOLOGIC LOG	From	То	How many feet? 10	OGIC LOG	
FIGHT 10 ETTHOLOGIC LOG	0	.5	cement grout	.0010 L00	
	.5	,	bentonite hole plug		
			REC	EIVED	
			kinti a		
			NOV 0 1 2004		
			BURFAU	OF WATER	
		L			
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and					
was completed on (mo/day/year) 10/18/2004 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 10/20/2004					
under the business name of Harp Well & Pump Service Inc. by (signature) Jo d d S. Harp					