				ER WELL RECORD							-
1 LOCATION					1 '	Section N		Township Nur		Range No	
County:			SE ½		NW ¼			т 27	s	R 1	E
	direction from		vn or city street a	ddress of well if loo	cated within city	?					
2 WATER W	ELL OWNE	R:	Kansas Me	etals c/o Chu	ck Efflandt						
RR#, St. Addr	ress, Box#	:	100 N. Bro	adway Ste.	700			Board of Agricu	lture, Divisi	on of Water F	Resources
City, State, ZI			Wichita, K	S 67202				Application Nun			
, LOCATE V		ATON WITH	4	COMPLETED WE	1.1	17 #	ELEV/A			38 (TOC)	
	N	Ο Λ.			 .d 4	12		TION:		20 71 991	
			Depui(s) Ground	dwater Encountere	4474	-!	IL. 2		II. 3	0.44	II.
\perp	<i>.</i>			WATER LEVEL							
- 1	С _W	NE		p test data: Well							
. W ∰		i E	Est. Yield	gpm: Well	water was		ft. a	after	_ hours pu	mping	gpm
÷ "		_	Bore Hole Diam	eter 8.5 ii	n. to	1/	ft	. and	in. 1	to	ft.
	sw	, SE	1 Domesti	eter 8.5 in TO BE USED AS: c 3 Feed lot	6 Oil field wa	r suppiy ter suppiy	,	8 Air conditions	ng 11 12	Other (Speci	i ifv helow)
	1	1	2 Invigation	4 Industrial	7 1		, 	40 Manifesian		Outor (Opcor	ily bolow,
* <u> </u>				4 Industrial							
	S		I	/bacteriological sa	mple submitted	to Depart	tment? Ye	es No X	If yes, n	no/day/yr sam	nple was
			submitted					Well Disinfected			
5 TYPE OF				5 Wrought Iro				CASING JOINT	S: Glued	Clam	nped
		_	(SR)	6 Asbestos-C	ement 9 Ott	ıer (speci	ify below)		Welde		
2 PVC		4 ABS		7 Fiberglass						ed Flu	
Blank casing	diameter	2	in. to 7	ft., Dia		n. to		ft., Dia	i	n. to	ft.
Casing height	above land	surface	2.57	in., weight	0.703		lbs./ft. W	all thickness or a	auge No.	Sch.	40
TYPE OF SC	REEN OR P	ERFORATIO	N MATERIAL:			7 PVC		10 Asbes	tos-cemen	t	
1 Steel	l	3 Stainle	ess steel	5 Fiberglass	-	8 RMP	(SR)	11 Other	(specify)	• • • • • • • • • • • • • • • • • • • •	
2 Brass	S	4 Galva	nized steel	5 Fiberglass6 Concrete tile	е	9 ABS		12 None	used (open	i hole)	
SCREEN OR	PERFORAT				Gauzed wrappe	ed .		8 Saw cut	1	1 None (ope	en hole)
1 Conti	inuous slot	3	Mill slot	6	Wire wrapped			9 Drilled holes			
2 Louve	ered shutter	4	Key punched	7	Torch cut		1	0 Other (specify	/) <u> </u>		
SCREEN-PER	RFORATED	INTERVALS:	From	7 ft. to	17		ft. Fro	m	ft. to		ft.
				ft. to							
GRA\	/EL PACK IN	NTERVALS:	From	5 ft. to	17		ft. Fro	m	ft. to		ft.
				ft. to							
6 GROUT M	ATERIAL:	1 Neat		? Cement grout			_	Other			
						# to		# From		4 4-	
M/hat is the ne	arest source	of possible	contamination:	ft. From	• • • • • • • • • • • • • • • • • • • •	1. 10	Livorton	π. From ck pens	14 Abor	it. to idoned water	
1 Septi				7 Pit	t oring	10	Eugl sto	rage	14 Abar		
2 Sewe			5 Cess pool		ewage lagoon		Fertilize			r (specify bek	
	rtight sewer	lines	6 Seepage pit		edyard			ide storage	TO Othe	1 (Specify ben	OW)
Direction from	•		o coopage pa	0.10	,0 0 ,0,0		many fe	-			
FROM	TO	CODE	LITHOI	LOGIC LOG	FRO		го		GING INT	ERVALS	
0	0.5		phalt								
0.5	7		l, clay, sand								
_ 1			nd, fine to m	ned grained,							
7	17	ро	orly graded			-			SECF	WED	
					RECEIV						
				-					0 200A		
									AUA S	9 2004	
										- NAIATE	D
-								80	REAU (OF WATE	-17
								1			
7 CONTRAC	CTOR'S OR	LANDOWNE	R'S CERTIFICAT	ION: This water w	ell was (1) cons	tructed.	(2) recons	structed, or (3) plu	gged under	my jurisdictio	n and was
_			10-		_			to the best of my		,	
								or was completed			
INSTRUC	CTIONS: Ple	ase fill in blank	s and circle the cor	I Services, In rect answers. Send	three copies to K	ansas De	parmento	f Health and Enviro	nment. Bur	au of Water 1	1000 S W
Jackson	St., Ste. 420,	Topeka, Kansa	as 66612-1367. Te	lephone: 913-296-5	545. Send one to	WATER	WELL OW	NER and retain on	e for your re	cords.	