	WATER WELL	RECORD F	Form WV	/C-5 K	SA 82a-12	12		
1 LOCATION OF WATER WELL:	FRACTION		SEC	TION NUMBE		P NUMBER	RANGE NUM	MBER
Sedgwick	NE 1/4 SV		1/4	19	Т 2	7 s	R 1E	E/W
Distance and direction from nearest town or			_					
McLean Blvd. and Athen		Wichita, I	Cansas					
	CHITA, CITY OF					Board of Agric	culture, Division of Wa	ter Resource
	5 N. Main						20040	
	ichita, Kansas		_	P CODE:		Application Num	ber: 20040	202
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETE	D WELL: 4	<b>8</b> ft.		ELEVATION:			
N	Depth of groundwater Enco	untered:	ft.			ft.		ft.
1 1	WELL'S STATIC WATER I	EVEL 20	FT. BELO	W LAND SI	JRFACE MEAS	URED ON mo/d	ay/yr: 1/3/0	5
NE	Pump tes	t data: Well wa	ter was		ft. after	hours	of pumping @	gpi
<u>o</u>	Est. Yield: g	pm Well wa	ter was		ft. after	hours	of pumping @	gpr
W Sile	Bore Hole Diameter	12 in.	to 4	5 ft	. and	in.	to	ft.
	WELL WATER TO BE USE	-				9. Dewaterin	ng 11. Injecti	ion well
9W 9E	1. Domestic 3. Feedi		iter supply		and garden onl		12. Other (Spe	cify belov
	2. Irrigation 4. Indus				nditioning	10. Monitorin	=	
s	Was a chemical/bacteriological submitted	al sample submitted to l	Department?	YES Was l	NO Water Well Disin		/hat mo/day/yr wa	-
5 TYPE OF CASING USED:	GGOTTINGG						=	
1. Steel 3. RPM	(SR) 5. Wrought Iron	7. Fiberglass		ther (Specify	y below) CA	SING JOINTS: C		hreaded
2. PVC 4. ABS	6. Asbestos-Cem	ent 8. Concrete t	ile SD	R-26			Welded (	Clamped
Blank casing diameter 8	in. to <b>20</b>	ft., Dia.	in.	to	ft.,	Dia. i	n. to	ft.
•	26	·			,			11.
Casing height above land surface:	*****	Weight:	5.52	os. / ft.	Wall th	nickness or gaug	e No332	
TYPE OF SCREEN OR PERFORATI  1. Steel 3. Stainless Stee		7. PVC	9. A	RS.	11 O	ther (specify)		
				-			noio)	
2. Brass 4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. A	sbestos-Ce	ment 12. N	one used (open l	iole)	
SCREEN OR PERFORATION OPEN								
1. Continuous siot 3. Mill	slot 5. Gauze	d wrapped	7. <b>To</b>	7. Torch cut		9. Drilled holes 11		en hole)
2. Louvered shutter 4. Key	punched 6. Wire w	/rapped	8. Sa	w cut	10. Oth	er (specify)		
SCREEN - PERFORATION INTERVA	L From 20	<b>D</b> ft. to	40	ft.,	From	ft.	to	ft.
	From	ft. to		ft.,	From			
GRAVEL PACK INTERVALS	24	_				ft.	to	ft.
GRAVEL FACK INTERVALS				ft.,	From	ft.	to	ft.
	From	ft. to	)	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Ne	at cement 2. (	Cement Grout	:	B. Bentonite	•	Other bento	onite hole plug	5
Grout Intervals: From	0 ft. to 20	ft., From	ft.	to	ft.,	From	ft. to	ft.
What is the nearest source of possible	7 Dit n	rivy	I0. Livestoc	k pens	13 Insect	icide storage	15. Oil well/Ga	s wall
1. Sepuc tank 4. Lateral lines						· ·	16. Other (specify below)	
2. Sewer lilles 0. Cess i Col			11. Fuel sto	_	14. Abanc	ion water well	None Apparent	
3. Watertight sewer line 6. See	page pit 9. Feed	yard	12. Fertilize	r storage			None App	ai Ciit
Direction from well?			<del></del>	·	How m	any feet?		
From To	LITHOLOGIC LO	G	From	То	ļ	LITHOLO	GIC LOG	
0 4 topsoil					<u> </u>			
4 12 clay			+	<b></b>				
12 18 loose fill 18 48 coarse sand	and gravel			<del>                                     </del>	<u> </u>			
16 46 COALSE SAIIC	I aliu gravei							
	<del></del>							
				<u> </u>				
					<u> </u>			
			ļ					
			<u> </u>	<u> </u>	<u></u>			
Contractor's or Landowner's Cer	rtification: This water well w	as 1. constructed	2. re	constructe	d or 3.	plugged u	ınder my jurisdictio	n and
was completed on (mo/day/year)	1/03/2005	and this record	is true to the	best of my	knowledge and	belief.		
Kansas Water Well Contractor's Lic	ense No. 236			•	d on (mo/day/yea		2005	
				•	, , ,			
under the business name of Har	p Well & Pump Ser	vice Inc.	by (si	gnature)	7	odd S.	Ш.,,	