WATER WELL RECORD Form WWC-5 KSA 82a-1212																
1 LOCATION OF WATER WELL: Sedgwick				FRACTION SW 1/4 SW 1/4 SE				SECTION NUMBER			TOWNSHIP NUMBER			RANGE NUMBER		
9		m nearest town or o			SW if located w		SE 1	/4	8	т	27	S	R	1 <b>E</b>	E/W	
1	Rodches		hita, Kan		ii located w	vitalia City:										
_	ER WELL C		ORTH H		CHOOL	L (USD	259)									
RR#,ST.	. ADDRESS		37 Ro€cl								В	ard of Ag	riculture, Divisi	on of Wa	ter Resource	
	CITY,	STATE: Wi	ichita, K	ansas			- 15	ZI	P CODE:		- ::	cation Nu	mber:			
	E WELL'S LO AN "X" IN SEC	TION BOX:	<u>ت</u>	OF COMPI			45	ft.		ELEVATIO	N:					
	N N		Depth of gro					ft.				ft.		0/04//	ft.	
			WELL'S ST						W LAND S	SURFACE ME				8/31/6		
0	- <b>WM</b>	<del>NE</del>	Est. Yi		np test da gpm		II water v II water v			ft. after ft. after			s of pumping s of pumping	_	gpm gpm	
w Mile		E	Bore Hole		12		ii water	to 4	5 i	ft. and		in.	o or pomping	to	ft.	
-	:	, ,	WELL WAT	TER TO BE	E USED A						9.1	Dewater	ing 11	. Injecti	on well	
11	-SW	- SE	1. Domes		Feedlot					and garden				er (Spe	cify below)	
∟	<u> </u> X		2. Irrigation		Industrial iological sar	l 6. Oil fie mple submitte			8. AIT CO	onditioning	<b>\</b>		i <b>ng well</b> what mo/da	y/yr wa	s sample	
	3		submitted	THOSE DACTOR	iorogical sai		- To Dept	arumont:		Water Well D	isinfected	?	YES	NC		
	PE OF CAS		5.	Wrought	Iron	7. Fiberg	lass	9. Ot	her (Speci	fy below)	CASING J	OINTS:	Glued	7	hreaded	
l	1. Steel	3. RPM (	(SR)	Asbestos		8. Concr		SDI	R-26				Welded	(	Clamped	
_	2. PVC sing diamete	> 4. ABS or 5	in.							4	D:-					
	-		12		25 ft.,			in. 35	to	ft.,	Dia.			0	ft.	
		land surface: OR PERFORATI		in.,		Weight:	2	35 It	os. / ft.	Wa	all thicknes	s or gau	ige No.	.214		
1. Stee		. Stainless Steel		iberglass		7. PVC		9. A	BS	11	. Other (s	ecify)				
2. Bras	ss 4	. Galvanized		oncrete Ti	le	8. RMP (\$	SR)	10. A	sbestos-Ce	ement 12	None us	ed (oper	n hole)			
SCREEN	OR PERFO	RATION OPEN	INGS ARE:													
1. Conti	inuous slot	3. Mill	slot	5. <b>G</b>	auzed w	rapped		7. <b>To</b>	rch cut	9. [	Drilled ho	les	11. No	ne ( op	en hole)	
2. Louve	ered shutte	r 4. Key	y punched	6. <b>V</b>	Vire wrap	ped .		(8. Sa	w cut	10. 0	Other (sp	ecify)				
SCREEN -	- PERFORA	TION INTERVA	L Fro	ım.	25	ft.	to	45	ft.,	From		ft.		•	ft.	
			- Fro		-	ft.	to	10	ft.,	From		ιι. ft.		0	ft.	
GRAVEL PACK INTERVALS:					24	ft.	to	45	ft.,	From		ft.		0	ft.	
			Fro			ft.	to		ft.,	From		ft.		0	ft.	
6 GRO	UT MATERI.	ALS: 1 No.	at cement		2 Com	ent Grout			Bentonit		Other		tonite hol			
	Intervals:	From	4 ft.	to		ft., Fro	om	ft.	to	ft.,			ft.	to	ft.	
ı		urce of possible	e contaminateral lines			,		Livestoc								
1. Seption	Pit privy				-		ecticide s	_	40 046	well/Gas	ify below)					
2. Sewe	er lines	5. Ces:			Sewage	-		Fuel stor	-	14. <b>Ab</b>	andon wa	ter well		е Арр		
1	rtight sewe from well?	r line 6. See	page pit	9.	Feed yar	d	12. I	Fertilizer	storage	How	v many fee		11011	· APP	41 0110	
From	To		LITHO	LOGIC	LOG			From	То	How			OGIC LO	G		
0	4	topsoil										1102	<u> </u>			
4	10	clay														
10 15	15 45	fine sand														
	45	medium coa	arse sand	1			-									
														***		
	<u> </u>									-						
						<del></del>	+			-						
	-															
							-									
7 Cont	tractor's or !	andowner's Cer	tification: T	hie water :	vell was 4	constru	-ted	2	constructe	ed or 3.	plugg	ed	under my ju	risdiction	and	
$\vdash$				nis water v 1/2005									shoot my ju	.00101101		
l .		(mo/day/year)							•	y knowledge a		0.14	/2007			
1		Contractor's Lice		23	-		er well re		•	ed on (mo/day/			/2005			
under th	e business	name of Har	p Well &	<sup>k</sup> Pump	Service	e Inc.		by (sig	gnature)		To do	l S.	Harp			