

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		NE ¼ SE ¼ SW ¼	4	T 27 S	R 1 E W
Distance and direction from nearest town or city street address of well if located within city? 26th and Washington, Wichita, KS					
2 WATER WELL OWNER: FI Kansas Remediation Trust					
RR#, St. Address, Box # : 4400 College Blvd., Suite 350			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Wichita, KS 67123			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 25 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 16.3 ft. below land surface measured on mo/day/yr 10-18-05 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Domestic (lawn & garden) 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yrs sample was submitted Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
Blank casing diameter 2" in. to 1.5 ft., Dia		8 Concrete tile		CASING JOINTS: Glued Clamped	
Casing height above land surface -2 in., weight		9 Other (specify below)		Welded	
TYPE OF SCREEN OR PERFORATION MATERIAL:		PVC		Threaded X	
1 Steel		3 Stainless Steel		10 Asbestos-Cement	
2 Brass		4 Galvanized Steel		11 Other (Specify)	
		5 Fiberglass		12 None used (open hole)	
		6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:		5 Guazed wrapped		8 Saw cut	
1 Continuous slot		8 Mill slot .010		9 Drilled holes	
2 Louvered shutter		4 Key punched		10 Other (specify)	
		6 Wire wrapped		11 None (open hole)	
		7 Torch cut			
SCREEN-PERFORATED INTERVALS: From 25 ft. to 1.5 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 25 ft. to 1.3 ft., From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout		3 Bentonite	
Grout Intervals: From 1.3 ft. to 1 ft., From ft. to ft.		4 Other			
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
Direction from well? 999		10 Livestock pens		14 Abandoned water well	
		11 Fuel storage		15 Oil well/Gas well	
		12 Fertilizer storage		16 Other (specify below)	
		13 Insecticide storage			
		How many feet? 999			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
20	20.5	Sand-med to very coarse	25	13	10/20 Sand
20.5	17	Sand-very fine to fine	13	1	3/8 Bentonite Chips
17	16	Clay-light brown			
16	11	Sand-very fine to fine			
11	1	Clay-dark grey and brown			
1	0	Gravel fill			MW-5S
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-18-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 665 . This Water Well Record was completed on (mo/day/yr) 10-26-05 under the business name of Pratt Well Environmental by (signature) <i>[Signature]</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					