		WA	TER WELL RE	CORD F	orm WWC-5	KSA 82a	1212 ID	No					
LOCATION OF WATER WELL: County: Sedgwick			Fraction	BTT-7	CE		ction Numbe	er Tov	wnship Nu	mber	Ran	ge Nun	_
			NE 1/4		-	4	21		27	S	R	1	E)W
		from nearest tov	-		vell if located	within city?							
2nd and Indiana, Wichita, KS  WATER WELL OWNER: KS Dept. of Health and EnviroDry Cleaning Fac. Rel. Trust Fund													Бn
		# : 1000					ry cre	_			ivision of V		
City, State,	ZIP Code	Tonek	a KS 6	6612				Ap	plication	Number:			
		CATION WITH	4 DEPTH OF	COMPLETE	WELL	5.6	ft. ELE	VATION:					
AN "X" IN	SECTION N	BOX:	Depth(s) Grou	ndwater Enc	ountered	1 51 # bel	ow land sur	ft. 2	od on mo	ft. 3	5-18-	05	ft.
					vater Encountered 1								
	-NW	- NE		st. Yield gpm: Well water was									
	1	1		ZELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)									ow)
w	1	E	2 Irrigation										
SW SE   Was a chemical/bacteriological sample submitted to Department? Yes NoX; If yes, mo/day/yrs si													
	<u> </u>		mitted					water weil i	Distriecte	u? tes		NO	) Х
E TYPE C	S BLANK (	CASING USED:		E Mrauch	+ ivan	O Conor	ata tila		SING IOI	NTC: Clus	4 0		4
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SF			٦)	5 Wrought iron 6 Asbestos-Cement		8 Concrete tile 9 Other (specify b			SING JOII		d C led		
PVC 4 ABS			7 Fiberglass								ledX adedX		
Blank casing diameter2													
			in., we	ignt	<b>∂</b> P\		IDS./ft. Wa		ss or guag estos-Cem		<u> </u>	±	
TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless Steel				5 Fibergla	ass		8 RMP (SR)				)		
2 Brass	s	4 Galvaniz	6 Concret	6 Concrete tile		9 ABS		12 Non	e used (op	en hole)			
SCREEN OR PERFORATION OPENINGS ARE: 5 Guazed wrapped 8 Saw cut 11 None (open h 1 Continuous slot 3 Mill slot 0.1.0 6 Wire wrapped 9 Drilled holes											hole)		
	inuous slot ered shutte		ill slot .010 ey punched	1	7 Torch				ed holes er (specify	)			ft.
				23.6	ft. to	.8	ft Fro	om		ft. <b>t</b> o			ft.
SCREEN-PERFORATED INTERVALS:         From         23.6         ft. to         8         ft. From         ft. from         ft. to         ft. from           GRAVEL PACK INTERVALS:         From         23.6         ft. to         6.6         ft. From         ft. from         ft. to         ft. from													ft.
G		CK INTERVALS:			ft. to ft. to								
	10/20				ent grout								
	T MATERIA	tonite											
Grout Inter		n 6,6		.Ω ft., I	-rom	π.		ft., Fi estock pens			π. to bandoned		
What is the nearest source of possible contamination:  1 Septic tank  4 Lateral lines					7 Pit privy			estock pens el storage			oll well/Gas		Well
Sewer lines 5 Cess-pool					8 Sewage	agoon	•						
3 Wate	ertight sewe	er lines 6 Seep	age pit	ge pit 9 Feedyard			13 Insecticide storaç						
Direction fro		West						nany feet?	10				
FROM	TO		LITHOLOGI	C LOG		FROM	то		PLU	gging in	TERVALS		
5	<u>5</u> 25	Clay	nd avers	. 1									
	25	Sanus a	nd grave	:1									
									AMW-	-7			
71			11-211-21-21								- 2100		
△ CONTRA	ACTOR'S C	R LANDOWNE (ear) 05-	R'S CERTIFICA	ATION: This	water well wa	as (1) constr	ucted, (2) re	econstructed	, or (3) pl	ugged und	der my juris	diction	and was
completed o	n (mo/day/y Contractor's	ear)	665	••••••	This Water	Well Booord	and this	record is true	e to the be	ist of my kr りらっつり	nowledge ar A _ ∩ 5	nd belie	₃f. Kansas
under the bu			att Well					y (signature)		m c			
									Juni	11 6	ny		