			WATER W	ELL RECO	ORD Fo	orm WW	C-5 K	SA 82a-1212			
111	OF WATER	WELL:	FRACTION	NIE			ON NUMBER			RANGE N	
Sedgw			SE 1/4	NE 1/4		1/4	8	т 27	S	R 11	C E/W
Distance and direction from nearest town or city street address of well if located within city? 15th St. North and Ferrell Wichita, Kansas											
2 WATER WELL OWNER: WICHITA, CITY OF											
⊢ J	RR#,ST. ADDRESS,BOX #: 455 N. Main							Board of Agriculture, Division of Water Reson			
	CITY, S		nita, Kansas			ZIP	CODE:		Application Num	nber: 2006	50121
3 LOCATE	WELL'S LO	CATION 4	DEPTH OF COMP	LETED WELL	: 40	ft.		ELEVATION:			
WITH A	N "X" IN SECT	FION BOX: De	pth of groundwate	r Encountered:		ft.			ft.		ft.
		W	ELL'S STATIC WA	ATER LEVEL	17	FT. BELOV	V LAND SU	RFACE MEASUR	RED ON mo/o	lay/yr: 4/12	2/06
Pump test data: Well water was ft. after hours									of pumping @	gpm	
w Wile	1	' i i	Est. Yield:	gpm	Well water		_	ft. after	hours	of pumping @	gpm
			ore Hole Diamete		in.	to 40) ft.	and	in.	to	ft.
	WELL WATER TO BE USED AS: 9 Dewatering 11. Injection well 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify be										
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below) 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well											
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample											
submitted Was Water Well Disinfected? YES NO											
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded 1. Steel 3. RPM (SR) Welded Clamped											
l	Steel PVC	3. RPIVI (SI	6. Asbesto	s-Cement 8	. Concrete tile	, SDR	2-26			Welded	Clamped
	ng diamete	_	in. to	20 ft.,	Dia.	in.	to	ft., [Dia.	in, to	ft.
1		land surface:	12 in.,	,			s. / ft.		ckness or gaug		
1	-		,		weight.	0.02	S. / IL.	VVGII UIK	Skiless of gad	ge 110. •332	•
	TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)										
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1. Conti	nuous slot	3. Mill sl	lot 5.	Gauzed wrapp	oed	7. Tor	ch cut	9. Drille	ed holes	11. None (open hole)
2. Louve	red shutte	r 4. Key p	unched 6.	Wire wrapped		8. Sav	v cut	10. Othe	r (specify)		
SCREEN -	PERFORA	TION INTERVAL	From	20 ft.	to	35	ft	From	ft.	to	ft.
			From	ft.	to		ft.,	From	ft.	to	ft.
G	RAVEL PAG	CK INTERVALS:	From	20 ft.	to	40	ft.,	From	ft.	to	ft.
			From	ft.	to		ft.,	From	ft.	to	ft.
6 GROU	JT MATERI.	ALS: 1 Nest	cement	2. Cement	Grout	2	Bentonite			tonite hole pl	
	ntervals:	From 0	ft. to	••	From	ft.	to	ft.,	From	ft. to	
What is the nearest source of possible contamination:											
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas 16. Other (speci											
2. Sewe	r lines	5. Cess	1 001	8. Sewage lage		1. Fuel stor	-	14. Abando	on water well	•	pparent
1	tight sewe	r line 6. Seepa	age pit	9. Feed yard	1	2. Fertilizer	storage			None A	pparent
Direction		· · · · · · · · · · · · · · · · · · ·	LITHOLOGI	CLOG		Erom	То	How ma	ny feet?	OGIC LOG	
From 0	To 4	top soil	LITHOLOGI	C LOG		From	10	<u> </u>	LITHOL	JGIC LOG	
4	15	clay									
15	31	medium san	d								
31	40	medium san	d								

								-			
									- ***		
	_			****				 			
						L					
7 Contractor's or Landowner's Certification: This water well was 1, constructed 2, reconstructed or 3, plugged under my jurisdiction and											
was co	mpleted on	(mo/day/year)	4/12/2000	6 an	d this record	is true to the	best of my	knowledge and b	pelief.		
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4/14/2006											
under th	ne business	name of Harn	Well & Pum	n Service I	nc.	by (si	gnature)	а	110	11	
1		Traip	, ,, on or I ull	.p 551 1166 1		, ,	- ,	Jo	dd S.	Harp	