WATER WELL REC	ORD Form		SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	, BTXXT	SECTION NUMBER		RANGE NUMBER
Sedgwick NW 1/4 SE 1/		8	T 27 S	R 1E E/W
Distance and direction from nearest town or city street address of well if located within city?  1841 Jeanette Wichita, Kansas				
2 WATER WELL OWNER: GOEHRING, Roxanne				
RR#,ST. ADDRESS,BOX #: 1544 N. Sedgwick			Board of Agri	iculture, Division of Water Resource
CITY, STATE: Wichita, Kansas		ZIP CODE:	Application Nun	nber:
3 LOCATE WELL'S LOCATION 4 DEPTH OF CHARGE WEL	<u>.</u> 27	ft.	ELEVATION:	mbor.
WITH AN "X" IN SECTION BOX:  Depth of groundwater Encountered		ft.	ft.	ft.
WELL'S STATIC WATER LEVEL			JRFACE MEASURED ON mo/o	
Pump test data:	Well water wa			
	Well water wa			s of pumping @ gpm s of pumping @ gpm
Est. Yield: gpm	in.	to ft.		to ft.
₩ELL WATER VIASUSED AS:			9. Dewateri	44 1 4 4 4 4
	5. Public water su		and garden only	12. Other (Specify below)
	6. Oil field water			ng well what mo/day/yr was sample
S Was a chemical/bacteriological sample submitted	e submitted to Departi		NO ; if yes, Yater Well Disinfected?	YES NO
5 TYPE OF CASING USED: 5 Wrought Iron		9. Other (Specify		Glued (Threaded)
1. Steel 3. RPM (SR)	7. Fiberglass	a. Other (Specify	below) CASING JOINTS.	Welded Clamped
2. PVC 4. ABS 6. Asbestos-Cement	8. Concrete tile			violate olamped
Blank casing diameter 1 1/4 in. to ft.,	Dia.	in. to	ft., Dia.	in. to ft.
Casing height couldn't surface: 60 in.,	Weight:	lbs. / ft.	Wall thickness or gau	ge No.
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1. 0.00	. PVC	9. ABS	11. Other (specify)	N/A
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:				
1. Continuous slot 3. Mill slot 5. Gauzed wrap	ped	7. Torch cut	9. Drilled holes	11. None ( open hole)
2. Louvered shutter 4. Key punched 6. Wire wrappe	d	8. Saw cut	10. Other (specify) N	J/A
SCREEN - PERFORATION INTERVAL From ft.	to	4	From #	
From ft.		ft.,	From ft.	to ft.
	_	ft.,	From ft.	to ft.
		ft.,	From ft.	to ft.
From ft.	to	ft.,	From ft.	to ft.
GROUT MATERIALS: 1. Neat cement 2. Cemen		3. Bentonite		tonite hole plug
Grout Intervals: From ft. to ft., What is the nearest source of possible contamination:	From	ft. to	ft., From 5	5 ft. to 27 ft.
1. Septic tank 4. Lateral lines 7. Pit privy	10. <b>Li</b>	vestock pens	13. Insecticide storage	15. Oil well/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lag	joon 11. Fi	uel storage	14. Abandon water well	16. Other (specify below)
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage				
Direction from well? West		• • • • • • • • • • • • • • • • • • • •	How many feet? 30	ft.
From To LITHOLOGIC LOG	F	rom To		OGIC LOG
		0 5	compacted earth	
		5 27	bentonite hole plug	
	<u>_</u>	-		
7 Contractor's or Landowner's Certification: This water well was 1, constructed 2, reconstructed or 3, plugged under my jurisdiction and				
was completed on (mo/day/year) 6/30/2006 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No. 236  This water well record was completed on (mo/day/year)  7/3/2006				
, , , ,				
under the business name of Harp Well and Pump Service by (signature)				