*	1			ER WELL RECORD	Form WW	C-5 KSA 8	2a-1212			
		ATER WELL:	Fraction			ection Numb		per	Range Number	
	Sedgwic		SE 3	4 SE 1/4 SV	N 1/4	21	Т 27	SR	1 EW	
			own or city stree	t address of well if locat	ed within c	ity?				
811 E.	Waterma	ın, Wichita	,							
2 WATE	R WELL C	WNER: Sam H	ordogo							
				C4 - 200						
City Ctaty	Audiess, Di	ox# : 12671]					Board of Agricultu		Water Resources	
City, State, ZIP Code : San Diego, California 92130 3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL					Application Number:					
3 LOCA	IE WELL'S	LOCATION	4 DEPTH OF C	COMPLETED WELL	28	ft. ELE	VATION:			
VVIIII	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N Depth(s) Groundwater Encountered 1									
Τ Γ	1									
1	WELL'S STATIC WATER LEVEL									
ŀ	Est. Yield . NA gpm: Well water was									
ο										
M g	Bore Hole Diameter 8 in. to 28 ft., and in. to									
-	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well									
i.	CW	SE	1 Domestic	3 Feedlot 6	Oil field wa	ater supply	9 Dewatering	(12) Other (Specify below)	
ıl	SVV	7 7	2 Irrigation	4 Industrial 7	Lawn and	garden only	10 Monitoring well	Air s	oarge	
. <u>†</u>	X	1	Was a chemic	al/bacteriological sample	submitted	to Departme	nt? YesNo√	; If yes, mo/da	y/yr samole was	
	1	S	submitted			V	/ater Well Disinfected?	Yes	No √	
5 TYPE	OF BLANK	CASING USED:		5 Wrought iron	8 Con	crete tile	CASING JOINTS	S: Glued	Clamped	
1 S		3 RMP (SI		6 Asbestos-Cement		er (specify be				
		4 ABS	7	7 Fiberglass					/	
			in to 3	5.5ft., Dia					•	
	_			. in., weight			•		Scn40	
TYPE OF	SCREEN C	R PERFORATION	N MATERIAL		(7) P		10 Asbest	os-cement		
1 S	teel	3 Stainless	s steel	5 Fiberglass	8 R	MP (SR)	11 Other (specify)		
2 B	rass	4 Galvaniz	ed steel 6 Concrete tile			BS	12 None u	None used (open hole)		
SCREEN	OR PERFO	RATION OPENIN	GS ARE: 5 Gauzed wra				8 Saw cut	11 None (open hole)		
1 C	ontinuous s	slot (3)M	lill slot		vrapped		9 Drilled holes		(-)	
2 1	ouvered shi		ey punched	7 Torch	• •		10 Other (specify) .			
		ED INTERVALS:	From	. 25.5 ft. to		ft E				
00.122.1		LO MITELLIA	From	ft. to			rom	ft to	ft	
	DAVEL DA	CK INTERVALS:	From	. 23.5 ft. to	28		rom	# 10	44	
	SIVAVEL FA	ICK INTERVALS.								
				ft. to						
	T MATERIA		cement	2 Cement grout	(3)Ben	tonite	Other Concrete			
Grout Inte	rvals: Fro	m	.ft. to2.	ft., From	2 ft	. to 23.	5 ft , From	ft. t	o ft	
What is th	e nearest s	ource of possible	contamination:			10 Liv	estock pens	14 Abandor	ed water well	
1 Septic tank 4 Lateral lines 7 Pit privy							el storage	15 Oil well/0	Sas well	
-		5 Cess		on	12 Fertilizer storage 16 Other (specify be					
2 Sewer lines 5 Cess 3 Watertight sewer lines 6 Seep			•	011	13 Insecticide storage			been'y below,		
	•	illies o deep	page pit 9 Feedyard			How many feet?				
Direction f	TO TO		LITHOLOGIC	10G	FROM	TO		GING INTERV	ALS	
		C		100	FROW	10	FLOG	SING INTERV	ALO .	
0	1	Gravel, clay,								
1	2	Clay, v. sandy		Brown						
2	7	Sand (m), dry								
7	12.5	Clay, silty, w/	sand stringer	s, moist, Brown						
12.5	28			mod. odor, Tan to C	3				 -	
				, ,,,,						
				AANA III	-					
					-					
							ASW8, Tag # 0037183	2, Flushmoun	1	
							Project Name: GF - Un			
					1	+				
							GeoCore # 1283, KDH			
				ION: This water well wa						
and was c	ompleted or	n (mo/day/year) .		4/28/2006	· · · · · · ·	and this	record is true to the be-	st of my know	edge and belief.	
Kansas W	ater Well C	ontractor's Licen	se No	52 7 This	Water We	ell Record wa	s completed on/mo/day	/yr) p. FA	20/06	
	business na			eoCore, Inc.		by (sign		Kolf	•	
				ocore, inc.		, , , , , ,	- Cul			