GSI JOB	#057279									ed a d	MW-5	į
				ER WELL RECOR	D Form	WWC-5	KSA 82a-1		o. <u>0037</u>			_
	ON OF WATE						n Number	1	hip Number	1	ge Number	4
County:	Sedg	wick	<u>NE %</u>	NE 1/4	SE	1/4	22	Т	<u>27 s</u>	R	01 E	
			vn or city street a	ddress of well if lo	ocated with	in city?						
	ouglas - Wi		an Pres Co									-
2 WATER	WELL OWNE	R: Waym	an Bros. Co	noco				<b>—</b> .				
RR#, St. Ad	dress, Box #	: 0199 C	Ne ezo2z						f Agriculture, Di	vision of W	ater Resources	
City, State, A	ZIP Code WELL'S LOC		, KS 67037	· · · · · · · · · · · · · · · · · · ·				Applicat	ion Number:			-
3 AN "X" IN	N SECTION B	OX:	4 DEPTH OF	COMPLETED WE	ELL	27.5	ft. ELE	VATION:	130	4.72 (TC	DC)	
			Depth(s) Groun	idwater Encounter	red 1		f	t. 2	ft.	3	ft.	<u>ି</u> କୁ
	NW	NE	WELL'S STATI	C WATER LEVEL	22.	12 ft.b	elow land s	surface meas	sured on mo/day	/vr	7/6/06	OFFICE
		:		np test data: We								Ξ
≝ w L		E		gpm: We								18
Ŧ		X	Bore Hole Diam	neter 8.25	in to	27.5		ft and	nouro	in to	sp ft	ONLY
<b>   </b>	sw	- SE	WELL WATER	TO BE USED AS tic 3 Feed lot	: 5 Publ	ic water sur	ply	8 Air co	onditioning	11 Injectio	n well	Ę
	i l	i	1 Domest	ic 3 Feed lot	6 Oil fi	eld water si	ipply	9 Dewa	atering	12 Other (	Specify below)	
			2 Irrigatio	n 4 Industrial	7 Lawr	n and garde	n (domest	ic) 10 Moi	nitoring well			_
	S			l/bacteriological s								
			submitted				W	ater Well Dis	infected? Yes		No X	
5 TYPE O	F BLANK CAS	ING USED:		5 Wrought I	ron	8 Concret	e tile	CASIN	G JOINTS: Glu	ed	Clamped	
1 Ste	el	3 RMP	(SR)	6 Asbestos-	Cement	9 Other (s	pecify belo	ow)	We	lded		
2 PV	С	4 ABS		7 Fiberglass	6				Thre	aded	Flush	7
				<b>.5</b> ft., Dia				ft. Dia		in, to	ft	
Casing heig	ht above land	surface	Flush	in. weight	0.7	703	lbs./ft	Wall thickn	ess or gauge No	n. <b>S</b>	SCH. 40	
TYPE OF S	CREEN OR P	ERFORATIO	N MATERIAL:	in., weight		7 6	PVC	10	) Asbestos-cen	nent		
1 Ste		3 Stainl	ess steel	5 Fiberolass	3	8 6	MP (SR)	1	1 Other (specify	/)		
2 Bra		4 Galva	nized steel	5 Fiberglass 6 Concrete	tile	9 A	BS	12	2 None used (o	pen hole)		
SCREEN O	R PERFORAT	ION OPENI	NGS ARE:	5	Gauzed	wrapped		8 Saw c	ut	11 Non	ie (open hole)	
1 Coi	ntinuous slot	3	Mill slot	6	Wire wra	pped		9 Drilled				
2 Loi	uvered shutter	4	Key punched	7	Torch cu	t		10 Other	(specify)			
SCREEN-P	ERFORATED	INTERVALS	: From	17.5 ft. t	0	27.5	ft.	From	ft	to	ft	
			From	ft. t	0		ft.	From	ft	. to	ft	:
GR	AVEL PACK II	TERVALS:	From	15.5 ft. t	0	27.5	ft.	From	ft	. to	ft	.   ~
								From			ft	
6 GROUT	MATERIAL:	1 Neat		2 Cement grout		3 Bento	onite	4 Other				
				5 ft. From								
			contamination:				10 Live	stock pens	14 A	bandoned	water well	
1 Se	ptic tank		4 Lateral lines	s 71	Pit privy		11 Fuel			)il well/ Ga		
2 Se	wer lines		5 Cess pool	8 5	Sewage lag	goon	12 Fert	ilizer storage	16 0	Other (spec	ify below)	
3 Wa	atertight sewer	lines	6 Seepage pi	it 9 l	Feedyard		13 Inse	cticide stora	ge			
Direction fro				-			How man	y feet?				_
FROM		CODE				FROM	то		PLUGGING	INTERVA	LS	
0.5	0.5		opsoil Ity Clay, Iow	nlacticity								#
9	14		at Clay, nois									-  "
14	27.5			e grained, lo	ose					-		
			,	<b>1</b>								-
												_
						·····						
			····									
ZICONTO				TION: This water	unall una l		od (2) ==		or (2) pluggod	dor my ind	iediction and un	
												1
	on (mo/day/yr)			5/06					est of my know			
			Centralia		- le -				completed on (n	no/day/yr)	7/7/06	
	USINESS Name			ical Services		by	(signature		mag	Burgaria	Nator 1000 6 14	
Jackso	on St. Ste. 420	Toneka Kans	as 66612-1367 T	orrect answers. Se	no inree co 3-5545 Ser	id one to WA	TER WELL	OWNER and	and Environment, I retain one for vo	ur records	water, 1000 S W	