	WAT	ER WELL RE	CORD F	orm WW	/C-5 K	SA 82a-121	2			
1 LOCATION OF WATE			··· NIE		ION NUMBER	1		RANGE NUM		
Sedgwick	SW m nearest town or city street addr		1/4 NE	1/4	19	Т 27	S	R 1E	E/W	
204 N. Elizab	•									
2 WATER WELL OWNER: BERGMAN, Ruby										
	R#,ST. ADDRESS,BOX #: 204 N. Elizabeth					Board of Agriculture, Division of Water Resource				
-	STATE: Wichita, Ka		A(P CODE:		Application Num	ber:		
J LOCATE WELL'S LO	CTION BOX:	F COMPLETED W				ELEVATION:				
N N		undwater Encounte		ft.	AND OU	IDEA OF MEACH	ft.	2/26/	ft.	
WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 2/26/07 Pump test data: Well water was ft. after hours of pumping @ gpm										
	Est. Yie	•	Well wat			ft. after		of pumping @	gpm	
w Mile	E Bore Hole	Diameter 12	in.	to 4	0 ft.	and	in.	to	ft.	
sw	WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Spe									
1. Domestic 3. Feediot 5. Public water supply 6. Lawli and garden only 12. Other (Specify below) 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well										
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample										
submitted Was Water Well Disinfected? YES NO										
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded 1. Steel 3. RPM (SR) Welded Clamped										
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26										
Blank casing diamete	er 5 in.	to 25 ft.	, Dia.	in.	to	ft., C	Dia. i	n. to	ft.	
Casing height above	e land surface: 12	in.,	Weight:	2.35 lb	s. / ft.	Wall thic	ckness or gaug	e No214		
TYPE OF SCREEN OR PERFORATION MATERIAL:										
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)										
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)										
SCREEN - PERFORA			ft. to	40	ft.,	From	ft.	40	ft.	
JORELIN-FERI OR	Fro		ft. to	40	ft.,	From	rt. ft.	to to	ft.	
GRAVEL PA	CK INTERVALS: Fro	2.4	ft. to	40	ft.,	From	ft.	to	ft.	
	Fro	m	ft. to		ft.,	From	ft.	to	ft.	
6 GROUT MATER	ALS: 1. Neat cement	2. Cen	nent Grout	3	. Bentonite	(onite hole plug		
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.										
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10.					k pens	13. Insection	ide storage	15. Oil well/Ga	s well	
1. Septic tank 4. Lateral lines 7. Fit prity 1. Septic tank 4. Lateral lines 7. Fit prity 1. Septic tank 4. Lateral lines 7. Fit prity 1. Septic tank 4. Lateral lines 7. Fit prity 1. Septic tank 4. Lateral lines 7. Fit prity 1. Septic tank 4. Lateral lines 7. Fit prity 1. Septic tank 1. Septic tank 4. Lateral lines 7. Fit prity 1. Septic tank 1. Sep								cify below)		
3. Watertight sewe		9. Feed ya	rd 1	2. Fertilizer	storage					
Direction from well?	West					How ma	ny feet? 40 f			
From To	LITHO	LOGIC LOG		From	То		LITHOLO	GIC LOG		
0 4 8	topsoil									
8 20	clay medium sand									
20 40	coarse sand									
										
										
						•				
	_								·····	
				-		-				
7 Contractor's or	Landowner's Certification: Ti	nis water well was	1. constructed) 2. re	constructed	1 or 3, p	lugged (under my jurisdictio	n and	
was completed on	2.2	5-2007				knowledge and b				
· .	Contractor's License No. 2				•	on (mo/day/year		-2007		
under the business name of Harp Well and Pump Service by (signature) Todd S. Hourp										