GSI Job N	No. 057279	•									MW-8
				TER WELL RECO	ORD Form \			12 ID No.			
	N OF WATER						n Number	•	Number	1 -	Number
	Sedg		NE ½			, -	22	т 27	S	R	01 E
	direction from 40 S. Chaut		wn or city street	address of well if	located withi	n city?					
	VELL OWNER			Bros. Conoc	30				.,		
_	ress, Box #		-	ouglas Ave.				Board of Ad	ricultura Divi	ision of Wate	er Resources
				(S 67214				Application		Sion of Wate	31 1103001003
LOCATE	IP Code WELL'S LOC	ATON WIT									
AN "X" IN	SECTION BO	X:	DEPTH OF	F COMPLETED \	WELL	30	ft. ELEV	ATION:			
<b>↑</b>		NE	Depth(s) Grou	indwater Encoun	tered 1		ft.	2	ft.	3	ft.
	-NW		WELL'S STAT	TIC WATER LEV	EL	ft. be	elow land s	urface measure	ed on mo/day/	yr	
<u> </u>	i			mp test data: \							
<b>₩</b> w	<del></del>		Est. Yield	apm: \	Nell water wa	ıs	ft	. after	hours p	oumping	gpm
7 <b>I</b>		X	Bore Hole Dia	meter 2 R TO BE USED A stic 3 Feed lot	in. to	30		ft. and	ir	n. to	ft.
	wa	SE	WELL WATER	R TO BE USED A	S: 5 Publi	c water sup	ply	8 Air cond	itioning 1	1 Injection	well
			1 Dome	stic 3 Feed lot	6 Oil fi	eld water su	ipply	9 Dewater	ing 1	2 Other (Sp	secity below)
` <u> </u>	s		I .	on 4 Industria							
	Ü		Was a chemic	cal/bacteriologica	l sample sub	mitted to De					
			submitted					ter Well Disinfe			No X
5 TYPE OF	BLANK CAS	ING USED	:	5 Wrough	t Iron	8 Concret	e tile	CASING J	OINTS: Glue	ed C	Clamped
1 Stee	el	_ 3 RMF	P(SR)	6 Asbesto	s-Cement	9 Other (s	pecify belo	w)		ded	
2 PVC		4 ABS	;	7 Fibergla	iss _				Thre	eaded	Flush
Blank casing	diameter	1	in. to	<b>15</b> ft., Dia		in. to		ft., Dia		in. to	ft.
Casing heigh	nt above land	surface	Flushmoun	in., weight	0.7	703	lbs./ft.	Wall thickness	or gauge No	. Se	ch. 40
			ON MATERIAL:			7 F	PVC	10 A	sbestos-cem	ent	
1 Stee	el		nless steel		iss	8 F	RMP (SR)	11 (	Other (specify)		
2 Bras			ranized steel	6 Concret		9 A	ABS	12 N	lone used (op	en hole)	
			INGS ARE:		5 Gauzed	wrapped		8 Saw cut		11 None	(open hole)
	ntinuous slot		Mill slot		6 Wire wra			9 Drilled ho			
			Key punched		7 Torch cu						
SCREEN-PE	ERFORATED	INTERVAL		<b>15</b> f							
			From	f	t. to	20	π. ι	-rom	π.	το	π.
GRA	AVEL PACK IN	NIERVALS		<b>13</b> f							
			From	f	t. to		ft.	-rom	π.	to	ft.
GROUT	MATERIAL:	1 Nea	at cement	2 Cement gro	ut	3 Bente	onite	4 Other		·	
Grout Interva	als From	0.5	ft. to <b>1</b>	ft. From		ft. to		ft. Fro	m	ft. to	ft.
		e of possible	e contamination:					stock pens		bandoned w	
	otic tank		4 Lateral lin		Pit privy Sewage la		11 Fuel	_		il well/ Gas	
	wer lines	l'	5 Cess poo	goon	n 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage				y below)		
Direction fro	tertight sewer	iines	6 Seepage pit 9 Feedyard 13 Insecticide storage How many feet?								
FROM	TO	CODE	LITI	HOLOGIC LOG		FROM	TO	y leet?	PLUGGING	INTERVALS	3
0	9		Clay, light to		ft to firm	7.1.0					
9	14		Clay, with silt,								
			Sand, light gr		fine to		T				
14	16.5		ine grained, si								
46.5	20		Sand, light br	own, fine to co	arse						
16.5	30		grained								
	<del> </del>										
7 CONTR	ACTOR'S OR	LANDOW	NER'S CERTIFIC	CATION: This wa	ater well was	(1) construc	ted, (2) red	constructed, or	(3) plugged un	der my juris	diction and was
completed of	on (mo/day/yr)	)	0	5/14/07		and th	is record is	true to the bes	t of my knowl	edge and be	elief. Kansas
Water Well	Contractor's L	icense No.		531		This V	Vater Well F	Record was co	mpleted on (m	no/day/yr)	06/05/07
under the b	usiness name	of	Geotechi	nical Servic	es, Inc.	by (	(signature)	Smal	a Wate		
INSTR	UCTIONS: PI	ease fill in bl	anks and circle the	correct answers.	Send three co	pies to Kans	as Departm	ent of Health and	Environment,	Bureau of W	ater, 1000 S W
Jackso	on St., Ste. 420,	горека, Ка	nsas 66612-1367.	relephone: 913-	296-5545. Se	nd one to W	A I EK WELL	UVVNER and re	etain one for yo	ur records.	