	WATER WELL RE	CORD FO	rm vvvv	3-5 KS	A 82a-1212			
LOCATION OF WATER WELL:	FRACTION NE 1/4 SW	ALL NIE		ON NUMBER		1	RANGE NU	
Sedgwick Distance and direction from nearest town or city s			1/4	21	Т 27		R 1E	EW
256 N. Ohio Wichita,		itimi oty:						
	HOLIC CHARITIES	<u>s</u>						
RR#,ST. ADDRESS,BOX #: 532 N	N. Broadway					Board of Agricu	lture, Division of W	later Resource
	ita, Kansas		ZIP	CODE:		opplication Numb	er:	
DI LOCATE WELL'S LOCATION 4 C	рертн ог сумалься) w	ÆLL: 41	ft.		ELEVATION:			
	oth of groundwater Encounte		ft.			ft.		ft.
	ELL'S STATIC WATER LEVI			V LAND SU	RFACE MEASUR			/07
NW XIE	Pump test da Est. Yield: gom				ft. after ft. after		of pumping @	gpm
≝ 	Est. Yield: gpm ore Hole Diameter	Well wate in.	to	ft.		in.	of pumping @ to	gpm ft.
	ELL WATER WAS USED A				and	9. Dewatering	44 1	ction well
sw se 1.	Domestic 3. Feedlot	5. Public water	er supply	7. Lawn a	nd garden only		12. Other (S	pecify below)
	Irrigation 4. Industria			8. Air con	•	10. Monitoring	j well nat mo/day/yr v	vae eamnle
	Vas a chemical/bacteriological sa bmitted	mple submitted to De	epartment?	YES Was V	NO Vater Well Disinfed			NO
TYPE OF CASING USED:	5. Wrought Iron	7. Fiberglass	9. Oth	er (Specify	below) CASIN	IG JOINTS:	Glued	Threaded
1. Steel 3. RPM (SR	₹)			(0,000.)	20.000	,	Welded	Clamped
2. PVC 4. ABS	6. Asbestos-Cement	Concrete tile						
	in. to ft.	, Dia.	in.	to	ft., Di	a. in	. to	ft.
Casing height high buland surface:	36 in.,	Weight:	lb	s. / ft.	Wall thick	rness or gauge	No.	
TYPE OF SCREEN OR PERFORATION 1. Steel 3. Stainless Steel	I MATERIAL: 5. Fiberglass	7. PVC	9. AE	19	11 Othe	r (specify) N	/ A	
Steel 3. Stainless Steel Reass 4. Galvanized	6. Concrete Tile	8. RMP (SR)		bestos-Cer		used (open h		
SCREEN OR PERFORATION OPENING		o. r (01.)	10.70	000000	12.11011	o acca (open n	0.0,	
1. Continuous slot 3. Mill sk		rapped	7. Ton	ch cut	9. Drilled	l holes	11. None (open hole)
2. Louvered shutter 4. Key pi		• •	8. Sav			(specify) N/		,
,,,,	•		o. Ouv					
SCREEN - PERFORATION INTERVAL	From	ft. to		ft.,	From	ft.	to	ft.
ODANEL BACK INTERVALO	From	ft. to		ft.,	From 	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	ft. to		ft.,	From	ft.	to	ft.
- 1	From	ft. to		ft.,	From	ft.	to	ft.
GROUT MATERIALS: 1. Neat		nent Grout		Bentonite		_	nite hole pl	~-
Grout Intervals: From What is the nearest source of possible co	ft. to ontamination:	ft., From	ft.	to	ft.,	From 3	ft. to	25 ft.
1. Septic tank 4. Lateral	7 Dit neba	, 10). Livestock	pens	13. Insectic	de storage	15. Oil well/	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify be							pecify below)	
3. Watertight sewer line 6. Seepa	ge pit 9. Feed ya	rd 1:	2. Fertilizer	storage		•••		
Direction from well? East	LITUOLOGIO LOG			· 	How man	y feet? 200	010 1 00	
From To	LITHOLOGIC LOG		From 0	To 3	compacted o	LITHOLO	GIC LOG	
			3	25	compacted ex bentonite ho			
			25	41	well gravel	- Pro-		
	•							

Contractor's or Landowner's Certifi		1. constructed	2. re	constructe	d or 3. 🗘	lugged	ınder my jurisdio	ction and
was completed on (mo/day/year)	6-21-2007	and this record i	s true to the	best of my	knowledge and be	elief.		
Kansas Water Well Contractor's Licen	se No. 236	This water we	ell record wa	s complete	d on (mo/day/year)	6-22-	-2007	
under the business name of Harp Well and Pump Service by (signature) Todd S. Havb								