		WATER	WELL REC	ORD F	orm WW	C-5 K	SA 82a-12	:12		
1 LOCATION OF WATER WELL: FRACTION					1	ION NUMBE				
Sedgwick			•• •	1/4 SW	1/4	21	T	2 7 S	R 1E	E/W
Distance and direction from										
In Alley 302-3 2 WATER WELL OF		EDGWICK C	Vichita, Kan OUNTY EN		ENTAL	RESOU	RCES			
RR#,ST. ADDRESS,		625 S. Tyler R		· · · · · · · · · · · · · · · · · · ·	EITIE	RESCO	RCLO	Board of Agri	iculture, Division of W	later Resource
I '		Vichita, Kansa			ZI	CODE: 6	7215	Application Nun	nber:	
3 LOCATE WELL'S LO	CATION	4 DEPTH OF	MAGES D WEL	LL: 25			ELEVATION			
WITH AN "X" IN SEC	TION BOX:	Depth of groundw	- ,		ft.			ft.		ft.
		WELL'S STATIC	WATER LEVEL	. 12	FT. BELO	W LAND SI	JRFACE MEAS	SURED ON mo/o	day/yr: 7/17	//07
NW	NE		Pump test data:	: Well wat	er was		ft. after	hours	s of pumping @	gpm
w X	:	Est. Yield:	gpm	Well wat		-	ft. after		s of pumping @	gpm
≥ w	E	Bore Hole Diam	neter unknown		to	ft	. and	in.	to 11 Injec	ft. ction well
)sw	SE	1. Domestic	3. Feedlot	5. Public wat	er supply	7. Lawn	and garden or	9. Dewateri nly	12. Other (Sp	
		2. Irrigation	4. Industrial	6. Oil field w	ater supply	8. Air co	nditioning	10. Monitoria	ng wel	•
s		Was a chemical/b submitted	pacteriological samp	ele submitted to D	epartment?	YES	NO Water Well Dis		what mo/day/yr w	vas sample NO
5 TYPE OF CAS	ING USED:				9 01	her (Specifi		ASING JOINTS:	Glued	Threaded
1. Steel	3. RPN	VI(SR) 5. Wro	ught Iron	7. Fiberglass	3. 0	ner (opecin	y below) O	101110 JOHN 10.	Welded	Clamped
2. PVC	> 4. ABS	6. Asbe	estos-Cement	8. Concrete ti	le					·
Blank casing diamete	er 2	in. to	ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height		removed all in	1.,	Weight:	It	os. / ft.	Wall	thickness or gaug	ge No.	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) N/A										
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Otner (specify) 11/12 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)										
SCREEN OR PERFO		NINGS ARE								
1. Continuous slot		lill slot	5. Gauzed wra	pped	7. To	rch cut	9. Di	rilled holes	11. None (d	pen hole)
2. Louvered shutte	r 4. K	ey punched	6. Wire wrappe	ed	8. Sa	w cut	10. O	ther (specify) N	I/A	
SCREEN - PERFORA	TION INTERV	/AL From	f	t. to		ft.,	From	ft.	to	ft.
OOKEEN TENEOUS		From		t. to		ft.,	From	ft.	to	ft.
GRAVEL PAG	CK INTERVAL	LS: From	fi	t. to	1	ft.,	From	ft.	to	ft.
		From	ft	t. to	1	ft.,	From	ft.	to	ft.
6 GROUT MATERI	ALS: 1. N	Neat cement	2. Ceme	nt Grout		B. Bentonite	e	Other bent	tonite hole plu	ug
Grout Intervals: From ft. to ft., From						ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination: 1. South tank 4. Lateral lines 7. Pit privy					0. Livestoc	k pens	13. Inse	cticide storage	15. Oil well/0	as well
1. Sepurcialis 1. Sep								46 Other (or		
2. Sewer lines 3. Watertight sewe		ess Poor eepage pit	9. Feed yard	•	12. Fertilize	r storage				
Direction from well?	East	copago pic	•			_	How	many feet? 3		
From To		LITHOLO	GIC LOG		From	То		LITHOLO	OGIC LOG	
					0	25	bentonite	hole plug		
							ļ			
				-						
					<u> </u>					
7	Landoum and a	Podification: This	untor well was 4	construct-	1 0 ==	construct	ed or 3.C	plugged	under my jurisdic	tion and
		Certification: This w				constructe	ed or 3. C v knowledge an		ander my junisuic	aon and
was completed on		,				•	_		0/2007	
Kansas Water Well			D C .			•	ed on (mo/day/y		9/2007 - 7/	
under the business	mame or H	arp Well and	rump Servic	ce	by (S	gnature)		$(\alpha \alpha \alpha)$	Hart)