WATER WELL RECORD FO	orm WWC-5 KS	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER	l	RANGE NUMBER
Sedgwick NE 1/4 SW 1/4 NE Distance and direction from nearest town or city street address of well if located within city?	1/4 21	T 27 S	R 1E E/W
256 N. Ohio Wichita, Kansas			
2 WATER WELL OWNER: CATHOLIC CHARITIES			
RR#,ST. ADDRESS,BOX #: 256 N. Ohio		Board of Agr	iculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Nur	mber:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 35	ft.	ELEVATION:	
N Depth of groundwater Encountered:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL 15	FT. BELOW LAND SUI	RFACE MEASURED ON mo/o	day/yr: 9/20/07
Pump test data: Well water			s of pumping @ gpm
Est. Yield: gpm Well water Bore Hole Diameter 12 in.	er was to 35 ft.	ft. after hours	s of pumping @ gpm to ft.
₩ELL WATER TO BE USED AS:		9 Dewater	44 1-2
	er supply 7. Lawn a	nd garden only	12. Other (Specify below)
	ater supply 8. Air cond	. 16	ng well what mo/day/yr was sample
S Was a chemical/bacteriological sample submitted to D submitted		ater Well Disinfected?	YES NO
5 TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass	9. Other (Specify	below) CASING JOINTS:	Glued Threaded
1. Steel 3. RPM (SR)	SUD 36	,	Welded Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete till	6		
Blank casing diameter 5 in. to 25 ft., Dia.	in. to	ft., Dia.	in. to ft.
Casing height above land surface: 12 in., Weight: TYPE OF SCREEN OR PERFORATION MATERIAL:	2.35 lbs. / ft.	Wall thickness or gau	ge No214
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)			
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 25 ft. to	35 ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft. to	35 ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite	Other bent	tonite hole plug
Grout Intervals: From 4 ft. to 24 ft., From	ft. to	ft., From	ft. to ft.
What is the nearest source of possible contamination: 1 Sentic tank 4 Lateral lines 7. Pit privy	0. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
8 Sawage laggon 11 Fuel storage 14 Abandon water well 16. Other (specify below)			
2. Sewer lines 5. Cess Footi			
3. Watertight sewer line 6. Seepage pit 9. reed yard 1 Direction from well? West	_	How many feet? 20	ft. plus
From To LITHOLOGIC LOG	From To	LITHOLO	OGIC LOG
0 4 topsoil			· ·
4 12 clay 12 28 medium sand			
28 35 shale			
Contractor's or Landowner's Certification: This water well was 1. constructed			under my jurisdiction and
was completed on (mo/day/year) 9-20-2007 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/24/2007			
	il record was completed	on (mo/day/year) 9/24	4/2007