WATER WELL RECORD FO	orm WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER		RANGE NUMBER
Sedgwick NW 1/4 NW 1/4 SE	1/4 31	T 27 S	R 1E E/W
Distance and direction from nearest town or city street address of well if located within city? 301/302 West Drive Wichita, Kansas			
2 WATER WELL OWNER: PRAIRIE HOMESTEAD RETIREMI	ENT COMPLEX	OFFICE	
RR#,ST. ADDRESS,BOX #: 1605 W. May Ave	EIVI COMI EEX		riculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Nu	mber:
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 40		ELEVATION:	
WITH AN "X" IN SECTION BOX: N Depth of groundwater Encountered:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL 17	FT. BELOW LAND SL	IRFACE MEASURED ON mo/	day/yr: 9/15/07
Pump test data: Well water			s of pumping @ gpm
	er was	ft. after hour	s of pumping @ gpm
Est. Yield: gpm Well water Bore Hole Diameter 12 in.	to 40 ft.	and in.	to ft.
WELL WATER TO BE USED AS:	7 Jawa 6	9. Dewater	ing 11. Injection well
	ter supply 7. Lawn a ater supply 8. Air con		12. Other (Specify below)
2. Irrigation 4. Industrial 6. Oil field wa Was a chemical/bacteriological sample submitted to D		NO ; If yes,	what mo/day/yr was sample
submitted		Vater Well Disinfected?	YES NO
5 TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass	9. Other (Specify	below) CASING JOINTS:	Glued Threaded
1. Steel 3. RPM (SR)	SDR-26		Welded Clamped
2. PVC 4. ABS	C	6 Di-	
Blank casing diameter 5 in. to 24 ft., Dia.	in. to	ft., Dia.	in. to ft.
	2.35 lbs. / ft.	Wall thickness or gau	ige No214
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	11. Other (specify)	
1. Steel 3. Stainless Steel 5. Fiberglass 7. FVC 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Cer		n hole)
2. 51355		()	•
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
	8. Saw cut	10. Other (specify)	, , , , , , , , , , , , , , , , , , , ,
2. Louvered shutter 4. Key punched 6. Wire wrapped	-		
SCREEN - PERFORATION INTERVAL From 24 ft. to	35 ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft. to	40 ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite	Other ben	tonite hole plug
Grout Intervals: From 4 ft. to 24 ft., From	ft. to	ft., From	ft. to ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy	0. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
11.00	1. Fuel storage	14. Abandon water well	16. Other (specify below)
2. 30.11.1	2. Fertilizer storage		
Direction from well? South		How many feet? 20	ft.
From To LITHOLOGIC LOG	From To	LITHOL	OGIC LOG
0 3 topsoil			
3 12 clay	 		
12			
55 40 State			
7		l or 0 minored	under my invited letter and
Contractor's or Landowner's Certification: This water well was 1. constructed			under my jurisdiction and
was completed on (mo/day/year) 9-15-2007 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/17/2007			
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp			