WATER WELL RECORD F	orm WWC-5 KS	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER	TOWNSHIP NUMBER	RANGE NUMBER
Sedgwick SW 1/4 NW 1/4 SE Distance and direction from nearest town or city street address of well if located within city?	1/4 31	T 27 S	R 1E E/W
150' West of 802/807 Manor Drive Wichita, Kansa	ıs		
2 WATER WELL OWNER: PRAIRIE HOMESTEAD RETIREMENT COMPLEX			
RR#,ST. ADDRESS,BOX #: 1605 W. May Ave.		_	culture, Division of Water Resource
CITY, STATE: Wichita, Kansas 3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 40	ZIP CODE:	Application Nun	nber:
WITH AN "X" IN SECTION BOX:) ft. ft.	ELEVATION: ft.	ft.
Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 17		RFACE MEASURED ON mo/o	
Pump test data: Well wat			of pumping @ gpm
	er was		s of pumping @ gpm
Est. Yield: gpm Well wat Bore Hole Diameter 12 in.	to 40 ft.	and in.	to ft.
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public wa	ter supply 7. Lawn a	9. Dewateri	ng 11. Injection well 12. Other (Specify below)
	ater supply 8. Air cond	fitioning 10. Monitori	ng well
S Was a chemical/bacteriological sample submitted to E submitted		no ; If yes, yeater Well Disinfected?	what mo/day/yr was sample YES NO
TYPE OF CASING LISED:			Glued Threaded
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass	9. Other (Specify SDR-26	delow) CASING JOINTS.	Welded Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete ti	le SDR-20		,
Blank casing diameter 5 in. to 24 ft., Dia.	in. to	ft., Dia.	in. to ft.
	2.35 lbs. / ft.	Wall thickness or gau	ge No214
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	11. Other (specify)	
Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Cem	ent 12. None used (open	hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 24 ft. to	35 ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft. to	40 ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug			
Grout Intervals: From 4 ft. to 24 ft., From What is the nearest source of possible contamination:	ft. to	ft., From	ft. to ft.
1. Septic tank 4. Lateral lines 7. Pit privy 1	0. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)			
Watertight sewer line	12. Fertilizer storage	How many feet? 20	ft plue
Direction from well? East	From To		OGIC LOG
0 3 topsoil			
3 12 clay			
12 35 coarse sand 35 40 shale			
35 40 Shale			
	1 1		
7		o. 0 -l	under multiplication
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and			
was completed on (mo/day/year) 9-15-2007 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/17/2007			
under the business name of Harp Well and Pump Service by (signature) Todd S. Horp			