1 LOCATION OF WATER WELL: Fraction	Section Number Township Number Range Number
County: Sedgwick NW ¼ NE ¼ SE	
Distance and direction from nearest town or city street address of well if located wit	
155 S. Chautauqua, Wichita	inii Ory:
2 WATER WELL OWNER: Wayman Bros. Conoco	
RR#, St. Address, Box # : 3001 E. Douglas Ave.	Poard of Agriculture, Division of Water Becourses
City, State, ZIP Code : Wichita, KS 67214	Board of Agriculture, Division of Water Resources
	Application Number:
AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL	29 ft. ELEVATION: 1302.48 (TOC)
Depth(s) Groundwater Encountered 1	20.5 ft. 2 ft. 3 ft.
WELL'S STATIC WATER LEVEL 20	.32 ft. below land surface measured on mo/day/yr 10/02/07
Pump test data: Well water w	vas ft. after hours pumping gpm
Est. Yield gpm: Well water w	vas ft. after hours pumping gom
X Bore Hole Diameter 8.5 in to	29 ft. and in. to ft. Solic water supply 8 Air conditioning 11 Injection well 12 Other (Specify below)
SW SE WELL WATER TO BE USED AS: 5 Pub	plic water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feed lot 6 Oil	field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lav	n and garden (domestic) 10 Monitoring well
	bmitted to Department? Yes No X If yes, mo/day/yr sample was
submitted	Water Well Disinfected? Yes No X
	8 Concrete tile CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement	
2 DVC 4 ABS 7 Fiberaless	Thursday Eluch
Blank casing diameter 2 in. to 14 ft., Dia	ın. to tt., Dia in. to ft.
Casing height above land surface Flushmount in., weight 0. TYPE OF SCREEN OR PERFORATION MATERIAL:	703 lbs./ft. Wall thickness or gauge No. Sch. 40
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass	8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed	9 ABS 12 None used (open hole)
	••
2 Louvered shutter 4 Key punched 7 Torch c	
SCREEN-PERFORATED INTERVALS: From 14 ft. to	
From tt. to	ft. From ft. to ft.
	29 ft. From ft. to ft.
From ft. to	ft. From ft. to ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout	3 Bentonite 4 Other
Grout Intervals From 0.5 ft. to 12 ft. From	ft. to ft. From ft. to ft.
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy	
2 Sewer lines 5 Cess pool 8 Sewage la	goon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard	13 Insecticide storage
Direction from well?	How many feet?
FROM TO CODE LITHOLOGIC LOG	FROM TO PLUGGING INTERVALS
0 0.1 Topsoil	
Clay, dark brown to light brown to gray 0.1 14.5 brown, with some silt	
14.5 Sand, fine to medium to coarse grains	
ourid, fine to medium to coarse grains	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was	1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was
completed on (mo/day/yr) 10/02/07	and this record is true to the best of my knowledge and belied Kansas
Water Well Contractor's License No. 531	This Water Well Record was completed on (mo(day/yr) 1/05/07
under the business name of Geotechnical Services, Inc.	by (signature)
INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three co	pies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W