WATER WELL RECORD Form WWC-5 KSA 82a-1212					
1 LOCATION OF WATER WELL: FRACTION SW NE SW NE		CTION NUMBER TOWNSHIP NUMBER RANGE NUMBER 30 T 27 S R 1E E/W			
Sedgwick ME 1/4 Me Distance and direction from nearest town or city street address of well if located within city? Sedgwick Sedgwick </td <td>1/4 3</td> <td>0</td> <td>т 27 s</td> <td>R 1E</td> <td>E/W</td>	1/4 3	0	т 27 s	R 1E	E/W
802 S. Millwood Wichita, Kansas					
2 WATER WELL OWNER: DUNHAM, Donna					_
RR#,ST. ADDRESS,BOX #: 802 S. Millwood			-	iculture, Division of Wat	ter Resource
CITY, STATE: Wichita, Kansas	4	ODE: 672		nber:	
WITH AN "X" IN SECTION BOX:	4 ft.	E	LEVATION:		
Depth of groundwater Encountered:	ft.		ft.		ft.
WELL'S STATIC WATER LEVEL 10		AND SURI	FACE MEASURED ON mo/		
UN₩ NE Pump test data: Well wa Est. Yield: gpm Well wa	iter was iter was			s of pumping @ s of pumping @	gpm gpm
Est. Yield: gpm Well wa	to	ft.	and in.	to	ft.
WELL WATER MASE USED AS:	_		9. Dewateri	ing 11. Injecti	on well
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below) 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well					
S 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well S Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample					
submitted	Department		ter Well Disinfected?		•
5 TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass	9. Other	(Specify be	elow) CASING JOINTS:	Glued T	hreaded
1. Steel 3. RPM (SR) 6. Asbestos-Cement 8. Concrete t 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete t	ile			Welded C	Clamped
Blank casing diameter $1 \frac{1}{4}$ in. to ft., Dia.	in.	to	ft., Dia.	in. to	ft.
		-			п.
Casing height Skipper and surface: 0 in., Weight: Ibs. / ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL:					
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) N/A					
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch	cut	9. Drilled holes	11. None (ope	en hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw c i	ut	10. Other (specify) N	/A	
SCREEN - PERFORATION INTERVAL From ft. to	, ft.,		From ft.	to	ft.
From ft. to	, ft.,		From ft.	to	ft.
GRAVEL PACK INTERVALS: From ft. to	o ft.,		From ft.	to	ft.
From ft. to	o ft.,		From ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Be	entonite	Other bent	onite hole plug	
Grout Intervals: From ft. to ft., From ft. to ft., From 7 ft. to 14 ft.					
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy	I0. Livestock pe	ns	13. Insecticide storage	15. Oil well/Gas	s well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)					
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage					
Direction from well? East			How many feet? 1209 E		ine, Kansas
From To LITHOLOGIC LOG		То		GIC LOG	
		_	isement floor ment	• • • • • •	
	7	<u> </u>	ntonite hole plug		
			· · · · · · · · · · · · · · · · · · ·		
	╉───┨──				
7 Contractor's or Landowner's Certification: This water well was 1. constructed			ar a alumand		and
was completed on (mo/day/year) 1/9/2008 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 1/11/2008					
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp					

Ċ