WATER WELL RECORD Form WWC-5 K-5.8 A82-1212 IDIO Output: Fraction County: Sedgwick NE NE NW 9 T 27 S R 1 E Selance and direction from nearest town or city strets address of well if located within city? S R 1 E 2/WSTER WELL OWNER: National By-Products Board of Agriculture, Division of Water Resources Application Number 1 E 2/WSTER VELL OWNER: Not Application Number 1310.07 (TOC) Desting Stormay 03126/08 2/WSTER VELL CONTENT Desting Stormay Desting Stormay 1310.07 (TOC) Desting Stormay 03126/08 2/WSTER VELL Desting Stormay Stormay 1310.07 (TOC) Desting Stormay 03126/08 2/WSTER VELL Desting Stormay Stormay 1310.07 (TOC) Desting Stormay 03126/08 2/WSTER VELL Desting Stormay Stormay The associal as
Sedgwick NE X NW y 9 T 27 S R 1 E Statuce and direction from nearest town or city street address of well if located within city? Z Z Y Y S R 1 E ZW TER WELL COWNER National By-Products Board of Agriculture, Division of Water Resources Application Number: Control Water Resources ZW TER St. Address Not : POB Dox 615 Board of Agriculture, Division of Water Resources Application Number: Control Well's LOCATONNITH Depth of COMPLETED WELL 20 ft. ELEVATION 1310.07 (TOC) COCATE WELL SIGCATON WATER E E E Well STATIC WATER LEVEL 13.10 ft. below TOC measured on moreasity 03/226/08 WW WELL STATE TO BE LISE DAS S 20 in to 20 ft. and in to ft. S S TryPE OF BLANK CASING USED: 5 View Water was ft. and in to ft. S and height abore land surface Floarglass 7 Floarglass S Arr conditioning 12 Other (Seecify below) <
Stance and direction from nearest town or city street address of well if located within city? Sate Sate <t< td=""></t<>
22: S. 28: W of SE Corner of Abandoned Building, 2050 N. Mosley – Wichita 2 WATER WELL OWNER: National By-Products RK, St. Address, Box # PO Box 615 3/K, Stat, ZIP Code Des Moines, IA 50303 1/K, Stat, ZIP Code Desthis (Groundwater facoundwater facoundwater facoundwater facoundwater facoundwater facoundwater facoundwater facoundwater facoundwater supply 0 in to 3/25/08 1/K, Stat, ZIP Code Statistical and the supply Bark conditioning 1 in injection well 1/K UNIT KINER TO BE USED AS: S Public water supply 8 Ar conditioning 11 injection well 1/K UNIT KINER TO BE USED AS: S Public water supply 8 Ar conditioning 12 Other (Specify below) 2 Urigation 4 industrial 7 Lawn and garden (domestic) 10 Monoling well 12 Other (Specify below) 1/K Steel 3 RMP (SR) 6 Abeteose-Crement 9 Other (specify below) Water Well Disinfected? Yes No X 1/K 2 PVC 4 ABS 7 Fiberglass Threaded Flush
WATER WELL OWNER: National By-Products RR, St. Address, Box # : PO Box 615 Star, St. Address, Box # : PO Box 615 Marker, State, ZP Code Des Moines, IA 50303 Application Number Application Number IOCATE WELLS LOCATON WITH ANX IN SECTION BOX. 4 DEPTH OF COMPLETED WELL INW
Bits, State, ZIP Code Des Moines, IA 50303 Application Number: My, State, ZIP Code Des Moines, IA 50303 Application Number: IUCCATE WELL'S LOCATON WITH DEPTH OF COMPLETED WELL 20 ft. ELEVATION: 1310.07 (TOC) INCATE WELL'S LOCATON WITH Depth(s) Groundwater Encountered 1 15.0 ft. after ft. 3 ft. INVELU'S STATIC WATER LEVEL 13.10 ft. below TOC measured on moldaylyr 03/26/08 gpm W State S Depth(s) Groundwater Encountered 1 ft. after hours pumping gpm W S S Fump test data: Well water was ft. after hours pumping gpm S S S S Full PTE TO BE USED XS. 5 Public water supply 8 Air conditioning 11 in to ft. 1 Domestic 3 Feed tot 6 Oil field water supply 8 Air conditioning well 12 Other (specify below) 12 Other (specify below) 2 Irrigation 41 industrial 7 Lawn and garden (domestic) 10 Monitoring well 12 Other (specify below) Well Water well water well 1 Steel 3 RMP (SR) 6 Aabestos-Cement
State Zing State Zing State Application Number: COCATE WELLS LOCATION MINTH
LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX. 4 DEPTH OF COMPLETED WELL 20 ft. ELEVATION: 1310.07 (TOC) AN "X" IN SECTION BOX. Depth(s) Groundwater Encountered: 1 15.0 ft. 2 ft. 3 ft. 3 ft. 4 Well'S STATIC WATER LEVEL 13.10 ft. below TOC measured on moldayly 03/26/08 Pump test data: Well water was ft. after hours pumping gpm Bore Hole Diameter 8.25 in. to 20 in. tafter hours pumping gpm 1 Domestic 3 Feed lot 6 Of field water supply 8 Air conditioning 11 11 inection well 2 Type OF BLANK CASING USED: 5 Virought Iron 8 Concrete domestic) 10 Moning well 2 Other (Specify below) Welded 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Flush 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Flush 2 Ins to 10 ft. Dia in. to ft. Dia in
AN X' IN SECTION BOX: ^A DEPTH OF COMPLETED WELL 20 f. t. ELEVATION: 1310.07 (TOC). W
x
W WLL'S STATIC WATER LEVEL 13.10 ft. below TOC measured on moldaylyr 03/26/08 Pump test data: Well water was ft. after hours pumping gpm S Bore Hole Diameter 8.25 in. to ft. after hours pumping gpm S S Est, Yield gpm: Well water was ft. after hours pumping gpm S S Est, Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8.25 in. to ft. after hours pumping gpm S VietL/WATER TO BE USED AS: 5 Public water supply 9 Dewatering 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, moldaylyr sample was submitted 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 1 Steel 3 Stainess steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Proc 4 ABS 7 Fiberglass 8 RMP (SR) 11 Other (specify) </td
1 Domestic 3 Feed lot 6 6 Oil field water supply 9 Dewatering 12 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Monitoring well
Interference 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well 10 Monitoring well 3 Status 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Flush 2 PVC 4 ABS 7 Fiberglass In. to ft. Dia in. to ft. Dia 1 Stall above land surface Flushmount in., weight 0.703 ibs.ft. Wall thickness or gauge No. SCH. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 10 Asbestos-cement 1 Stall biot 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 7 Torch
Interference 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well 10 Monitoring well 3 Status 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Flush 2 PVC 4 ABS 7 Fiberglass In. to ft. Dia in. to ft. Dia 1 Stall above land surface Flushmount in., weight 0.703 ibs.ft. Wall thickness or gauge No. SCH. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 10 Asbestos-cement 1 Stall biot 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 7 Torch
Interference 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well 10 Monitoring well 3 Status 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Flush 2 PVC 4 ABS 7 Fiberglass In. to ft. Dia in. to ft. Dia 1 Stall above land surface Flushmount in., weight 0.703 ibs.ft. Wall thickness or gauge No. SCH. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 10 Asbestos-cement 1 Stall biot 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 7 Torch
2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X Mo X Mo X 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Clamped Clamped Clamped Clamped Clamped Flush Clamped Clamped Clamped Clamped Clamped Flush Clamped Flush Clamped Clamped Clamped Stainless at setei 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 1 None (specify) Clamped Secreter None used (spen hole) Sccreter tile 9 ABS 12 None used (spen hole) Sccreter None Used Screter None Used No K Screter None Used No None Used None (specify) <td< td=""></td<>
2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X Mo X Mo X 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Clamped Clamped Clamped Clamped Clamped Flush Clamped Clamped Clamped Clamped Clamped Flush Clamped Flush Clamped Clamped Clamped Stainless at setei 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 1 None (specify) Clamped Secreter None used (spen hole) Sccreter tile 9 ABS 12 None used (spen hole) Sccreter None Used Screter None Used No K Screter None Used No None Used None (specify) <td< td=""></td<>
Was a chemical/bacteriological sample submitted to Department? Yes No A
submitted Water Well Disinfected? Yes No X 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded Flush Blank casing diameter 2 in. to ft., Dia in. to ft., Dia in. to ft. Casing height above land surface Flushmount in., weight 0.703 Ibs:/ft. Wall thickness or gauge No. SCH. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Agalvarized steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvarized steel 5 Gauzed wrapped 8 Save cut 11 None (open hole) SCREEN OR PERFORATION OPENINGSARE: 5 Gauzed wrapped 9 Drilled holes 1 None (open hole) SCREEN OR PERFORA
5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Flush 2 PVC 4 ABS 7 Fiberglass In. to ft. Dia
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded Flush Blank casing diameter 2 in. to 10 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface Flushmount in., weight 0.703 ibs./ft. Wall thickness or gauge No. SCH. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Absestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 2 Stainless steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 Nore (open hole) 1 Controus slot 3 3 Mill slot 6 Wrot wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
2 PVC 4 ABS 7 Fiberglass Threaded Flush Blank casing diameter 2 in. to 10 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface Flushmount in., weight 0.703 Ibs./ft. Wall thickness or gauge No. SCH. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) SCREEN OR PERFORATED INTERVALS: From 10 ft. to 20 ft. From ft. to ft. 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN OR PERFORATED INTERVALS: From ft. to ft. ft. SCREEN-PERFORATED INTERVALS: From ft. to 20 ft. From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft. to ft. ft. ft. to
Blank casing diameter 2 in. to 10 ft., Dia in. to ft., Dia in. to ft., Dia in. to ft., Dia Casing height above land surface Flushmount in., weight 0.703 ibs./ft. Wall thickness or gauge No. SCH. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Absestos-cement 1 Steiel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft. to ft. from ft. to ft. GRAVEL PACK INTERVALS: From ft. to g
Casing height above land surface Flushmount in., weight 0.703 Ibs./ft. Wall thickness or gauge No. SCH. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steinless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to 20 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 8.5 ft. to 20 ft. From ft. to ft. Grout Intervals From 1 ft. to 8.5 ft. to ft. to ft. to ft. 1 Septic tank 4 Lateral lines 7<
Image: Non-Performation Material: Image: Non-Performation Material: Image: Non-Performation Naterial: Image: Naterinterial: Image: Naterial: </td
Image: Non-Performation Material: Image: Non-Performation Material: Image: Non-Performation Naterial: Image: Naterinterial: Image: Naterial: </td
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft. From ft. to ft. to From ft. to 20 ft. From ft. to ft. to ft. to ft. to GRAVEL PACK INTERVALS: From ft. to 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 1 ft. to 8.5 ft. to
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 8.5 ft. to 20 ft. From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 1 ft. to 8.5 ft. From ft. to ft. ft. Mhat is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 16 Other (specify below) 3 Watertight sewer lines 5 Cess pool 8
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Dilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 8.5 ft. to 20 ft. From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 1 ft. to 8.5 ft. From ft. to ft. ft. 1 step te cank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 <
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 8.5 ft. to 20 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 8.5 ft. to 20 ft. From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 1 ft. to 8.5 ft. From ft. to ft. 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? How many feet?
SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft. From ft. to ft. to GRAVEL PACK INTERVALS: From 8.5 ft. to 20 ft. From ft. to ft. to GRAVEL PACK INTERVALS: From 8.5 ft. to 20 ft. From ft. to ft. to 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 1 ft. to 8.5 ft. From ft. to ft. to ft. to ft. 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
From ft. to ft. From ft. to ft. to ft. to ft. to GRAVEL PACK INTERVALS: From 8.5 ft. to 20 ft. From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 1 ft. to 8.5 ft. From ft. to ft. ft. ft. Grout Intervals From 1 ft. to 8.5 ft. From ft. to ft. ft. Mhat is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? FROM<
GRAVEL PACK INTERVALS: From 8.5 ft. to 20 ft. From ft. to ft. to From ft. to ft. to ft. from ft. to ft. from ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 1 ft. to 8.5 ft. From ft. to ft. to ft. Grout Intervals From 1 ft. to 8.5 ft. From ft. to ft. Grout Intervals From 1 ft. to 8.5 ft. From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit
From ft. to ft. rom ft. to
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 1 ft. to 8.5 ft. From ft. to ft. From ft. to ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? How many feet? How many feet? How many feet? Ithou found to the storage 10 PLUGGING INTERVALS 0 0.3 Concrete Ithou found to the storage Ithou found to the storage Ithou found to the storage
Grout Intervals From ft. to 8.5 ft. From ft. to ft. to<
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? How many feet? How many feet? How many feet? 10 PLUGGING INTERVALS 0 0.3 Concrete Interval Interval Interval
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? How many feet? FROM TO CODE LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 0.3 Concrete Interval Interval Interval
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? How many feet? FROM TO CODE LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 0.3 Concrete Image: Concrete Image: Concrete Image: Concrete
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage How many feet? Direction from well? FROM TO CODE LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 0.3 Concrete Image: Concrete Image: Concrete Image: Concrete
Direction from well? How many feet? FROM TO CODE LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 0.3 Concrete Image: Concrete Image: Concrete Image: Concrete
FROM TO CODE LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 0.3 Concrete
0 0.3 Concrete
Clay, dark brown to brown, increasing
0.8 7.5 silt with depth
Sand, very fine to fine grained, light
7.5 8 brown
8 16 Clay, brown, silty and sandy
16 20 Sand, fine to coarse grained, brown
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was
completed on (mo/day/yr) 04/02/08 and this record is true to the best of my knowledge and belief. Kansas
completed on (mo/day/yr) 04/02/08 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 05/09/08
completed on (mo/day/yr) 04/02/08 and this record is true to the best of my knowledge and belief. Kansas