	WATER WELL RECORD Form	WWC-5 KSA 82a-1212	D NoSVE	-5
LOCATION OF WATER WELL:			wnship Number	Range Number
ounty: Sedgwick	NW % SE % NW	<u>% 28 т</u>	27 s	r 1 (Ew
	n or city street address of well if located with	in city?		
02 S Washington Wichita, Ka				
WATER WELL OWNER: Stewar				
#, St. Address, Box # : 1202 S	Washington	Boa	rd of Agriculture, Divis	ion of Water Resources
y, State, ZIP Code : Wichita	a, Kansas 67211	Арр	lication Number:	
LOCATE WELL'S LOCATON WITH	4	46.0		
AN X IN SECTION BUX:	DEPTH OF COMPLETED WELL	10.0 ft. ELEVATION		
N	Depth(s) Groundwater Encountered 1 WELL'S STATIC WATER LEVEL 17	17.40 ft. 2	ft. 3	; ft.
	WELL'S STATIC WATER LEVEL 17	.0 ft. below land surface r	neasured on mo/day/y	r
NW NE	Pump test data: Well water wa			
	Est Vield NA nom: Well water w	as figher	bours or	moina nom
W X E	Bore Hole Diameter 10.5 in to	16.0 ft. and	in.	to ft.
	WELL WATER TO BE USED AS: 5 Publ	ic water supply 8 /	ir conditioning	Injection well
SW SE	Bore Hole Diameter 10.5 in. to WELL WATER TO BE USED AS: 5 Pub 1 Domestic 3 Feed lot 6 Oil fi	eld water supply 9 [Dewatering 12	Other (Specify below)
	2 Irrigation 4 Industriai 7 Law	n and garden (domestic) 10	Monitoring well	SVE Well
i	Was a chemical/bacteriological sample sub	mitted to Department? Yes	No X If yes,	mo/day/yr sample was
S	submitted		Disinfected? Yes	
TYPE OF BLANK CASING USED:	5 Wrought Iron			Clamped
1 Steel 3 RMP (•	9 Other (specify below)		d
2 PVC 4 ABS				
	7 Fiberglass			ded X
ank casing diameter 4.U	in. to 10 ft., Dia	in. to ft., D	8	in. to ft.
using height above land surface	lush Mount in., weight	ibs./ft. Wall th	ickness or gauge No.	Schedule 40
PE OF SCREEN OR PERFORATION	N MATERIAL:	(7) PVC	10 Asbestos-cemer	rt -
1 Steel 3 Stainle	ess steel 5 Fiberglass	8 RMP (SR)	11 Other (specify)	
2 Brass 4 Galvar	nized steel 6 Concrete tile	9 ABS wrapped 8 Sa	12 None used (ope	n hole)
CREEN OR PERFORATION OPENIN	IGS ARE: 5 Gauzed	wrapped 8 S		11 None (open hole)
1 Continuous slot	Mill slot 6 Wire write	ipped 9 Di	tilled holes	
2 Louvered shutter		n 100	ther (specity)	
CREEN-PERFORATED INTERVALS:		ft. From	ft. to	π.
	Fromft. to	ft. From	ft. to)ft.
GRAVEL PACK INTERVALS:	From 16 ft. to	5.0 ft. From	ft. to	,ft.
	From ft. to	ft. From	ft. to	o ft.
GROUT MATERIAL: 1 Neat of	cement 2 Cement grout	Bentonite 4 th	er Sand	
rout Intervals From	cement 2 Cement grout ft. to ft. From 2.0	ft. to 5.0	t. From 0.0	ft. to 2.0 ft.
hat is the nearest source of possible of	contamination:	10 Livestock pe	ns 14 Aba	indoned water well
1 Septic tank	4 Lateral lines 7 Pit privy		(former) 15 Oil	
2 Sewer lines				
3 Watertight sewer lines	6 Seepage pit 9 Feedyard	13 Insecticide s	-	
rection from well?	NA	How many feet?		0
FROM TO CODE		LITHOLOGIC LOG		
	rk brown silty clay firm			
	rk Brown silty clay, firm, stiff			
	ht brown silty sand fine grain			
	ht brown sand fine grain		, , , , , , , , , , , , , , , , , , ,	alaan daraa ahaa ahaa ahaa ahaa ahaa ahaa aha
	ht brown sand fine grain			
	pring terminated @ 16.0			
	· · · · · · · · · · · · · · · · · · ·		11	
	Flush-mount w	ell completion waiver e	xistent for site.	
				-
	an a			
		-		0 11
CONTRACTOR'S OR LANDOWNE	R'S CERTIFICATION: This water well was) donstructed, (2) reconstructe	d, or (3) plugged under	my jurisdiction and was
	3/20/08	and this record is true to the		
Vater Well Contractor's License No.		This Water Well Record w		
	Quad State Services, In			611-1
Ider the business name of			ature) / /////	mail of Mator thom S M
INSTRUCTIONS: Please fill in blank Jackson St., Ste. 420, Topeka, Kansa	ks and circle the correct answers. Send three co as 66612-1367. Telephone: 913-296-5545. Ser	wes to Kansas Department of Head Id one to WATER WELL OWNER	and Environghent, Bu and retain one for your r	reau of/Water, 1000 S W ecords.