			WATE	R WELL RECORD	Form WWC-					
		ATER WELL:	Fraction	CIV. 4		tion Numbe	'		Range Number	
	Sedgwic		SW 1/4		SE 1/4	7	T 27	<u> </u>	R 1E E/W	
1826 V	V. 13th St	., Wichita		address of well if loca	ited within city	·				
2 WATE	R WELL O	WNER: Town	& Country Ma	rkets						
RR#, St. A	Address, Bo	x# : P.O. B	ox 17087				Board of Agricul	ture, Divis	sion of Water Resources	
			a, Kansas 672				Application Num			
3 LOCAT	E WELL'S	LOCATION	4 DEPTH OF C	OMPLETED WELL	32	ft. ELE	/AΠΟΝ:			
WITH		ECTION BOX:	Depth(s) Ground	dwater Encountered	1 ,	ft	. 2	ft.	3 ft.	
⊼ Γ			WELL'S STATIC	WATER LEVEL	ft.	below land s	surface measured on	mo/day/y	/r	
1		99.4	Pum	p test data: Well wat	erwasN	(A ft. a	fter	nours pur	nping gpm	
-	NW	NE -	Est. Yield N	$oldsymbol{A}_{\cdot\cdot\cdot\cdot}$ gpm: Well wat	er was	ft. a	after	nours pur	nping gpm	
W Kile	į	1.0	Bore Hole Diam	eter8in. t	0 32	ft.,	and	in	. to ft.	
∑ w ⊦		 	WELL WATER	TO BE USED AS: 5	Public water	supply	8 Air conditioning	11	Injection well	
	1		1 Domestic	3 Feedlot 6	Oil field wate	er supply	9 Dewatering	(12)	Other (Specify below)	
	- SW	SE	2 Irrigation	4 Industrial	Lawn and ga	arden only	10 Monitoring well	\sim	Air sparge	
↓	i	$ \mathbf{x} $	Was a chemica	nl/bacteriological samp	le submitted to	Departmen	t? YesNo ✓	; If yes,	mo/day/yr sample was	
<u> </u>		S	submitted			W	ater Well Disinfected	? Yes	No ✓	
5 TYPE	OF BLANK	CASING USED:		5 Wrought iron	8 Concr	ete tile	CASING JOIN	TS: Glued	Clamped	
1 S	teel	3 RMP (S	R)	6 Asbestos-Cement	9 Other	(specify bel	ow)	Weld	ed	
(2)P		4 ABS		7 Fiberglass					aded. 🗸	
Blank casi	ing diamete	r	in. to 3	0 ft., Dia	in. t	to	ft., Dia		. in. to ft.	
									lo Sch. 40	
_	_	R PERFORATIO			(7)PV		10 Asbe			
1 S	teel	3 Stainles	s steel	5 Fiberglass	8 RM	P (SR)	11 Other	(specify)	
2 B	rass	4 Galvaniz	zed steel	6 Concrete tile	9 AB		12 N one	used (op	en hole)	
SCREEN	OR PERFO	RATION OPENIN	IGS ARE:	5 Gauz	ed wrapped		8 Saw cut		11 None (open hole)	
1 C	ontinuous s	slot (3)	/lill slot	6 Wire	wrapped		9 Drilled holes		()	
2 L	ouvered sho	utter 4 k	Key punched	7 Torc	h cut		10 Other (specify)			
SCREEN-	PERFORAT	ED INTERVALS		3.0 ft. to .	32	ft., F	rom	ft.	to ft.	
									to ft.	
	GRAVEL PA	CK INTERVALS	: From	28 ft. to .	32	ft., F	rom	ft.	to ft.	
			From	ft. to .	<i></i>	ft., F	rom	ft.	to ft.	
6 GROU	MATERIA	L: 1 Neat	cement	2 Cement grout	3 Bento	nite 4	Other			
			. ft. to 28	ft., From	ft. ·	to	ft, From		ft. to ft.	
What is th	e nearest s	ource of possible	e contamination:			10 Live	stock pens	14 A	bandoned water well	
1 Sept	tic tank	4 Late	ral lines	7 Pit privy			l storage	15 O	il well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon						12 Fer	12 Fertilizer storage 16 Other (specify below)			
3 Wat	ertight sewe		page pit	9 Feedyard		13 Inse	ecticide storage			
	from well?			•		How ma	iny feet?			
FROM	ТО		LITHOLOGIC	LOG	FROM	ТО	PLU	GGING IN	ITERVALS	
0	0.5	Concrete,								
0.5	1.5	Sand fill,								
1.5	4	Clay, sl. sand	y, moist, Dark	Brown						
4	9	Sand (vf-f), c	layey, moist, F	Brown						
9	12		l. moist, Yellov							
12	20		l. moist, Lt. G							
20	26			y to Dark Gray						
26	32			rayish Brown to	В					
							AS3, Flushmount			
							Project Name: GF - 7	Town Co	untry #28	
7 65 -	10705:5		NO 05575151	OU T.:			GeoCore # 1401, KD			
				ON: This water well w						
									knowledge and belief.	
	ater Well C	ontractor's Licer	11.	*/// Th	is Water Well	Pecord was	completed on (mo/d	av/vr) a	5/19/08	
					is vvalor vvoi		./1	" <i>[[</i>	1711	
	business na	ame of	Ge	oCore, Inc.		by (signa	ature) Ool	Rel	end top three copies to Kansas	