	WATER W	ELL RF0	CORD I	orm \	νw	C-5 K	(SA 82a-12	212			
1 LOCATION OF WATER WELL:	FRACTION NE SW NW SW					ON NUMBER			RANG	RANGE NUMBER	
Sedgwick	₩₩ 1/4	GIM	1/4 8*W	1/4		33	т 27	28 S	R	1E E/W	
	Vichita, Kan	sas	nin city?								
	LACE, Judy	,						Board of Ad	riculture, Division	of Water Resource	
	S. Topeka ita, Kansas				710	CODE		Application Nu			
		Based WE	11. 2	3	ft.	CODE:	ELEVATION:		iniber.		
WITH AN "X" IN SECTION BOX:	EPTH OF COME	•••		3			ELEVATION.			4	
	th of groundwate LL'S STATIC WA		_	FT 0	ft.		IDE 4 OF 1454	ft.		ft.	
		mp test data		FI. B	ELOV	V LAND SU	JRFACE MEAS ft. after		• •	/17/08	
υΝΨ ΝΕ	Est. Yield:	gpm		ater was			ft. after		rs of pumping @ rs of pumping @		
See Bo	re Hole Diamete		in.		0	ft.		in.	to	-	
WE	LL WATER 40A							9. Dewate	ring 11. t	njection well	
		Feedlot					and garden on		12. Other	(Specify below)	
	Irrigation 4. as a chemical/bacte	Industrial					nditioning	10. Monitor	i ng well , wh <u>at</u> mo/day/y	ır was samole	
	as a chemical/bacte mitted	nological samp	pie submitted to	Departme	entr	YES Was \	NO Water Well Disi		YES	NO NO	
5 TYPE OF CASING USED:	5. Wrought	Iron	7. Fiberglass		9. Oth	ner (Specify	v helow) CA	ASING JOINTS:	Glued	Threaded	
1. Steel 3. RPM (SR)		-	•	o. o	ioi (opooii)	, 00.011		Welded	Clamped	
2. PVC 4. ABS	6. Asbesto	s-Cement	8. Concrete	tile							
Blank casing diameter 1 1/4 i	n. to	ft.,	Dia.	i	n.	to	ft,	Dia.	in. to	ft.	
Casing height below and surface:	36 in.,		Weight:		lbs	s. / ft.	Wall	thickness or ga	uge No.		
TYPE OF SCREEN OR PERFORATION			7.01/0			_			NI/A		
Steel 3. Stainless Steel Rass 4. Galvanized	5. Fiberglass		7. PVC		9. AB			Other (specify)			
	6. Concrete 1	lile	8. RMP (SR)	1	10. As	bestos-Cer	ment 12. N	None used (ope	n hole)		
SCREEN OR PERFORATION OPENING											
1. Continuous slot 3. Mill slot 5. Gauzed wrapped			7	7. Torch cut 9. Drilled holes 11. None (open hole)							
2. Louvered shutter 4. Key pu	nched 6.	Wire wrapp	ed	8	3. Saw	/ cut	10. Ot	her (specify) $ m l $	V/A		
SCREEN - PERFORATION INTERVAL	From	f	t. t)		ft.,	From	ft.	to	ft.	
	From	f	t. t)		ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:	From	f	t. 1	0		ft.,	From	ft.	to	ft.	
	From	f	t. 1	0		ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat of	ement	2 Ceme	nt Grout		3	Bentonite			tonite hole		
Grout Intervals: From	ft. to				ft.	to	- ft.,	DCI	3 ft.	to 23 ft.	
What is the nearest source of possible co	-	. Pit privy		10. Live :							
1. Septic tank 4. Lateral	illies					-		ticide storage	40.04	ell/Gas well	
2. Sewer lines 5. Cess Po		. Sewage la	•	11. Fuel		-	14. Aban	don water wel	l 16. Other	(specify below)	
Watertight sewer line 6. Seepag Direction from well?	ge pit 9	. Feed yard		12. Fert	ilizer	storage					
	ITHOLOGI	CLOG		Fro	m	То	Hown	nany feet?	0010100		
	- THIOLOGI	0 100		1 10		3	cement	LITHOL	OGIC LOG		
				3		23	bentonite l	hole plug			
			·	+	\dashv						
				+			· · · · · · · · · · · · · · · · · · ·				
				+-							
				\perp							
				-	-		<u> </u>				
				+	\dashv						
										· · · · · · · · · · · · · · · · · · ·	
Contractor's or Landowner's Certific	ation: This water	well was 1.	constructe	d 2.	rec	onstructe	d or 3.	plugged	under my juris	diction and	
was completed on (mo/day/year) 6/17/2008 and this record is true to the best of my knowledge and belief.											

was completed on (mo/day/year) 6/17/2008 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6/18/2008

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp