				ER WELL RECOR	D Form			212 ID No.				
	ON OF WATE		Fraction				ion Number	I .	p Number	Ran	ge Numbe	er
			SE 1/4			1/4	20	T 2	7 s	R	1	Е
	d direction from arket - Wicl		n or city street a	ddress of well if lo	cated wit	hin city?						
2 WATER	WELL OWNE	R: T&B C	orporation									
 RR#, St. Ad	dress, Box #	: 1955 S	6. Washingto	on				Board of A	griculture, Div	ision of W	ater Resc	urces
City State	ZID Code	Wichit	a. KS 67211					Application	•			
LOCATE	WELL'S LOC	CATON WITH	4				-					
AN "X <u>" IN</u>	N SECTION B	OX:	TOFALH OF	COMPLETED WE	ELL	32.5	ft. ELEV	'ATION:	1297	7.47 (TC)C)	
1 I		1		dwater Encounter								
	NW	- NE	WELL'S STATION	C WATER LEVEL		ft. l	below land si	urface measu	ed on mo/day	/yr		
	i	i		np test data: We								
₩ W		E	Est. Yield	gpm: We	ell water w	vas	ft	. after	hours	pumping		gpm
7		l I	Bore Hole Diam	neter 8.25	in. to	32.	5	ft. and	i	n. to		ft.
	sˈw - 	SE	WELL WATER	TO BE USED AS:	: 5 Pub	olic water su	ipply	8 Air con	ditioning 1	1 Injection	n well	
	i	i	1 Domesti	ic 3 Feed lot	6 Oil f	field water s	vlgqua	9 Dewate	rina 1	2 Other	(Specify b	oelow)
† L		X	2 Irrigation	n 4 Industrial	7 Law	vn and gard	en (domestic) 10 Monito	oring well	Air	Sparge	
	S			l/bacteriological sa								
			submitted						ected? Yes		No X	
5 TYPE OF	F BLANK CAS	SING USED:		5 Wrought In	on	8 Concre			JOINTS: Glue			<u></u>
1 Ste		3 RMP (6 Asbestos-0					Wel			
2 PV		4 ABS	,	7 Fiberglass						ded	Flust	h
				•								
Blank casing	g diameter	····· <u>·</u>	in. to 31	0 ft., Dia		in. to	D	_ ft., Dia		_in. to		ft.
				in., weight	0.						CH. 40)
TYPE OF S	CREEN OR P	ERFORATIO	N MATERIAL:						Asbestos-cem			
1 Ste	el	3 Stainle		5 Fiberglass		8	RMP (SR)	11 (Other (specify)	·		
2 Bra			nized steel	6 Concrete to		9	ABS	12 1	None used (op	en hole)		
	R PERFORAT			5						11 None	e (open h	ole)
	ntinuous slot		Mill slot		Wire wr	apped		9 Drilled h				
2 Lou	vered shutter	4	Key punched		Torch c			10 Other (s	pecify)			
SCREEN-P	ERFORATED	INTERVALS:	From	30 ft. to		32.5	ft. F	rom	ft.	to		ft.
			From	ft. to			ft. F	rom	ft.	to		ft.
GRA	AVEL PACK I	NTERVALS:	From	15 ft. to		32.5	ft. F	rom	ft.	to		ft.
					5							
6 GROUT	MATERIAL:	1 Neat	cement :	2 Cement grout		3 Ben	tonite	4 Other Po	ft. ortland Gre	out		
				ft. From		ft t	<u> </u>	ft Fro	m	ft to		ft.
			contamination:					ock pens		andoned		
			4 Lateral lines	7 F	Pit privy		11 Fuels	storage	15 Oi			'
	wer lines		5 Cess pool		Sewage la			zer storage		her (speci		
	tertight sewer	lines	6 Seepage pit		eedyard	.300		ticide storage		(0000)	,, 20.0,	
Direction fro	•		o coopage p.		,		How many					
FROM	ТО	CODE	LITHO	LOGIC LOG		FROM	TO		PLUGGING I	NTERVAL	.s	
0	0.3	Co	ncrete									
0.3	3		I, Clay, dark									
3	6		ay, gray , iron	content								
6	9		ndy Silt									
9	10		ndy Clay									
40	00			gray, fine to coa	arse							
10	32.5	gra	ined, coarseni	ng downward								
		NA/	all Campleti	an Notal			-					
			ell Completi		******							
				re for remediati	on							
		1.1		n pipe trench			+					
7 CONTR	ACTOR'S OR	LANDOMANE		TION: This water		(1) construct	ted (2) rese	netructed or /	3) plugged :::	or my los-	diction	d
					wen was							
	on (mo/day/yr)			19/08					of my knowle	-		
Water Well	Contractor's L	icense No.		531		This W	ater Well Re	cord was con	pleted (mo	/day/yr)	10/15	/08
	usiness name			cal Services			(signature)		1/2			
INSTRI Jackson	UCTIONS:. Ple	ease fill in blank Topeka, Kansa	s and circle the co	elephone: 913-296-	d three co	pies to Kans	as Departmen	it of Health and DWNER and re	Environment, E	ureau of W	ater, 1000	sw