	WATER WELL RECORD	Form WWC-5	KSA 82a-1	212 ID No				
LOCATION OF WATER WELL			tion Number		ber	Range	Numbe	
unty: Sedgwick	SE ½ SE ½	SE ¼	20	⊤ 27	s	R	1	E
tance and direction from neare	est town or city street address of well if loc	ated within city?						
5 S. Market - Wichita								
WATER WELL OWNER: T&								
#, St. Address, Box # : 19	155 S. Washington			Board of Agricult	ure, Divisio	n of Wate	r Resou	ırces
y, State, ZIP Code : W	ichita, KS 67211			Application Number	oer:			
LOCATE WELL'S LOCATON AN "X" IN SECTION BOX:	MITH 4 DEPTH OF COMPLETED WEL	23	4 FIE\	/ATION:	1298.1	з (ТОС	1	
AN A IN SECTION BOX.								
	Depth(s) Groundwater Encountere							
NW NE								
	Pump test data: Well	water was	f	t. after	hours pum	ping	!	gpm
W	Est. Yield gpm: Well	water was	f	l. after	hours pum	ping	!	gpm
1 1	Bore Hole Diameter 10.25 in	n. to 23	3	ft. and	in. to	,,	,	_ ft.
SW SE	1 :	5 Public water si	upply	8 Air conditionin		njection w		
	1 Domestic 3 Feed lot 2 Irrigation 4 Industrial	6 Oil field water	supply	9 Dewatering	12 <u>[</u> 12 Soi	Jinen (Sp	ecily be	iow)
S								
	Was a chemical/bacteriological sai							
	submitted			ter Well Disinfected?				
TYPE OF BLANK CASING US	<u> </u>			CASING JOINTS		CI	amped	
1 Steel 3	RMP (SR) 6 Asbestos-C	ement 9 Other	(specify belo					
2 PVC 4					Threaded	_		
ink casing diameter 4	in. to 8 ft., Dia				in.	. to		ft.
sing height above land surface	Flushmount in., weight	0.703	lbs /ft	Wall thickness or ga	uge No.	SC	H. 40	-
PE OF SCREEN OR PERFOR		7	PVC	10 Asbest	os-cement			
4 Charl 0	Chairless steel E Fibereless	-	DMD (CD)	44 Other (
2 Brass 4	Galvanized steel 5 Fiberglass Galvanized steel 6 Concrete tile	e 9	ABS	12 None u	sed (open l	hole)		
REEN OR PERFORATION OF	PENINGS ARE: 5	Gauzed wrapped		8 Saw cut	11	None (pen ho	le)
1 Continuous slot	3 Mill slot 6	Wire wrapped		9 Drilled holes		•	•	•
2 Louvered shutter		Torch cut		10 Other (specify)			
REEN-PERFORATED INTER	•		fi f	From	ft to			ft
ALEM EN ONNED INVEN								
GRAVEL PACK INTERV	From ft. to //ALS: From 7 ft. to			rom				
GRAVEL FACE INTERV								
				rom Doubles				ft.
	Neat cement 2 Cement grout							· ·
	ft. to 5 ft. From	5 ft.	to 3	ft. From				ft.
nat is the nearest source of pos					14 Aband			
•	4 Lateral lines 7 Pi			storage	15 Oil we	II/ Gas w	ell	
2 Sewer lines	•	ewage lagoon		izer storage	16 Other	(specify I	pelow)	
3 Watertight sewer lines	6 Seepage pit 9 Fe	eedyard		ticide storage				- -
ection from well?			How many					
FROM TO CODE	-	FROM	ТО	PLUG	GING INTE	RVALS		
0 0.3	Concrete							
0.3 4	Fill, Clay, dark gray		+					
4 8	Clay, gray							
1	Sand, yellow to gray, medium to							
9 22	coarse grained, coarsening down	ward						
8 23	!	1						
8 23								—
8 23	Well Completion Note:							
8 23	Well Completion Note:							
8 23	0' to 1' - Concrete	on .						
8 23	0' to 1' - Concrete 1' to 3' - Sand, for remediation							
8 23	0' to 1' - Concrete							
8 23	0' to 1' - Concrete 1' to 3' - Sand, for remediation							
	0' to 1' - Concrete 1' to 3' - Sand, for remediation system pipe trench		cted (2) ross	posturated or (2) ships	and under	ny ji wiodi	tion end	
CONTRACTOR'S OR LANDO	0' to 1' - Concrete 1' to 3' - Sand, for remediation system pipe trench DWNER'S CERTIFICATION: This water w	vell was (1) constru			-			
CONTRACTOR'S OR LANDO	0' to 1' - Concrete 1' to 3' - Sand, for remediation system pipe trench DWNER'S CERTIFICATION: This water water was 09/19/08	vell was (1) constru	nis record is t	rue to the best of my	knowledge	and belie	f. Kans	sas
	0' to 1' - Concrete 1' to 3' - Sand, for remediation system pipe trench DWNER'S CERTIFICATION: This water water was 09/19/08	vell was (1) constru and th	nis record is t	rue to the best of my	knowledge	and belie	f. Kans	sas