T					VELL RECO	ORD For	m WWC-5	KSA	82a-1			
	ON OF WATE		Fraction		A 11.47	0144		ction Nu	ımber			Range Number
	Sed	gwick	SW	1/4		SW	1/4	33		T 27	S	R 1 (E)W
Distance an	a affection fro	m nearest to	wn or city stre	et addre	ss of well if	located w	ithin city?					
2 WATER	WELL OWNE	p. Disco	unt Cigar	ottae							-	
			S Broadw							B	b D:	
Cit. Ct-1-	710.0-4-	Wichi	to Ko	ay						-		ision of Water Resources
LOCATE	ZIP Code WELL'S LOC	TATOM MOTA	ıla, NS							Application Nu	mber:	
3 AN "X" IN	N SECTION B	OX:	4 DEPTH	OF COM	PLETED V	WELL	3	5 ft.	FLE	VATION:		
	N											3ft.
			MELL'S ST	ATIC MA	ATED LEV				''		IL.	/yr
	. i I	! I										
	NW 	- NE	1									oumping gpm
0	: 1	į	Est. Yield	. 	gpm: V	Vell water	was		1	ft. after	hours p	pumping gpm
₩ W		╼┿╼╼┫╒	Bore Hole [Bore Hole Diameter 8.25 in. to 35 ft. and WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditi 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewaterin							ir	1. toft.
Γ X	· !		WELL WAT	ER TO E	BE USED A	\S: 5 Pu	blic water	supply		8 Air condition	ning 1	1 Injection well
r^	sw	- SE										
	i											
′				nical/bac	teriological	sample s	ubmitted to	Departr				, mo/day/yr sample was
	S		submitted									No X
5 TYPE OF	F BLANK CAS	SING USED:		5	Wrought	Iron	8 Cond	crete tile		CASING JOIN	TS: Glue	d X Clamped
_1_Ste	eel	3 RMP	(SR)	ε	Asbesto	s-Cement	9 Othe	r (specif	y belo	ow)	Welc	ded
2 PV	С	4 ABS			' Fibergla:				-			aded
							in	to		ft Dia		in. toft.
Casing hair	ht ahova land	surface	···· ··· ··· ·· · · · · · · · · · · ·	in	weight		716		 he /#	Wall thickness or	nauga Ma	154
TYPE OF S	CREEN OR P	FRECRATIC	ON MATERIAL	· ""'',	weight	'	1 10 17	TING	DS./II.	10 Asha	gauge No.	
1 Ste			less steel	-· -	Fibergla	ce	/_	FVC	(SB)	11 Other	r (enacify)	21 IL
2 Bra			anized steel	ě	Concrete	oo o tilo	0	ABS	(OH)	12 None	used (on	en hole)
	R PERFORAT			`		5 Gauze	d wranned	ı			٠.	11 None (open hole)
	ntinuous slot		Mill slot			6 Wire w				9 Drilled holes		TT Trone (open note)
			Key punche	d		7 Torch				10 Other (speci	fv)	
	ERFORATED								ft 1	From	ft	to ft.
OOMELIN		IIII EIIIVAE										
CD.	AVEL DACK II	NITEDVALO.										to ft.
GH/	AVEL PACK II	NIEHVALS:										to ft.
			From			. to			ft. I	From	ft.	to ft.
GROUT	MATERIAL:	1 Neat	t cement	2 C	ement grou	t	3 Be	entonite		4 Other		
Grout Interv	als From	1	ft. to	28	ft. From		ft.	to		ft. From		ft. toft.
What is the	nearest sourc	e of possible	e contaminatio	n:				10	Lives	stock pens	14 Ab	andoned water well
1 Sep	ptic tank		4 Lateral I							storage	15 Oil	I well/ Gas well
2 Sev	wer lines		5 Cess po	ol	8	Sewage	agoon	12	Fertil	lizer storage	16 Ot	her (specify below)
3 Wa	itertight sewer	lines	6 Seepag	e pit	9	Feedyard	1	13	Insec	cticide storage	Co	ontaminated Site
Direction fro	m well?							How	many	/ feet?		
FROM	ТО	CODE		THOLOG	IC LOG		FROM	T	0	PLU	IGGING II	NTERVALS
0	7		layey silt									
7	12		ine sand									
12	16		led sand					_				
16	35	C	ourse san	d								
								\perp				
							-					
		-					-					
7 000	ACTORIO CO	LANDONA	EDIO OFFICE	CATIO	This		140	1 /2				
						er well was	_					er my jurisdiction and was
1 -	on (mo/day/yr)			9-10-0			and	this reco	rd is t	true to the best of m	y knowled	dge and belief. Kansas
Water Well	Contractor's L	icense No.			783			Water V	Vell R	ecord was complete	ed on (mo	/day/yr) 10/7/08
under the bi	usiness name	of	W		Pump 8					by (signature)	<u> </u>	Sette
INSTR	UCTIONS: Ple	ease fill in blar	nks and circle th	e correct	answers. S	end three c	opies to Ka	nsas Dep	artme	nt of Health and Envir	onment B	ureau of Water, 1000 S W
Jackso	n St., Ste. 420,	Topeka, Kan	sas 66612-1367	. Teleph	one: 913-29	2 6-5545. Se	end one to \	NATER \	VELL	OWNER and retain or	ne for your	records.