I I OCATION OF WATER WELL		UHD Form WV	/WC-5 KSA 82a-1212 ID No. AS 6					
LOCATION OF WATER WELL:	Fraction SW 1/4 NW 1/4 SW		Section Number		l l	Range Number		
istance and direction from nearest	town or city street address of well it	f located within c	133	T 27	S R		(EA	
stands and anodion nom noaroot	to the one of the or the or	i locatoa within c	y.					
WATER WELL OWNER: DISC	ount Cigarettes							
- R#, St. Address, Box # : 2160				Board of Agricu	Iture, Division of	Water Re	source	
Sh. Ctata ZID Cada . Wick	nita Ke			A !! ! ! ! !	- L			
B LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX:	TH 4							
'_AN "X" IN SECTION BOX:	DEPTH OF COMPLETED	WELL .	35 ft. ELE	VATION:				
N								
	WELL'S STATIC WATER LEV	EL NA	ft. below land	surface measured or	n mo/day/yr			
	Pump test data:	Well water was		ft. after	hours pumping		gpm	
	Est. Yield gpm: \							
₩ W	E Bore Hole Diameter 8.25	in. to	35	ft. and	in. to		ft.	
- 1. ! !	WELL WATER TO BE USED A 1 Domestic 3 Feed lot	AS: 5 Public w	ater supply	8 Air condition	ing 11 Inject	ion well		
X SE								
iiii	2 Irrigation 4 Industria							
* L	Was a chemical/bacteriologica	ıl sample submitt	ed to Department?	Yes No X	[If yes, mo/day	//yr samp	le was	
S	submitted		Wa	ater Well Disinfected	l? Yes	No 2	x	
TYPE OF BLANK CASING USED): 5 Wrough	t Iron 8	Concrete tile	CASING JOIN	TS: Glued X	Clamp	ed	
_1_Steel 3 RM	P (SR) 6 Asbesto	s-Cement 9	Other (specify belo	ow)	Welded			
2 PVC 4 ABS	S 7 Fibergla	ass						
Blank casing diameter 2	in. to 30 ft., Dia		in. to	ft., Dia	in. to		ft	
Casing height above land surface								
YPE OF SCREEN OR PERFORAT			7 PVC	10 Asbes	stos-cement			
1 Steel 3 Sta	inless steel 5 Fibergla	ass	8 RMP (SR)	11 Other	(specify)			
2 Brass 4 Gal	inless steel 5 Fibergla vanized steel 6 Concret	te tile	9 ABS	11 Other 12 None 8 Saw cut	used (open hole)			
CREEN OR PERFORATION OPE	NINGS ARE:	5 Gauzed wra	pped	8 Saw cut	11 No	ne (open	ı hole)	
	3 Mill slot		ed	9 Drilled holes				
2 Louvered shutter		7 Torch cut		10 Other (specif	y)			
SCREEN-PERFORATED INTERVAL		t. to	35 ft.	From	ft. to		ft.	
	From ff	t. to	ft.	From	ft. to		ft.	
GRAVEL PACK INTERVALS	S: From 28 fi	t. to	35 ft.	From	ft. to		ft.	
	From fi	t. to	ft.	From	ft. to		ft	
6 GROUT MATERIAL: 1 Ne	at cement 2 Cement grou	ut	3 Bentonite	4 Other				
Grout Intervals From 1	ft. to 28 ft. From		ft. to	ft. From	ft. to		ft	
What is the nearest source of possib				stock pens	14 Abandone	d water w	vell	
1 Septic tank		Pit privy		storage	15 Oil well/ Ga	as well		
2 Sewer lines	5 Cess pool 8	Sewage lagoo	n 12 Ferti	lizer storage	16 Other (spe	cify below	w)	
3 Watertight sewer lines	6 Seepage pit 9	Feedyard	13 Inse	cticide storage	Contam	nated	Site	
Direction from well?			How many					
FROM TO CODE	LITHOLOGIC LOG	F	ROM TO	PLU	GGING INTERVA	ILS		
	Clayey silt Fine sand							
	Med sand							
	Course sand							
	504700 04110							
Z CONTRACTORIS OF LANDOW	NEDIS CERTIFICATION. This	tor well was life's s	anatrustad (0) ====	potruoted or (2) =1	and under my ins	iediation	and was	
7 CONTRACTOR'S OR LANDOW								
completed on (mo/day/yr)	9-17-08			true to the best of m				
Vater Well Contractor's License No.	783			ecord was complete			7/08	
inder the business name of	Woofter Pump			oy (signature)	1 Sout	<u></u>	00.0	
INSTRUCTIONS: Please fill in bl	anks and circle the correct answers. S			nt of Health and Envir OWNER and retain or		water, 10	00 S W	