WATER V	VELL RECORD FO	orm WW	C-5 K	SA 82a-1212	2		
1 LOCATION OF WATER WELL: FRACTION	I			R TOWNSHIP NUMBER RANGE NUMBER			_
Sedgwick SE 1//		1/4	4	T 27	<u> </u>	R 1	E E/W
,	a, Kansas						
2 WATER WELL OWNER: BEST SUPPLY CO.							
RR#,ST. ADDRESS,BOX #: 1545 E. 29th N. Board of Agriculture, Division of Water Resource							
CITY, STATE: Wichita, Kansas	40		CODE:		Application Nur	mber:	
3 LOCATE WELL'S LOCATION 4 DEPTH OF COM				ELEVATION:	_		
N Depth of groundwa	10	ft.	ALL AND CL	IDEACE MEASUE	ft.	J.,	ft.
WELL'S STATIC V	Pump test data: Well water		V LAND SU	JRFACE MEASUR ft. after		day/yr: 11 s of pumping @	/3/08
	gpm Well water			ft. after		s of pumping @	gpm gpm
Est. Yield:	er in.	to	ft.	and	in.	to	ft.
	WELL WATER TO BE USED AS: 9. Dewatering 11. Injection well 1. Domestic 3. Feedlot 5. Public water supply 12. Other (Specify below)						
1. Domestic 3. Feedlot 5. Public water supply 1. Lawn and garden only 12. Other (Specify below) 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well							
S Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample							
submitted			Was V	Vater Well Disinfe	cted?	YES	NO
5 TYPE OF CASING USED: 5. Wroug	ht Iron 7. Fiberglass	9. Otl	ner (Specify	below) CASIN	IG JOINTS:	Glued	Threaded
,	tos-Cement 8. Concrete tile	•				Welded	Clamped
Blank casing diameter in. to	ft., Dia.	in.	to	ft., D	ia.	in. to	ft.
Casing height above land surface: 36 in.,	Weight:	lb	s. / ft.	Wall thic	kness or gau	ge No.	
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) N/A							
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)							
	. Wire wrapped	8. Sa v			(specify) N		(
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		o. cu			• • • • • • • • • • • • • • • • • • • •		
SCREEN - PERFORATION INTERVAL From	ft. to		ft.,	From	ft.	to	ft.
From GRAVEL PACK INTERVALS: From	ft. to		ft., ft.,	From From	ft. ft.	to to	ft.
From	ft. to		ft.,	From	ft.	to	ft.
	2. Cement Grout		Bentonite				ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: From ft. to ft., From ft. to ft., From 3 ft. to 25 ft.							
What is the nearest source of possible contamination:						-	
1. Septic tank 4. Lateral lines 1. Septic tank 4. Lateral line							
2. Sewer lines 5. Cess Pool 5. Cess Pool 5. Cess Pool 6.							
S. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? North How many feet? 70 ft. plus							
From To LITHOLOG	IC LOG	From	To			OGÍC LOG	
		0	3	compacted e			
		25	25 40	bentonite ho well gravel	e plug		
	***************************************			Well graver			
7 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				d or o	boppu	under my jurior	liction and
Contractor's or Landowner's Certification: This water well was 1, constructed 2, reconstructed or 3, plugged under my jurisdiction and was completed on (mo/day/year) 11-3-2008 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 11/7/2008							
under the business name of Harp Well and Pump Service by (signature) Todd S. Hovb							