				VVAILIV	VELL RECO	ווטו לאו	1 4444 -3	10A 02a-1	212 101	***			
	N OF WATE							on Number	[nship Number	Ra	nge Numbe	r
	Sed							15	Т	27 s	R	1	E
	d direction fro					located wit	hin city?	·					
At Interse	ection of H	ydraulic a	nd Murdoo	k – Wic	chita								
	WELL OWNE												
- R#, St. Add	dress, Box#	: 1416 I	Dodge St.	., Rm. 9	930				Board	of Agriculture,	Division of V	Vater Resou	urces
:4 C4-4- T	ZID Cada	. Omah	a NF 68	170					Applica	ation Number:			
LOCATE	WELL'S LOC	ATON WITH	1 1							ation Number:			
AN "X" IN	I SECTION B	OX:	DEPTH	OF COM	IPLETED W	VELL	27.	ft. ELE\	VATION:				
	į		Depth(s) G	roundwat	er Encounte	ered 1	15	ft	. 2		ft. 3		ft.
	NW -		l .			_				asured on mo/			
[-	14VV	: NE											
w L	ł	_		rump te:	Si uala. Vi	ven water v	vas	'	i. ailei	hoı	urs pumping		gpiii
- ''	i	_	Est. Yield		gpm: v\	veli water v	vas	<u>-</u> ¹	τ. aπer	ho	urs pumping		gpm
х		!	Bore Hole	Diameter	8 >= 110=5 A	in. to	41.	5	ft. and	conditioning vatering	in. to		ft.
	sw	- SE	WELL WA	TER TO E	3 Food lot	S: 5 Put	olic water su	pply	8 Air (conditioning	11 Injecti	on well	dow)
,		1	1 00	nesuc .	3 Feed lot	6 Oil	neiu water s	supply	9 Dev	vatering		(Specify be	low)
	S									onitoring well			
	3		Was a che	mical/bac	teriological	sample su	bmitted to E	epartment?	Yes	No X If	yes, mo/day	/yr sample v	was
			submitted					Wa	ater Well Di	sinfected? Ye	es	No X	
TYPE OF	BLANK CAS	ING USED:		E	Wrought	Iron	8 Concre	te tile	CASI	NG JOINTS: (Glued	Clamped	
1 Ste		3 RMP						specify belo			Welded		
												Flush	
2 PV		4 ABS			7 Fiberglas						nreaded	riusn	
llank casing	g diameter	2	in. to	7.5	ft., Dia		in. t		ft., Dia		in. to		ft.
asing heig	ht above land	surface	Flush	in.,	weight	0.	703	lbs./ft.	Wall thick	ness or gauge	No.	SCH. 40	
YPE OF S	CREEN OR P	ERFORATIO	N MATERIA	L:			7	PVC	1	10 Asbestos-c	ement		
1 Ste	el	3 Stain	less steel	5	5 Fiberglas	SS	8	RMP (SR)		11 Other (spe	cifv)		
2 Bra		4 Galva	nized steel	e	6 Concrete	tile	9	ABS	1	11 Other (spe 2 None used	(open hole)		
CREEN O	R PERFORAT									cut			
	ntinuous slot	-	Mill slot									, , ,	,
	vered shutter		Key punche			7 Torch o				er (specify)			
								4.1		(Specify)	4 1-		
ONECIN-PI	ERFORATED	HALEKAMES											
.			From _		tt.	ιο			rom		π. το		· tt.
GRA	AVEL PACK I	NTERVALS:				to	27.5	ft. l	From		_ ft. to	-	ft.
			From		ft.	to		ft.	From		ft. to		ft.
GROUT	MATERIAL:	1 Neat	cement	2 Ce	ement grout	ì	3 Ben	tonite	4 Other				
 Frout Interv	als From	1	ft to	5.5	ft From		ft	<u> </u>	ft	From	ft to		ft
	nearest sourc				- 11. 110111		· · · ·		stock pens		Abandoned		
		o or possible			7	Dit priva			•	15			
	ver lines		5 Cess p			Sewage la		12 Fertil			Other (spe		
						Feedvard	-				Other (spec	city below)	
	tertight sewer	imes	6 Seepa	je pii	9	reedyard			cticide stora	age			
irection fro		CODE	1 1	THO! OF	210 1 00		EBOM	How many	reet?	DI LICON	IC INTERVA	16	
FROM	то	CODE		THOLOG		lia-L4	FROM	ТО		PLUGGI	NG INTERVA	112	
			and, fine to		-	-							
0	27.5	1 1	own to gray id 10'	, with 5	Onie Sni Di	ermeen 2							
	27.0	ai ai	10				 	+					
	<u> </u>	 							 				
						*					***************************************		
							<u> </u>	 					
		 					 	1					
····	L					·	 	1					
							†		 				
		 -					 		<u> </u>				
	<u> </u>							 					
CONTRA	CTOP'S SS	LANDOVACE	ייי אייי	1007101	l. This		(4)	4=4 (0) == :		/0\ · · ·			، ، الم
_						er well was				or (3) plugged	_		
•	n (mo/day/yr)			10/21/0					/ \	best of my kno	,, -		sas
Vater Well	Contractor's L	icense No.			531		This V	/ater Well R	ecord was	completed	(mo/day/yr)	11/12	/08
inder the bu	usiness name	of	Geotec	hnical	Service		b\	(signature)	しんん.	_ 18			
INSTRI	JCTIONS:. PI	ease fill in blar	ks and circle t	he correct	answers. So	end three co	pies to Kans	as Departme	nt of Health	and Environme		Water, 1000	SW
										d retain one for			