. *				TER WELL RECO	ORD Form		KSA 82a-			
	ON OF WATE				0144		ion Number			Range Number
County:	Sed	gwick	NW 1/4		SW		20	⊤ 27	S	R 1 E
Distance an	nd direction fro	m nearest	town or city street a	206 N. Sei			ita, Ks			
	WELL OWNE									
RR#, St. Ad	ldress, Box#	: 206	S. Senecca	•				•		sion of Water Resources
City, State,	ZIP Code	: VVIC	hita, Ks 6720	3				Application Num	ber:	
3 AN "X" II	WELL'S LOC N SECTION B	BOX:	''' 4 DEPTH OF	COMPLETED	VELL	24.	ft. ELE	VATION:	13	300.55
			Depth(s) Grou	ndwater Encount	tered 11.5	17.	50	ft. 2	ft.	Ft. 01/21/09
	N							surface measured on		r 01/21/09
. Г	- ; ; ;		I							umping Gpm
	į	.i_	Est. Yield	Gpm: V	Vell water v	vas		Ft. after	Hours p	umping Gpm
	NW	NE	Bore Hole Diar	meter 8.625	In. to	25	5	ft. and	in.	to Ft.
₩ ₩	i		WELL WATER	TO BE USED A	S: 5 Pub	olic water su	upply	8 Air conditionin	ıg 11	to Ft. Injection well Other (Specify below)
				tic 3 Feed lot	6 011	neid water :	supply	9 Dewatering	'' ²	MANA/_12
-	sw	sE	2 Irrigatio					tic) 10 Monitoring w		
	1	į		al/bacteriological	sample su	bmitted to L				mo/day/yr sample was
V L	5 51 4411/ 64/		Submitted	F 10/2	1	0 0		ater Well Disinfected?		
H	F BLANK Ó AS eel		D: IP (SR)	5 Wrought 6 Asbestos					S: Glued Welde	Clamped
1 Ste		_				9 Other	(specify bei	ow)		ded X
2 PV	/C	4 AB	S	7 Fiberglas	SS				nrea	ded J
Blank casin	g diameter	2	4 14	Ft., 1.5 Dia		ln. t	0	ft., Dia		in. toft.
Casing heig	t above land	surface	FLUSH	In., weight	SC	H 40	Lbs./f	t. Wall thickness or ga	auge No.	
1			TION MATERIAL:			7	PVC	10 Asbest	os-cemei	nt
1 Ste	eel		inless steel	5 Fibergla	ss	8	RMP (SR)	11 Other (specify)	
2 Bra			Ivanized steel	6 Concrete	e tile	. 9	ABS	12 None u		
1			NINGS ARE:							11 None (open hole)
,	ontinuous slot		3 Mill slot		6 Wire wi 7 Torch o			9 Drilled holes	`	
Z LO	uvered shutter		4 Key punched	145 #	to to	24 5	#	From	f +/)ft.
SCREEN-F	EKFORATED	INTERVA	From	ff	to		^{IL.}	From	ft to	
92	ND PACK INT	FRVALS:	From	13.5 ft.	tn	24.5	' ^(t)	From	ft. to	Ft.
0,1	IND I MORNIN	EITTI EO.	From							
6 GROUT	MATERIAL:	1 Ne	eat cement	2 Cement grou	+	3 Ben	tonite	4 Other		D Ft.
				Ft.		Ft.				
Grout Inten	vals From3	0	ft. to 11.	5 From2	11.	5 to				ft. toft.
1		•	ole contamination:	_				•		indoned water well
			4 Lateral line					l storage		
	ewer lines		5 Cess pool		Sewage la	agoon		ilizer storage		er (specify below)
1	atertight sewer	r lines	6 Seepage p	it 9	Feedyard			ecticide storage	Col	ntaminated Site
Direction fr		0005	1.471.14	01.0010.1.00		EDOM	How man	1	CINC IN	TEDVALS
FROM	TO	CODE		OLOGIC LOG		FROM	ТО	PLUG	OING IN	TERVALS
.5	.5 6.5		Concrete Clayey Silt (N	II) brown	moist					
6.5	9.5		Silty Clay(CL)), firm. mois	t		1			
9.5	12		Sand(sw) fine	-medium gi	rain					
12	13		Silty Clay(CL)	dark brow	n, firm					
13	19		Sand(SW) fin							
19	25 TD		Sand(SW)me		e grain					
25	TD		End Borehole	7		-				
7 00175	ACTORIO OD) I ANDON	NEDIO CEDTIFICA	TION: Th:	or wall	(v) comet-	atod (2) ===	constructed of (2) at	2004	or my juriodiation and
										er my jurisdiction and w
Completed	Controctor's	iconne M-	1/2	585		And tr				ge and belief. Kansas
			Associ				valer vveii h	Record was completed By (signature) Bra	i on (mo/c dlev .l	day/yr) 2/12/2009
INSTR	ousiness name RUCTIONS:. Pl	ease fill in b	lanks and circle the c	orrect answers. S	end three co	pies to Kans	as Departme	ent of Health and Enviror	nment, Bu	reau of Water, Topeka
			913-296-5545. Sen						.,	

Brooker