WAIER WELL REC	JUKD	Form W	WC-5	Divis	sion of Water	Resources App. No)	
1 LOCATION OF WATER WELL:		Fraction		Section	Number	Township No.	Range Number	
County: SZDCKWICK		SW 1/4 NW 1/4 SR	1/4.561 1/4		22	T 27 S		
	funknown distance &	Global Positioning System (GPS) information:						
					Latitude: (in decimal degrees)			
from nearest town or intersection: If at owner's address, check here . Latitude:								
1,110' WEST OF E. LEWIS & GROVE					Longitude: (in decimal degrees)			
STREETS					Elevation:			
Datum: WGS 84, NAD 83, NA							NAD 27	
2 WATER WELL OWNER: BRB CONTRACTORS, FNC					Collection Method:			
RR#, Street Address, Box #: 3805 NW 25TN STREET					GPS unit (Make/Model:)			
City, State, ZIP Code: TOPEKA, KS 66675					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
7 40/11, 100 000/3					Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m			
3 LOCATE WELL								
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL								
SECTION BOX:	Depth(s) Groundwater Encountered (1)							
N SECTION BOX.								
	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr6.//13/.0.9							
Pump test data: Well water wasft. after hours pumping gpm								
EST. YIELDgpm. Well water wasft. after hours pumpinggpm								
W Bore Hole Diameter 24 in. to 3.1 ft., and in. to ft.							ft.	
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
' '								
Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well								
						res 🔼 No		
S	If yes, mo/	day/yr sample was sub	omitted					
l mile Water well disinfected? ☐ Yes ☑ No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter								
Casing height above land surface								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ Other (Specify)								
			iole)					
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From 21 ft. to 31 ft., From ft. to ft.								
From								
GRAVEL PACK INTERVALS: From								
From								
COPOLITIMATERIAL DIVINA DE COMPANIA DE COM								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From								
What is the nearest source of possible contamination:								
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)								
Sewer lines								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well								
Direction from well						West		
FROM TO	LITHOLOG		FROM				GGING INTERVALS	
	7.102.00	1 ml 2 d	1.10.11	. ~		C (COM.) OI 1 LO	COMITO MILLIANTE	
	VIJCI + C	77	 				<i>p</i>	
10 27'	oppse StM.	Y GANUEL	 		ファナ	U (19)	Kepnesers	
27 31	CLAU				20	Wear N AT	77115	
					(.	CATION	•	
						-74 //	P	
			 					
			 					
		· · · · · · · · · · · · · · · · · · ·						
 			 					
5 COMPRIS STORES	N. A. A. B. D. C. S.	to opposite of the	NI TI	11	1C3:			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ★ constructed, □ reconstructed, or □ plugged								
under my jurisdiction and was completed on (mo/day/year) 6/13/.0.5 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No This Water Well Record was completed on (no hard)								
under the business name of 6 RIPPIN DEWATERING, NORTH CLATER LUCby (signature)								
INSTRUCTIONS: Use typew							answers Send three conies	
(white, blue, pink) to Kansas I								
Telephone 785-296-5522. Ser								
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								
				2.1.00	· · · · · · · · · · · · · · · · · · ·	, , <u></u>	pj, rim copy	